

## 16-Channel (2 Banks of 8-Channels), High Voltage Analog Switch

### Features

- ▶ HVCMOS® technology for high performance
- ▶ 220V operating conditions
- ▶ 22Ω typical output on-resistance
- ▶ 3.3 and 5.0V CMOS logic compatibility
- ▶ Very low quiescent power dissipation (-10μA)
- ▶ -45dB min off isolation at 7.5MHz
- ▶ Low parasitic capacitance
- ▶ Excellent noise immunity
- ▶ Flexible operating supply voltages
- ▶ 48-lead LQFP package

### Applications

- ▶ Medical ultrasound imaging
- ▶ Non-destructive evaluation


### General Description

The Supertex HV2631 is a 220V, 16-channel, high voltage analog switch integrated circuit (IC). The output switches are configured as 2 sets of 8 single pole, single throw, analog switches. The IC is intended to be used in applications requiring high voltage switching controlled by low voltage control signals, such as ultrasound imaging.

The 2 sets of 8 analog switches are controlled by 2 input logic controls,  $D_{IN1}$  and  $D_{IN2}$ . A logic high on  $D_{IN1}$  will turn on switches 0 to 7 and a logic high on  $D_{IN2}$  will turn on switches 8 to 15.

Using HVCMOS® technology, this device combines high voltage bilateral DMOS switches and low power CMOS logic to provide efficient control of high voltage analog signals.

### Block Diagram




**Ordering Information**

|               |  |
|---------------|--|
| <b>Device</b> | <b>48-Lead LQFP</b><br>7.00x7.00mm body<br>1.60mm height (max)<br>0.50mm pitch |
| HV2631        | HV2631FG-G   |

-G indicates package is RoHS compliant ("Green")



**Pin Configuration**



**48-Lead LQFP (FG)**  
(top view)

**Absolute Maximum Ratings**

| Parameter  | Value                              |
|--|------------------------------------|
| V <sub>DD</sub> logic supply                         | -0.5V to +7.0V                     |
| V <sub>PP</sub> -V <sub>NN</sub> differential supply | 225V                               |
| V <sub>PP</sub> positive supply                      | -0.5V to V <sub>NN</sub> +225V     |
| V <sub>NN</sub> negative supply                      | +0.5V to -225V                     |
| Logic input voltage                                  | -0.5V to V <sub>DD</sub> +0.3V     |
| Analog signal range                                  | V <sub>NN</sub> to V <sub>PP</sub> |
| Peak analog signal current/channel                   | 2.5A                               |
| Storage temperature                                  | -65°C to 150°C                     |
| Power dissipation                                    | 1.2W                               |

Absolute Maximum Ratings are those values beyond which damage to the device may occur. Functional operation under these conditions is not implied. Continuous operation of the device at the absolute rating level may affect device reliability. All voltages are referenced to device ground.

**Product Marking**

Top Marking

YY = Year Sealed  
WW = Week Sealed  
L = Lot Number

Bottom Marking

C = Country of Origin\*  
A = Assembler ID\*  
\_\_\_\_\_ = "Green" Packaging  
\*May be part of top marking

Package may or may not include the following marks: Si or

**48-Lead LQFP (FG)**

**Recommended Operating Conditions**

| Sym              | Parameter                          | Value  |
|------------------|------------------------------------|--|
| V <sub>DD</sub>  | Logic power supply voltage         | 3.0V to 5.5V                                 |
| V <sub>PP</sub>  | Positive driver supply             | +50V to +110V                                |
| V <sub>NN</sub>  | Negative high voltage supply       | -10V to V <sub>PP</sub> -220V                |
| V <sub>IH</sub>  | High level input voltage           | V <sub>DD</sub> -1.0V to V <sub>DD</sub>     |
| V <sub>IL</sub>  | Low-level input voltage            | 0V to 1.0V                                   |
| V <sub>SIG</sub> | Analog signal voltage peak-to-peak | V <sub>NN</sub> +10V to V <sub>PP</sub> -10V |
| T <sub>A</sub>   | Operating free air temperature     | 0°C to 70°C                                  |

- Notes:**
- Power up/down sequence is arbitrary except GND must be powered-up first and powered-down last.
  - V<sub>SIG</sub> must be V<sub>NN</sub> ≤ V<sub>SIG</sub> ≤ V<sub>PP</sub> or floating during power up/down transition.
  - Rise and fall times of power supplies V<sub>DD</sub>, V<sub>PP</sub> and V<sub>NN</sub> should not be less than 1.0msec.

## DC Electrical Characteristics

(Over recommended operating conditions unless otherwise specified)

| Sym                  | Parameter                                  | 0°C |      | +25°C |     |      | +70°C |      | Units | Conditions   |
|----------------------|--|-----|------|-------|-----|------|-------|------|-------|--|
|                      |  | Min | Max  | Min   | Typ | Max  | Min   | Max  |       |  |
| R <sub>ONS</sub>     | Small signal switch on-resistance          | -   | 30   | -     | 26  | 32   | -     | 40   | Ω     | V <sub>SIG</sub> = 0V, I <sub>SIG</sub> = 5.0mA, V <sub>PP</sub> = 50V, V <sub>NN</sub> = -170V  |
|                      |  | -   | 25   | -     | 22  | 27   | -     | 35   |       | V <sub>SIG</sub> = 0V, I <sub>SIG</sub> = 200mA, V <sub>PP</sub> = 50V, V <sub>NN</sub> = -170V  |
|                      |  | -   | 25   | -     | 22  | 27   | -     | 30   |       | V <sub>SIG</sub> = 0V, I <sub>SIG</sub> = 5.0mA, V <sub>PP</sub> = 110V, V <sub>NN</sub> = -110V |
|                      |  | -   | 20   | -     | 18  | 22   | -     | 25   |       | V <sub>SIG</sub> = 0V, I <sub>SIG</sub> = 200mA, V <sub>PP</sub> = 110V, V <sub>NN</sub> = -110V |
| ΔR <sub>ONS</sub>    | Small signal switch on-resistance matching | -   | 20   | -     | 5.0 | 20   | -     | 20   | %     | V <sub>SIG</sub> = 0V, I <sub>SIG</sub> = 5.0mA, V <sub>PP</sub> = 110V, V <sub>NN</sub> = -110V |
| R <sub>ONL</sub>     | Large signal switch on-resistance          | -   | -    | -     | 15  | -    | -     | -    | Ω     | V <sub>SIG</sub> = 0V, I <sub>SIG</sub> = 1.0A   |
| I <sub>SOL</sub>     | Switch off-leakage per switch              | -   | 5.0  | -     | 1.0 | 10   | -     | 15   | μA    | V <sub>SIG</sub> = V <sub>PP</sub> -10V, V <sub>NN</sub> = +10V                                  |
| V <sub>OS(OFF)</sub> | DC offset switch off                       | -   | 300  | -     | 100 | 300  | -     | 300  | mV    | R <sub>LOAD</sub> = 100kΩ  |
| V <sub>OS(ON)</sub>  | DC offset switch on                        | -   | 500  | -     | 100 | 500  | -     | 500  |       |  |
| I <sub>PPQ</sub>     | Quiescent V <sub>PP</sub> supply current   | -   | -    | -     | 10  | 50   | -     | -    | μA    | All switches off   |
| I <sub>NNQ</sub>     | Quiescent V <sub>NN</sub> supply current   | -   | -    | -     | -10 | -50  | -     | -    |       |  |
| I <sub>PPQ</sub>     | Quiescent V <sub>PP</sub> supply current   | -   | -    | -     | 10  | 50   | -     | -    | μA    | All switches on, I <sub>SW</sub> = 5.0mA   |
| I <sub>NNQ</sub>     | Quiescent V <sub>NN</sub> supply current   | -   | -    | -     | -10 | -50  | -     | -    |       |  |
| I <sub>SW</sub>      | Switch output peak current                 | -   | 2.0  | -     | -   | 2.0  | -     | 2.0  | A     | V <sub>SIG</sub> duty cycle < 0.1%   |
| f <sub>SW</sub>      | Output switching frequency                 | -   | -    | -     | -   | 50   | -     | -    | kHz   | Duty cycle = 50%   |
| I <sub>PP</sub>      | Average V <sub>PP</sub> supply current     | -   | 8.1  | -     | -   | 8.8  | -     | 10   | mA    | V <sub>PP</sub> = 50V, V <sub>NN</sub> = -170V, All switches turning on and off at 50kHz         |
| I <sub>NN</sub>      | Average V <sub>NN</sub> supply current     | -   | -8.1 | -     | -   | -8.8 | -     | -10  |       |  |
| I <sub>PP</sub>      | Average V <sub>PP</sub> supply current     | -   | 8.1  | -     | -   | 6.3  | -     | 6.9  | mA    | V <sub>PP</sub> = 110V, V <sub>NN</sub> = -110V, All switches turning on and off at 50kHz        |
| I <sub>NN</sub>      | Average V <sub>NN</sub> supply current     | -   | -8.1 | -     | -   | -6.3 | -     | -6.9 |       |  |
| I <sub>DDQ</sub>     | Quiescent V <sub>DD</sub> supply current   | -   | 10   | -     | -   | 10   | -     | 10   | μA    | All logic inputs are static  |
| I <sub>DD</sub>      | Average V <sub>DD</sub> supply current     | -   | 2.0  | -     | -   | 2.0  | -     | 2.0  | mA    | D <sub>IN1</sub> = D <sub>IN2</sub> = 3.0MHz, LE = high  |
| C <sub>IN</sub>      | Logic input capacitance                    | -   | 10   | -     | -   | 10   | -     | 10   | pF    | ---  |

## AC Electrical Characteristics

(Over recommended operating conditions unless otherwise specified)


| Sym               | Parameter                                | 0°C |     | +25°C |     |     | +70°C |     | Units | Conditions |
|-------------------|--|-----|-----|-------|-----|-----|-------|-----|-------|------------|
|                   |  | Min | Max | Min   | Typ | Max | Min   | Max |       |            |
| t <sub>WLE</sub>  | Time width of $\overline{LE}$            | 150 | -   | 150   | -   | -   | 150   | -   | ns    | ---        |
| t <sub>WDIN</sub> | Time width of D <sub>IN</sub>            | 150 | -   | 150   | -   | -   | 150   | -   | ns    | ---        |
| t <sub>SD</sub>   | Set up time before $\overline{LE}$ rises | 150 | -   | 150   | -   | -   | 150   | -   | ns    | ---        |

**AC Electrical Characteristics** (cont.)

(Over recommended operating conditions unless otherwise specified)

| Sym                  | Parameter                             | 0°C |     | +25°C |     |     | +70°C |     | Units | Conditions   |
|----------------------|---------------------------------------|-----|-----|-------|-----|-----|-------|-----|-------|--|
|                      |                                       | Min | Max | Min   | Typ | Max | Min   | Max |       |  |
| t <sub>ON</sub>      | Turn on time                          | -   | 5.0 | -     | -   | 5.0 | -     | 5.0 | μs    | V <sub>SIG</sub> = V <sub>PP</sub> -10V,<br>R <sub>LOAD</sub> = 10KΩ |
| t <sub>OFF</sub>     | Turn off time                         | -   | 5.0 | -     | -   | 5.0 | -     | 5.0 |       |  |
| dv/dt                | Maximum V <sub>SIG</sub> slew rate    | -   | 20  | -     | -   | 20  | -     | 20  | V/ns  | ---  |
| K <sub>O</sub>       | Off isolation                         | -30 | -   | -30   | -33 | -   | -30   | -   | dB    | f = 5.0MHz,<br>load = 1.0KΩ//15pF                                    |
|                      |                                       | -45 | -   | -45   | -50 | -   | -45   | -   |       | f = 7.5MHz, R <sub>LOAD</sub> = 50Ω                                  |
| K <sub>CR</sub>      | Switch crosstalk                      | -45 | -   | -45   | -   | -   | -45   | -   | dB    | f = 5.0MHz, R <sub>LOAD</sub> = 50Ω                                  |
| I <sub>ID</sub>      | Output switch isolation diode current | -   | 300 | -     | -   | 300 | -     | 300 | mA    | 300ns pulse width,<br>2.0% duty cycle                                |
| C <sub>SG(OFF)</sub> | Off capacitance SW to GND             | 5.0 | 17  | 5.0   | 12  | 17  | 5.0   | 17  | pF    | V <sub>SIG</sub> = 0V, f = 1.0MHz                                    |
| C <sub>SG(ON)</sub>  | On capacitance SW to GND              | 25  | 50  | 25    | 38  | 50  | 25    | 50  | pF    | V <sub>SIG</sub> = 0V, f = 1.0MHz                                    |
| +V <sub>SPK</sub>    | Output voltage spike                  | -   | -   | -     | 250 | -   | -     | -   | mV    | R <sub>LOAD</sub> = 50Ω  |
| -V <sub>SPK</sub>    |                                       | -   | -   | -     | 500 | -   | -     | -   |       |  |
| QC                   | Charge injection                      | -   | -   | -     | 770 | -   | -     | -   | PC    | V <sub>PP</sub> = +50V, V <sub>NN</sub> = -170V                      |
|                      |                                       | -   | -   | -     | 620 | -   | -     | -   |       | V <sub>PP</sub> = 110V, V <sub>NN</sub> = -110V                      |


**Logic Timing Waveforms**




**Truth Table**

| DIN2 | DIN1 | LE | SW0 to SW7          | SW8 to SW15 |
|------|------|----|---------------------|-------------|
| L    | L    | L  | OFF                 | OFF         |
| L    | H    | L  | ON                  | OFF         |
| H    | L    | L  | OFF                 | ON          |
| H    | H    | L  | ON                  | ON          |
| X    | X    | H  | Hold Previous State |             |


Test Circuits




Switch OFF Leakage




DC Offset ON/OFF




$T_{ON}/T_{OFF}$  Test Circuit




$K_O = 20 \text{Log} \frac{V_{OUT}}{V_{IN}}$   
OFF Isolation




Isolation Diode Current



$K_{CR} = 20 \text{Log} \frac{V_{OUT}}{V_{IN}}$   
Crosstalk



$Q = 1000\text{pF} \cdot \Delta V_{OUT}$   
Charge Injection




Output Voltage Spike

## Pin Configuration


| Pin | Function          | Pin | Function |
|-----|-------------------|-----|----------|
| 1   | VNN               | 25  | SW10     |
| 2   | N/C               | 26  | SW10     |
| 3   | VPP               | 27  | SW9      |
| 4   | N/C               | 28  | SW9      |
| 5   | D <sub>IN</sub> 1 | 29  | SW8      |
| 6   | $\overline{LE}$   | 30  | SW8      |
| 7   | D <sub>IN</sub> 2 | 31  | SW7      |
| 8   | N/C               | 32  | SW7      |
| 9   | N/C               | 33  | SW6      |
| 10  | VDD               | 34  | SW6      |
| 11  | GND               | 35  | SW5      |
| 12  | N/C               | 36  | SW5      |
| 13  | N/C               | 37  | SW4      |
| 14  | SW15              | 38  | N/C      |
| 15  | SW15              | 39  | SW4      |
| 16  | SW14              | 40  | N/C      |
| 17  | SW14              | 41  | SW3      |
| 18  | SW13              | 42  | SW3      |
| 19  | SW13              | 43  | SW2      |
| 20  | SW12              | 44  | SW2      |
| 21  | SW12              | 45  | SW1      |
| 22  | SW11              | 46  | SW1      |
| 23  | SW11              | 47  | SW0      |
| 24  | N/C               | 48  | SW0      |

# 48-Lead LQFP Package Outline (FG)


7.00x7.00mm body, 1.60mm height (max), 0.50mm pitch



**Top View**



**View B**



**Side View**

**Note:**  
 1. A Pin 1 identifier must be located in the index area indicated. The Pin 1 identifier can be: a molded mark/identifier; an embedded metal marker; or a printed indicator.

| Symbol         | A   | A1    | A2   | b    | D    | D1    | E     | E1    | e     | L        | L1   | L2       | θ        |    |
|----------------|-----|-------|------|------|------|-------|-------|-------|-------|----------|------|----------|----------|----|
| Dimension (mm) | MIN | 1.40* | 0.05 | 1.35 | 0.17 | 8.80* | 6.80* | 8.80* | 6.80* | 0.50 BSC | 0.45 | 1.00 REF | 0.25 BSC | 0° |
|                | NOM | -     | -    | 1.40 | 0.22 | 9.00  | 7.00  | 9.00  | 7.00  |          | 0.60 |          | 3.5°     |    |
|                | MAX | 1.60  | 0.15 | 1.45 | 0.27 | 9.20* | 7.20* | 9.20* | 7.20* |          | 0.75 |          | 7°       |    |

JEDEC Registration MS-026, Variation BBC, Issue D, Jan. 2001.  
 \* This dimension is not specified in the JEDEC drawing.

Drawings are not to scale.

Supertex Doc. #: DSPD-48LQFPFG Version, D041309.

(The package drawing(s) in this data sheet may not reflect the most current specifications. For the latest package outline information go to <http://www.supertex.com/packaging.html>.)

Supertex inc. does not recommend the use of its products in life support applications, and will not knowingly sell them for use in such applications unless it receives an adequate "product liability indemnification insurance agreement." Supertex inc. does not assume responsibility for use of devices described, and limits its liability to the replacement of the devices determined defective due to workmanship. No responsibility is assumed for possible omissions and inaccuracies. Circuitry and specifications are subject to change without notice. For the latest product specifications refer to the Supertex inc. website: <http://www.supertex.com>.

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Analogue Switch ICs](#) category:*

*Click to view products by [Microchip](#) manufacturer:*

Other Similar products are found below :

[FSA3051TMX](#) [NLAS4684FCTCG](#) [NLAS5223BLMNR2G](#) [NLX2G66DMUTCG](#) [425541DB](#) [425528R](#) [099044FB](#) [NLAS5123MNR2G](#)  
[PI5A4157CEX](#) [NLAS4717EPFCT1G](#) [PI5A3167CCEX](#) [SLAS3158MNR2G](#) [PI5A392AQE](#) [PI5A4157ZUEX](#) [PI5A3166TAEX](#) [FSA634UCX](#)  
[XS3A1T3157GMX](#) [TC4066BP\(N,F\)](#) [DG302BDJ-E3](#) [PI5A100QEX](#) [HV2605FG-G](#) [HV2301FG-G](#) [RS2117YUTQK10](#) [RS2118YUTQK10](#)  
[RS2227XUTQK10](#) [ADG452BRZ-REEL7](#) [MAX4066ESD+](#) [MAX391CPE+](#) [MAX4730EXT+T](#) [MAX314CPE+](#) [BU4066BCFV-E2](#)  
[MAX313CPE+](#) [BU4S66G2-TR](#) [NLASB3157MTR2G](#) [TS3A4751PWR](#) [NLAS4157DFT2G](#) [NLAST4599DFT2G](#) [NLAST4599DTT1G](#)  
[DG419LDY+T](#) [DG300BDJ-E3](#) [DG2503DB-T2-GE1](#) [TC4W53FU\(TE12L,F\)](#) [HV2201FG-G](#) [74HC2G66DC.125](#) [DG3257DN-T1-GE4](#)  
[ADG619BRMZ-REEL](#) [ADG1611BRUZ-REEL7](#) [DG2535EDQ-T1-GE3](#) [LTC201ACN#PBF](#) [74LV4066DB,118](#)