

Low Harmonic Distortion, 32-Channel, High Voltage Analog Switch Relay Replacement IC

Features

- ▶ 32-channel high voltage analog switch
- ▶ 2:1 multiplexer/demultiplexer
- ▶ Enable control for all-OFF state
- ▶ 3.3 or 5.0V CMOS input logic level
- ▶ HVCMOS technology for high performance
- ▶ Very low quiescent power dissipation, 10 μ A
- ▶ Low parasitic capacitance
- ▶ DC to 50MHz analog signal frequency
- ▶ -60dB typical OFF-isolation at 5.0MHz
- ▶ CMOS logic circuitry for low power
- ▶ Excellent noise immunity
- ▶ Flexible operating supply voltages
- ▶ 56-Lead 8x8 QFN package

Applications

- ▶ Electromechanical relay replacement in medical ultrasound probes.

General Description


The Supertex HV2809 is a low harmonic distortion, 32-channel, high voltage analog switch integrated circuit (IC), designed for use in medical ultrasound imaging systems as a probe selection relay replacement. It serves as a 16PDT (16-pole, double throw) high voltage analog switch array. The enable function allows the parts to be configured as either a 2:1 or 4:1 multiplexer/demultiplexer. The HV2809 is a very fast transducer multiplexer that consumes minimal power and emits no audible noise.

Using HVCMOS technology, this device combines high voltage bilateral DMOS switches and low power CMOS logic to provide efficient control of high voltage analog signals.

The device is suitable for various combinations of high voltage supplies, e.g., V_{PP}/V_{NN} : +40V/-160V, +100V/-100V, and +160V/-40V.

The HV2809 comes in an 8.0mm x 8.0mm x 1.0mm, 56-Lead QFN package. Compared to an electromechanical relay, it not only saves considerable PCB area, but also saves on the PCB assembled height.

Block Diagram



Ordering Information

Part Number	Package Options	Packing
HV2809K6-G	56-Lead (8x8) QFN	250/Tray
HV2809K6-G M937	56-Lead (8x8) QFN	2000/Reel

- G indicates package is RoHS compliant ('Green')




Absolute Maximum Ratings

Parameter	Value
V_{DD} logic supply	-0.5V to +6.5V
$V_{PP}-V_{NN}$ differential supply	220V
V_{PP} positive supply	-0.5V to V_{NN} +200V
V_{NN} negative supply	+0.5V to -200V
Logic input voltage	-0.5V to V_{DD} +0.3V
Analog signal range	V_{NN} to V_{PP}
Peak analog signal current/channel	3.0A
Storage temperature	-65°C to 150°C

Absolute Maximum Ratings are those values beyond which damage to the device may occur. Functional operation under these conditions is not implied. Continuous operation of the device at the absolute rating level may affect device reliability. All voltages are referenced to device ground.

Pin Configuration



56-Lead QFN
(top view)

Product Marking

• HV2809K6	L = Lot Number
LLLLLLLL	YY = Year Sealed
YYWW	WW = Week Sealed
AAA CCC	A = Assembler ID
	C = Country of Origin
	= "Green" Packaging

Package may or may not include the following marks: Si or

56-Lead QFN

Typical Thermal Resistance

Package	θ_{ja}
56-Lead QFN	21°C/W

Recommended Operating Conditions

Sym	Parameter	Value
V_{DD}	Logic power supply voltage	3.0 to 5.5V
V_{PP}	Positive high voltage supply	+40 to V_{NN} +200V
V_{NN}	Negative high voltage supply	-40 to -160V
V_{IH}	High level input voltage	0.9 V_{DD} to V_{DD}
V_{IL}	Low level input voltage	0 to 0.1 V_{DD}
V_{SIG}	Analog signal voltage peak-to-peak	V_{NN} +10V to V_{PP} -10V
T_A	Operating free air temperature	0 to 70°C

Notes:

- Power up/down sequence is arbitrary except GND must be powered-up first and powered-down last.
- V_{SIG} must be $V_{NN} \leq V_{SIG} \leq V_{PP}$ or floating during power up/down transition.
- Rise and fall times of power supplies V_{DD} , V_{PP} and V_{NN} should not be less than 1.0msec.

DC Electrical Characteristics (Over recommended operating conditions unless otherwise specified)

Sym	Parameter	0°C		+25°C		+70°C		Unit	Conditions
		Min	Max	Min	Typ	Max	Min		
R_{ONS}	Small signal switch ON-resistance	-	30	-	26	38	-	48	Ω
		-	25	-	22	27	-	32	
		-	25	-	22	27	-	30	
		-	18	-	18	24	-	27	
		-	23	-	20	25	-	30	
		-	22	-	16	25	-	27	
ΔR_{ONS}	Small signal switch ON-resistance matching	-	20	-	5.0	20	-	20	%
R_{ONL}	Large signal switch ON-resistance	-	-	-	15	-	-	-	Ω
I_{SOL}	Switch OFF-leakage per switch	-	5.0	-	1.0	10	-	15	μA
V_{OS}	DC offset switch OFF	-	300	-	100	300	-	300	mV
	DC offset switch ON	-	500	-	100	500	-	500	
I_{PPQ}	Quiescent V_{PP} supply current	-	-	-	10	50	-	-	μA
I_{NNQ}	Quiescent V_{NN} supply current	-	-	-	-10	-50	-	-	
I_{PPQ}	Quiescent V_{PP} supply current	-	-	-	10	50	-	-	μA
I_{NNQ}	Quiescent V_{NN} supply current	-	-	-	-10	-50	-	-	
I_{SW}	Switch output peak current	-	3.0	-	3.0	2.0	-	2.0	A
f_{sw}	Output switching frequency	-	-	-	-	50	-	-	kHz
I_{PP}	Average V_{PP} supply current	-	13	-	-	14	-	16	mA
		-	8.0	-	-	10	-	11	
		-	8.0	-	-	10	-	11	
I_{NN}	Average V_{NN} supply current	-	13	-	-	14	-	16	mA
		-	8.0	-	-	10	-	11	
		-	8.0	-	-	10	-	11	
I_{DD}	V_{DD} supply current	-	0.1	-	-	0.1	-	0.1	mA
I_{DDQ}	Quiescent V_{DD} supply current	-	10	-	-	10	-	10	μA
C_{IN}	Logic input capacitance	-	10	-	-	10	-	10	pF

* See Test Circuits on page 5

AC Electrical Characteristics (Over recommended operating conditions unless otherwise specified)










Sym	Parameter	0°C		+25°C		+70°C		Unit	Conditions
		Min	Max	Min	Typ	Max	Min		
t_{ON}	Turn ON time	-	30	-	15	30	-	30	μs
t_{OFF}	Turn OFF time	-	30	-	15	30	-	30	
dv/dt	Maximum V_{SIG} slew rate	-	20	-	-	20	-	20	V/ns
		-	20	-	-	20	-	20	
		-	20	-	-	20	-	20	
K_O	OFF isolation	-30	-	-30	-33	-	-30	-	dB
		-58	-	-58	-	-	-58	-	
K_{CR}	Switch crosstalk	-60	-	-60	-70	-	-60	-	dB
I_{ID}	Output switch isolation diode current	-	300	-	-	300	-	300	mA
$C_{SG(OFF)}$	OFF capacitance SW to GND	-	14	-	9.0	14	-	14	pF
	OFF capacitance Y to GND	-	28	-	18	28	-	28	
$C_{SG(ON)}$	ON capacitance SW to GND	-	33	-	23	33	-	33	pF
	ON capacitance Y to GND	-	33	-	23	33	-	33	
$+V_{SPK}$	Output voltage spike SW	-	250	-	-	250	-	250	mV
		-	250	-	-	250	-	250	
		-	250	-	-	250	-	250	
		-	250	-	-	250	-	250	
		-	250	-	-	250	-	250	
		-	250	-	-	250	-	250	
$-V_{SPK}$	Output voltage spike Y	-	250	-	-	250	-	250	mV
		-	250	-	-	250	-	250	
		-	250	-	-	250	-	250	
		-	250	-	-	250	-	250	
		-	250	-	-	250	-	250	
		-	250	-	-	250	-	250	
QC	Charge injection	-	-	-	1020	-	-	-	pC
		-	-	-	700	-	-	-	
		-	-	-	370	-	-	-	

* See Test Circuits on page 5

Truth Table

Logic Inputs		Switch Status
EN	A/B	
H	H	SW0, 2, 4...30 ON, SW1, 3, 5...31 OFF
H	L	SW0, 2, 4...30 OFF, SW1, 3, 5...31 ON
L	X	All switches OFF

Test Circuits



Pin Function

Pin	Function
1	Y2829
2	SW29
3	SW30
4	Y3031
5	SW31
6	ENABLE
7	VDD
8	A/B
9	GND
10	SW0
11	Y01
12	SW1
13	SW2
14	Y23

Pin	Function
15	SW3
16	SW4
17	Y45
18	SW5
19	SW6
20	Y67
21	SW7
22	SW8
23	Y89
24	SW9
25	SW10
26	Y1011
27	SW11
28	SW12


Pin	Function
29	Y1213
30	SW13
31	VNN
32	SW14
33	Y1415
34	SW15
35	VPP
36	VPP
37	SW16
38	Y1617
39	SW17
40	VNN
41	SW18
42	Y1819

Pin	Function
43	SW19
44	SW20
45	Y2021
46	SW21
47	SW22
48	Y2223
49	SW23
50	SW24
51	Y2425
52	SW25
53	SW26
54	Y2627
55	SW27
56	SW28

VSUB (Thermal Pad)	The central thermal pad on the bottom of package must be connected to VNN externally
--------------------	--

56-Lead QFN Package Outline (K6)

8.00x8.00mm body, 1.00mm height (max), 0.50mm pitch



Notes:

1. A Pin 1 identifier must be located in the index area indicated. The Pin 1 identifier can be: a molded mark/identifier; an embedded metal marker; or a printed indicator.
2. Depending on the method of manufacturing, a maximum of 0.15mm pullback (L1) may be present.
3. The inner tip of the lead may be either rounded or square.

Symbol	A	A1	A3	b	D	D2	E	E2	e	L	L1	θ	
Dimension (mm)	MIN	0.80	0.00	0.20 REF	0.18	7.85*	2.75	7.85*	2.75	0.50 BSC	0.30	0.00	0°
	NOM	0.90	0.02		0.25	8.00	5.70	8.00	5.70		0.40	-	-
	MAX	1.00	0.05		0.30	8.15*	6.70†	8.15*	6.70†		0.50	0.15	14°

JEDEC Registration MO-220, Variation VLLD-2, Issue K, June 2006.

* This dimension is not specified in the JEDEC drawing.

† This dimension differs from the JEDEC drawing.

Drawings are not to scale.

Supertex Doc.#: DSPD-56QFNK68X8P050, Version A031010.

(The package drawing(s) in this data sheet may not reflect the most current specifications. For the latest package outline information go to <http://www.supertex.com/packaging.html>.)

Supertex inc. does not recommend the use of its products in life support applications, and will not knowingly sell them for use in such applications unless it receives an adequate "product liability indemnification insurance agreement." **Supertex inc.** does not assume responsibility for use of devices described, and limits its liability to the replacement of the devices determined defective due to workmanship. No responsibility is assumed for possible omissions and inaccuracies. Circuitry and specifications are subject to change without notice. For the latest product specifications refer to the **Supertex inc.** (website: <http://www.supertex.com>)

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Analogue Switch ICs](#) category:

Click to view products by [Microchip manufacturer:](#)

Other Similar products are found below :

[FSA3051TMX](#) [NLAS4684FCTCG](#) [NLAS5223BLMNR2G](#) [NLVAS4599DTT1G](#) [NLX2G66DMUTCG](#) [425541DB](#) [425528R](#) [099044FB](#)
[NLAS5123MNR2G](#) [PI5A4157CEX](#) [NLAS4717EPFCT1G](#) [PI5A3167CCEX](#) [SLAS3158MNR2G](#) [PI5A392AQE](#) [PI5A4157ZUEX](#)
[PI5A3166TAEX](#) [FSA634UCX](#) [XS3A1T3157GMX](#) [TC4066BP\(N,F\)](#) [DG302BDJ-E3](#) [PI5A100QEX](#) [HV2605FG-G](#) [HV2301FG-G](#)
[RS2117YUTQK10](#) [RS2118YUTQK10](#) [RS2227XUTQK10](#) [ADG452BRZ-REEL7](#) [MAX4066ESD+](#) [MAX391CPE+](#) [MAX4730EXT+T](#)
[MAX314CPE+](#) [BU4066BCFV-E2](#) [MAX313CPE+](#) [BU4S66G2-TR](#) [NLASB3157MTR2G](#) [TS3A4751PWR](#) [NLAS4157DFT2G](#)
[NLAST4599DFT2G](#) [NLAST4599DTT1G](#) [DG419LDY+T](#) [DG300BDJ-E3](#) [DG2503DB-T2-GE1](#) [TC4W53FU\(TE12L,F\)](#) [HV2201FG-G](#)
[74HC2G66DC.125](#) [DG3257DN-T1-GE4](#) [ADG619BRMZ-REEL](#) [ADG1611BRUZ-REEL7](#) [DG2535EDQ-T1-GE3](#) [LTC201ACN#PBF](#)