



# MIC94060/61/62/63

## High Side Power Switches

### General Description

The MIC94060-63 are high-side load switches designed for operation between 1.7V to 5.5V. The devices contain a low on-resistance P-channel MOSFET that supports over 2A of continuous current. The MIC94061 and MIC94063 features an active load discharge circuit which insures capacitive loads retain no charge when the main switch is in an OFF state.

MIC94060-61 feature rapid turn on while MIC94062-63 provide a slew rate controlled Soft-Start turn-on of 800 $\mu$ s (typical) to prevent in-rush current from glitching supply rails.

An active pull-down on the enable input keeps MIC94060-63 in a default OFF state until the EN pin is pulled to a high level. Built-in level shift circuitry allows low voltage logic signals to switch higher supply voltages, or vice versa; high level logic signals can control low level voltages.

MIC94060-63's operating voltage range makes them suitable for 1-cell Lithium ion and 2- to 3-cell NiMH/NiCad/Alkaline powered systems, as well as, all 5V applications. Their low operating current of 2 $\mu$ A and low shutdown current of <1 $\mu$ A maximize battery life.

Data sheets and support documentation can be found on Micrel's web site at: [www.micrel.com](http://www.micrel.com).


### Features

- 1.7V to 5.5V input voltage range
- 2A continuous operating current
- 77m $\Omega$  (typ)  $R_{DS(ON)}$
- Built-in level shift for control logic; can be operated by 1.5V logic.
- Low 2 $\mu$ A quiescent current
- Soft-Start: MIC94062-63
- Micro-power shutdown <1 $\mu$ A
- Load discharge circuit: MIC94061, MIC94063
- Space saving 1.2mm x 1.6mm Thin MLF<sup>®</sup> package


### Applications

- Load switch in portable applications:
  - Cellular phones
  - PDAs
  - MP3 players
  - Digital Cameras
  - Portable instrumentation
- Battery switch-over circuits
- Level translator

### Typical Application



**MIC94060, 62**  
Load Switch Application



**MIC94061, 63**  
Load Switch with Capacitive Load Discharge


## Ordering Information

| Part Number |             | Part Marking <sup>(1)</sup> |             | Soft-Start | Load Discharge | Package                                      |
|-------------|-------------|-----------------------------|-------------|------------|----------------|--|
| Standard    | Pb-Free     | Standard                    | Pb-Free     |            |                |  |
| MIC94060BC6 | MIC94060YC6 | P54                         | <u>P</u> 54 |            |                | SC-70-6                                      |
| MIC94061BC6 | MIC94061YC6 | P55                         | <u>P</u> 55 |            | •              |  |
| MIC94062BC6 | MIC94062YC6 | P56                         | <u>P</u> 56 | •          |                |  |
| MIC94063BC6 | MIC94063YC6 | P57                         | <u>P</u> 57 | •          | •              |  |
| —           | MIC94060YMT | —                           | P54         |            |                | 1.2mm x 1.6mm<br>Thin MLF <sup>®</sup> (2,3) |
| —           | MIC94061YMT | —                           | P55         |            | •              |  |
| —           | MIC94062YMT | —                           | P56         | •          |                |  |
| —           | MIC94063YMT | —                           | P57         | •          | •              |  |


### Notes

- Underbar symbol on SC-70 Pb-free packages may not be to scale.
- MLF<sup>®</sup> ▲ = Pin 1 identifier.
- MLF<sup>®</sup> is a GREEN RoHS compliant package. Lead finish is NiPdAu. Mold compound is Halogen Free.

## Pin Configuration



SC-70-6 (C6)



Top View

1.2x1.6 mm Thin MLF<sup>®</sup> (MT)

## Pin Description

| Pin Number |     | Pin Name         | Pin Function   |
|------------|-----|------------------|--|
| SC-70      | MLF |                  |  |
| 1          | 1   | V <sub>OUT</sub> | Drain of P-channel MOSFET.   |
| 2,5        | 2   | GND              | Ground and the backside pad (MLF only) should both be connected to electrical ground.                    |
| 4          | 3   | V <sub>IN</sub>  | Source of P-channel MOSFET.  |
| 3          | 4   | EN               | Enable (Input): Active-high CMOS compatible control input for switch A. Do not leave floating.           |
| 6          | --  | NIC              | No Internal Connection. A signal or voltage applied to this pin will have no effect on device operation. |

**Absolute Maximum Ratings** <sup>(1)</sup>

|   |                   |
|---|-------------------|
| Input Voltage ( $V_{IN}$ )                        | +6V               |
| Enable Voltage ( $V_{EN}$ )                       | +6V               |
| Continuous Drain Current ( $I_D$ ) <sup>(3)</sup> |                   |
| $T_A = 25^\circ\text{C}$                          | $\pm 2\text{A}$   |
| $T_A = 85^\circ\text{C}$                          | $\pm 1.4\text{A}$ |
| Pulsed Drain Current ( $I_{DP}$ ) <sup>(4)</sup>  | $\pm 6\text{A}$   |
| Continuous Diode Current ( $I_S$ ) <sup>(4)</sup> | -50mA             |
| Storage Temperature ( $T_S$ )                     | -55°C to +150°C   |
| ESD Rating – HBM <sup>(6)</sup>                   | 4KV               |

**Operating Ratings** <sup>(2)</sup>

|  |                 |
|--|-----------------|
| Input Voltage ( $V_{IN}$ )                   | +1.7 to +5.5V   |
| Junction Temperature ( $T_A$ )               | -40°C to +125°C |
| Package Thermal Resistance                   |                 |
| SC-70-6 ( $\theta_{JA}$ )                    | 240°C/W         |
| 1.2x1.6 MLF ( $\theta_{JA}$ )                | 172°C/W         |
| 1.2x1.6 MLF ( $\theta_{JC}$ ) <sup>(3)</sup> | 134°C/W         |

**Electrical Characteristics**

$V_{IN} = 5\text{V}$ ;  $T_A = 25^\circ\text{C}$ , bold values indicate  $-40^\circ\text{C} \leq T_A \leq +85^\circ\text{C}$ , unless noted.

| Symbol         | Parameter  | Condition  | Min | Typ | Max | Units         |
|----------------|--|--|-----|-----|-----|---------------|
| $V_{EN\_TH}$   | Enable Threshold Voltage                                     | $V_{IN} = 1.8\text{V to } 4.5\text{V}, I_D = -250\mu\text{A}$                      | 0.5 |     | 1.2 | V             |
|                |  | $V_{IN} = 1.7\text{V to } 4.5\text{V}, I_D = -250\mu\text{A}$                      | 0.4 |     | 1.2 | V             |
| $I_{EN}$       | Enable Input Current   | $V_{IN} = V_{EN} = 5.5\text{V}$  |     | 2   | 4   | $\mu\text{A}$ |
| $I_{VIN}$      | OFF State Leakage Current                                    | $V_{IN} = +5.5\text{V}, V_{EN} = 0\text{V}$  |     |     | 1   | $\mu\text{A}$ |
| $R_{DS(ON)}$   | P-Channel Drain to Source ON Resistance<br><br>SC-70 Package | $V_{IN} = +4.5\text{V}, I_D = -100\text{mA}, V_{EN} = 1.5\text{V}$                 |     | 77  | 110 | m $\Omega$    |
|                |  | $V_{IN} = +3.6\text{V}, I_D = -100\text{mA}, V_{EN} = 1.5\text{V}$                 |     | 85  | 115 | m $\Omega$    |
|                |  | $V_{IN} = +2.5\text{V}, I_D = -100\text{mA}, V_{EN} = 1.5\text{V}$                 |     | 100 | 140 | m $\Omega$    |
|                |  | $V_{IN} = +1.8\text{V}, I_D = -100\text{mA}, V_{EN} = 1.5\text{V}$                 |     | 145 | 200 | m $\Omega$    |
|                |  | $V_{IN} = +1.7\text{V}, I_D = -100\text{mA}, V_{EN} = 1.5\text{V}$                 |     | 155 | 215 | m $\Omega$    |
| $R_{DS(ON)}$   | P-Channel Drain to Source ON Resistance<br><br>MLF Package   | $V_{IN} = +4.5\text{V}, I_D = -100\text{mA}, V_{EN} = 1.5\text{V}$                 |     | 85  | 115 | m $\Omega$    |
|                |  | $V_{IN} = +3.6\text{V}, I_D = -100\text{mA}, V_{EN} = 1.5\text{V}$                 |     | 100 | 140 | m $\Omega$    |
|                |  | $V_{IN} = +2.5\text{V}, I_D = -100\text{mA}, V_{EN} = 1.5\text{V}$                 |     | 145 | 200 | m $\Omega$    |
|                |  | $V_{IN} = +1.8\text{V}, I_D = -100\text{mA}, V_{EN} = 1.5\text{V}$                 |     | 155 | 215 | m $\Omega$    |
|                |  | $V_{IN} = +1.7\text{V}, I_D = -100\text{mA}, V_{EN} = 1.5\text{V}$                 |     | 165 | 225 | m $\Omega$    |
| $R_{SHUTDOWN}$ | Turn-Off Resistance  | $V_{IN} = +3.6\text{V}, I_{TEST} = 1\text{mA}, V_{EN} = 0\text{V}$<br>MIC94061, 63 |     | 200 | 300 | $\Omega$      |

**Dynamic**

| Symbol         | Parameter          | Condition  | Min | Typ  | Max  | Units         |
|----------------|--------------------|--|-----|------|------|---------------|
| $t_{ON\_DLY}$  | Turn-On Delay Time | $V_{IN} = +3.6\text{V}, I_D = -100\text{mA}, V_{EN} = 1.5\text{V}$<br>MIC94060, 61 |     | 0.85 | 1.5  | $\mu\text{s}$ |
|                |                    | $V_{IN} = +3.6\text{V}, I_D = -100\text{mA}, V_{EN} = 1.5\text{V}$<br>MIC94062, 63 |     | 700  | 1200 | $\mu\text{s}$ |
| $t_{ON\_RISE}$ | Turn-On Rise Time  | $V_{IN} = +3.6\text{V}, I_D = -100\text{mA}, V_{EN} = 1.5\text{V}$<br>MIC94060, 61 | 0.5 | 1    | 5    | $\mu\text{s}$ |
|                |                    | $V_{IN} = +3.6\text{V}, I_D = -100\text{mA}, V_{EN} = 1.5\text{V}$<br>MIC94062, 63 | 500 | 800  | 1500 | $\mu\text{s}$ |













**Dynamic (Continued)**

|                       |                     |  |     |     |    |
|-----------------------|---------------------|--|-----|-----|----|
| t <sub>OFF_DLY</sub>  | Turn-Off Delay Time | V <sub>IN</sub> = +3.6V, I <sub>D</sub> = -100mA, V <sub>EN</sub> = 1.5V<br>MIC94060, 61 | 100 | 200 | ns |
|                       |                     | V <sub>IN</sub> = +3.6V, I <sub>D</sub> = -100mA, V <sub>EN</sub> = 1.5V<br>MIC94062, 63 | 60  | 200 | ns |
| t <sub>OFF_FALL</sub> | Turn-Off Fall Time  | V <sub>IN</sub> = +3.6V, I <sub>D</sub> = -100mA, V <sub>EN</sub> = 1.5V<br>MIC94060, 61 | 60  | 100 | ns |
|                       |                     | V <sub>IN</sub> = +3.6V, I <sub>D</sub> = -100mA, V <sub>EN</sub> = 1.5V<br>MIC94062, 63 | 60  | 100 | ns |

**Notes:**





1. Exceeding the absolute maximum rating may damage the device.
2. The device is not guaranteed to function outside its operating rating.
3. With backside thermal contact to PCB.
4. Pulse width <300μs with < 2% duty cycle.
5. Continuous body diode current conduction (reverse conduction, i.e. V<sub>OUT</sub> to V<sub>IN</sub>) is not recommended.
6. Devices are ESD sensitive. Handling precautions recommended. HBM (Human body model), 1.5kΩ in series with 100pF.

# Typical Characteristics







# Functional Characteristics





## MIC94060



# MIC94061







# MIC94062








**MIC94063**



# Package Information



6-Pin SC-70 (C6)




SIDE VIEW

4-Pin Thin MLF® (MT)

- NOTE:
1. ALL DIMENSIONS ARE IN MILLIMETERS.
  2. MAX. PACKAGE WARPAGE IS 0.05 mm.
  3. MAXIMUM ALLOWABLE BURRS IS 0.076 mm IN ALL DIRECTIONS.
  4. PIN #1 ID ON TOP WILL BE LASER/INK MARKED.
- △ DIMENSION APPLIES TO METALIZED TERMINAL AND IS MEASURED BETWEEN 0.20 AND 0.25 mm FROM TERMINAL TIP.
- △ APPLIED ONLY FOR TERMINALS.
- △ APPLIED FOR EXPOSED PAD AND TERMINALS.

### Recommended Land Pattern for MLF 1.2x1.6 4 Lead



Optional for maximum thermal performance. Heatsink should be connected to GND plane of PCB for maximum thermal performance.

Disclaimer: This is only a recommendation based on information available to Micrel from its suppliers. Actual land pattern may have to be significantly different due to various materials and processes used in PCB assembly. Micrel makes no representation or warranty of performance based on the recommended land pattern."

**MICREL, INC. 2180 FORTUNE DRIVE SAN JOSE, CA 95131 USA**  
 TEL +1 (408) 944-0800 FAX +1 (408) 474-1000 WEB <http://www.micrel.com>

The information furnished by Micrel in this data sheet is believed to be accurate and reliable. However, no responsibility is assumed by Micrel for its use. Micrel reserves the right to change circuitry and specifications at any time without notification to the customer.

Micrel Products are not designed or authorized for use as components in life support appliances, devices or systems where malfunction of a product can reasonably be expected to result in personal injury. Life support devices or systems are devices or systems that (a) are intended for surgical implant into the body or (b) support or sustain life, and whose failure to perform can be reasonably expected to result in a significant injury to the user. A Purchaser's use or sale of Micrel Products for use in life support appliances, devices or systems is a Purchaser's own risk and Purchaser agrees to fully indemnify Micrel for any damages resulting from such use or sale.

© 2004 Micrel, Incorporated.

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for* [Power Switch ICs - Power Distribution category:](#)

*Click to view products by* [Microchip manufacturer:](#)

Other Similar products are found below :

[AP22652AW6-7](#) [MAPDCC0001](#) [L9349TR-LF](#) [MAPDCC0005](#) [NCP45520IMNTWG-L](#) [VND5050K-E](#) [MP6205DD-LF-P](#) [FPF1018](#) [DS1222](#)  
[NCV380HMUAJAATBG](#) [TCK2065G,LF](#) [SZNCP3712ASNT3G](#) [L9781TR](#) [NCP45520IMNTWG-H](#) [MC17XS6500BEK](#) [SP2526A-1EN-L/TR](#)  
[SP2526A-2EN-L/TR](#) [MAX4999ETJ+T](#) [MC22XS4200BEK](#) [L9347LF-TR](#) [MAX14575BETA+T](#) [VN1160C-1-E](#) [VN750PEP-E](#) [TLE7244SL](#)  
[L9352B-TR-LF](#) [BTS50060-1EGA](#) [MAX1693HEUB+T](#) [MC07XSG517EK](#) [TLE7237SL](#) [MIC2033-05BYMT-T5](#) [MIC2033-12AYMT-T5](#)  
[MIC2033-05BYM6-T5](#) [MP6513GJ-P](#) [NCP3902FCCTBG](#) [AP22811BW5-7](#) [SLG5NT1437VTR](#) [SZNCP3712ASNT1G](#) [NCV330MUTBG](#)  
[DML1008LDS-7](#) [MAX4987AEETA+T](#) [KTS1670EDA-TR](#) [MAX1694EUB+T](#) [KTS1640QGDV-TR](#) [KTS1641QGDV-TR](#) [IPS160HTR](#)  
[BTS500251TADATMA2](#) [MC07XS6517BEKR2](#) [SIP43101DQ-T1-E3](#) [DML10M8LDS-13](#) [MAX1922ESA+C71073](#)