

**MSCSM70VM10C4AG**

**Datasheet**

**Vienna Rectifier Phase Leg SiC Power  
Module**

April 2020



# Contents

---

<b>1 Revision History.....</b>	<b>1</b>
Revision 1.0.....	.1
<b>Product Overview.....</b>	<b>2</b>
2.1 Features.....	3
2.2 Benefits.....	3
2.3 Applications.....	3
<b>Electrical Specifications.....</b>	<b>4</b>
3.1 SiC MOSFET Characteristics (per SiC MOSFET).....	4
3.2 SiC Schottky Diode Ratings Characteristics (per SiC Diode).....	6
3.3 Diode Characteristics.....	7
3.4 Thyristor Characteristics.....	7
3.5 Thermal and Package Characteristics.....	8
3.6 Typical SiC MOSFET Performance Curves.....	9
3.7 Typical SiC Diode Performance Curves.....	11
3.8 Typical CR1 Diode Curves.....	12
<b>Package Specification.....</b>	<b>13</b>

# Tables

---

Table 1 • Absolute Maximum Ratings.....	4
Table 2 • Electrical Characteristics.....	4
Table 3 • Dynamic Characteristics.....	5
Table 4 • Body Diode Ratings and Characteristics.....	5
Table 5 • Absolute Maximum Ratings.....	6
Table 6 • SiC Schottky Diode Ratings and Characteristics.....	6
Table 7 • Absolute Maximum Ratings.....	7
Table 8 • Electrical Characteristics.....	7
Table 9 • Absolute Maximum Ratings.....	7
Table 10 • Electrical Characteristics.....	8
Table 11 • Package Characteristics.....	8

# Figures

---

Figure 1 • MSCSM70VM10C4AG Electrical Schematic.....	2
Figure 2 • MSCSM70VM10C4AG Pinout Location.....	2
Figure 3 • Maximum Thermal Impedance.....	9
Figure 4 • Output Characteristics at $T_J = 25\text{ }^{\circ}\text{C}$ .....	9
Figure 5 • Output Characteristics at $T_J = 175\text{ }^{\circ}\text{C}$ .....	9
Figure 6 • Normalized RDS(on) vs. Temperature.....	9
Figure 7 • Transfer Characteristics.....	9
Figure 8 • Capacitance vs. Drain Source Voltage.....	10
Figure 9 • Gate Charge vs. Gate Source Voltage.....	10
Figure 10 • Body Diode Char, $T_J = 25\text{ }^{\circ}\text{C}$ .....	10
Figure 11 • 3rd Quadrant Char, $T_J = 25\text{ }^{\circ}\text{C}$ .....	10
Figure 12 • Body Diode Char, $T_J = 175\text{ }^{\circ}\text{C}$ .....	10
Figure 13 • 3rd Quadrant Char, $T_J = 175\text{ }^{\circ}\text{C}$ .....	10
Figure 14 • Switching Energy vs. Current.....	11
Figure 15 • Turn-on Energy vs. $R_g$ .....	11
Figure 16 • Operating Frequency vs. Drain Current.....	11
Figure 17 • Turn-off Energy vs. $R_g$ .....	11
Figure 18 • Maximum Thermal Impedance.....	11
Figure 19 • Forward Characteristics.....	12
Figure 20 • Capacitance vs. Reverse Voltage.....	12
Figure 21 • Maximum Thermal Impedance.....	12
Figure 22 • Forward Characteristics.....	12
Figure 23 • Package Outline.....	13

# 1 Revision History

---

The revision history describes the changes that were implemented in the document. The changes are listed by revision, starting with the most current publication.


## 1.1 Revision 1.0

Revision 1.0 is the first publication of this document, published in April 2020.


## 2 Product Overview

The MSCSM70VM10C4AG is Vienna Rectifier phase leg 700 V/241 A full Silicon Carbide power module.

**Figure 1 • MSCSM70VM10C4AG Electrical Schematic**



**Figure 2 • MSCSM70VM10C4AG Pinout Location**



All ratings at  $T_J = 25^\circ\text{C}$  unless otherwise specified.

**Caution:** These devices are sensitive to electrostatic discharge. Proper handling procedures should be followed.

## 2.1 Features

The following are key features of the MSCSM70VM10C4AG device:

- SiC Power MOSFET
  - Low RDS(on)
  - High temperature performance
- Silicon carbide (SiC) Schottky diode (CR2 and CR3)
  - Zero reverse recovery
  - Zero forward recovery
  - Temperature-independent switching behavior
  - Positive temperature coefficient on VF
- Kelvin emitter for easy drive
- Very low stray inductance
- High level of integration
- Aluminum nitride (AlN) substrate for improved thermal performance

## 2.2 Benefits

The following are benefits of the MSCSM70VM10C4AG device:

- Outstanding performance at high-frequency operation
- Direct mounting to heatsink (isolated package)
- Low junction-to-case thermal resistance
- Solderable terminals both for power and signal for easy PCB mounting
- Low profile
- RoHS compliant

## 2.3 Applications

The MSCSM70VM10C4AG device is designed for the following applications:

- Plasma and induction heating
- Uninterruptible power supplies

## 3 Electrical Specifications

This section shows the electrical specifications of the MSCSM70VM10C4AG device.

### 3.1 SiC MOSFET Characteristics (per SiC MOSFET)

This section describes the electrical characteristics of the MSCSM70VM10C4AG (Q1 and Q2) device.

**Table 1 • Absolute Maximum Ratings**

Symbol	Parameter	Maximum Ratings		Unit
$V_{DSS}$	Drain-source voltage	700		V
$I_D$	Continuous drain current	$T_C = 25\text{ }^\circ\text{C}$	238	A
		$T_C = 80\text{ }^\circ\text{C}$	189	
$I_{DM}$	Pulsed drain current	476		
$V_{GS}$	Gate-source voltage	−10/25		V
$R_{DSon}$	Drain-source ON resistance	9.5		$\text{m}\Omega$
$P_D$	Power dissipation	$T_C = 25\text{ }^\circ\text{C}$	674	W

**Table 2 • Electrical Characteristics**

Symbol	Characteristic	Test Conditions		Min	Typ	Max	Unit
$I_{DSS}$	Zero gate voltage drain current	$V_{GS} = 0\text{ V}$ ; $V_{DS} = 700\text{ V}$				200	$\mu\text{A}$
$R_{DSon}$	Drain–source on resistance	$V_{GS} = 20\text{ V}$	$T_J = 25\text{ }^\circ\text{C}$		7.5	9.5	$\text{m}\Omega$
		$I_D = 80\text{ A}$	$T_J = 175\text{ }^\circ\text{C}$		9.5		
$V_{GS(\text{th})}$	Gate threshold voltage	$V_{GS} = V_{DS}$ , $I_D = 8\text{ mA}$		1.9	2.4		V
$I_{GSS}$	Gate–source leakage current	$V_{GS} = 20\text{ V}$ , $V_{DS} = 0\text{ V}$				200	nA

**Table 3 • Dynamic Characteristics**

Symbol	Characteristic	Test Conditions	Min	Typ	Max	Unit
$C_{iss}$	Input capacitance	$V_{GS} = 0 \text{ V}$ $V_{DS} = 700 \text{ V}$ $f = 1 \text{ MHz}$		9000		pF
$C_{oss}$	Output capacitance			1020		
$C_{rss}$	Reverse transfer capacitance			58		
$Q_g$	Total gate charge	$V_{GS} = -5/20 \text{ V}$ $V_{Bus} = 470 \text{ V}$ $I_D = 80 \text{ A}$		430		nC
$Q_{gs}$	Gate-source charge			116		
$Q_{gd}$	Gate-drain charge			70		
$T_{d(on)}$	Turn-on delay time	$V_{GS} = -5/20 \text{ V}$ $V_{Bus} = 400 \text{ V}$ $I_D = 160 \text{ A}$ $T_J = 150 \text{ }^\circ\text{C}$ $R_{Gon} = 13.5 \Omega$ ; $R_{Goff} = 2.4 \Omega$		40		ns
$T_r$	Rise time			35		
$T_{d(off)}$	Turn-off delay time			50		
$T_f$	Fall time			20		
$E_{on}$	Turn on energy		$T_J = 150 \text{ }^\circ\text{C}$		1090	μJ
$E_{off}$	Turn off energy	$V_{GS} = -5/20 \text{ V}$ $V_{Bus} = 400 \text{ V}$ $I_D = 160 \text{ A}$ $R_{Gon} = 13.5 \Omega$ $R_{Goff} = 2.4 \Omega$	$T_J = 150 \text{ }^\circ\text{C}$		372	μJ
$R_{Gint}$	Internal gate resistance				2.8	Ω
$R_{thJC}$	Junction-to-case thermal resistance				0.222	°C/W

**Table 4 • Body Diode Ratings and Characteristics**

Symbol	Characteristic	Test Conditions	Min	Typ	Max	Unit
$V_{SD}$	Diode forward voltage	$V_{GS} = 0 \text{ V}$ ; $I_{SD} = 80 \text{ A}$		3.4		V
		$V_{GS} = -5 \text{ V}$ ; $I_{SD} = 80 \text{ A}$		3.8		
$t_{rr}$	Reverse recovery time	$I_{SD} = 80 \text{ A}$ ; $V_{GS} = -5 \text{ V}$ $V_R = 400 \text{ V}$ ; $dI_F/dt = 2000 \text{ A}/\mu\text{s}$		38		ns
$Q_{rr}$	Reverse recovery charge			636		
$I_{rr}$	Reverse recovery current			29.6		A

### 3.2 SiC Schottky Diode Ratings Characteristics (per SiC Diode)

This section shows the SiC Schottky diode (CR2 and CR3) ratings and characteristics of the device.

**Table 5 • Absolute Maximum Ratings**

Symbol	Parameter	Max Ratings		Unit
$V_{RRM}$	Peak repetitive reverse voltage	700		V
$I_F$	DC forward current	$T_C = 70^\circ\text{C}$	100	A
$P_D$	Power dissipation	$T_C = 25^\circ\text{C}$	322	W

**Table 6 • SiC Schottky Diode Ratings and Characteristics**

Symbol	Characteristic	Test Conditions		Min	Typ	Max	Unit
$V_{RRM}$	Peak repetitive reverse voltage					700	V
$I_{RRM}$	Reverse leakage current	$V_R = 700 \text{ V}$	$T_J = 25^\circ\text{C}$		30	400	$\mu\text{A}$
			$T_J = 175^\circ\text{C}$		500		
$V_F$	Diode forward voltage	$I_F = 100 \text{ A}$	$T_J = 25^\circ\text{C}$		1.5	1.8	V
			$T_J = 175^\circ\text{C}$		1.9		
$Q_C$	Total capacitive charge	$V_R = 400 \text{ V}$		266			nC
$C$	Total capacitance	$f = 1 \text{ MHz}, V_R = 200 \text{ V}$		496			pF
			$f = 1 \text{ MHz}, V_R = 400 \text{ V}$		432		
$R_{thJC}$	Junction-to-case thermal resistance				0.466		$^\circ\text{C}/\text{W}$

### 3.3 Diode Characteristics

This section shows the electrical characteristics and ratings of the CR1 diode.

**Table 7 • Absolute Maximum Ratings**

Symbol	Parameter			Max Ratings	Unit
$V_{RRM}$	Peak repetitive reverse voltage			1600	V
$I_F$	DC forward current	$T_C = 80^\circ\text{C}$		200	A
$I_{FSM}$	Non-repetitive forward surge current	$t = 10 \text{ ms}$	$T_J = 25^\circ\text{C}$	1600	
$P_D$	Power dissipation	$T_C = 25^\circ\text{C}$		400	W

**Table 8 • Electrical Characteristics**

Symbol	Characteristic	Test Conditions	Min	Typ	Max	Unit
$I_R$	Reverse current	$V_R = 1600 \text{ V}$			50	$\mu\text{A}$
$V_F$	Forward voltage	$I_F = 77 \text{ A}$	$T_J = 25^\circ\text{C}$	1	1.21	V
			$T_J = 125^\circ\text{C}$	0.9	1.1	
$V_T$	On-state voltage				0.83	V
$r_T$	On-state slope resistance				2.2	$\text{m}\Omega$
$R_{thJC}$	Junction-to-case thermal resistance				0.32	$^\circ\text{C}/\text{W}$

### 3.4 Thyristor Characteristics

This section shows the electrical characteristics and ratings of the thyristor (Q3).

**Table 9 • Absolute Maximum Ratings**

Symbol	Parameter			Max Ratings	Unit
$V_{DRM}$	Repetitive peak reverse voltage			1600	V
$I_{DRM}$	Repetitive peak reverse current			3	mA
$I_{TRMS}$	RMS on-state current	$T_C = 100^\circ\text{C}$		60	A
$I_{TSM}$	Surge on-state current	$t = 10 \text{ ms}$	$T_J = 45^\circ\text{C}$	520	
$V_{RGM}$	Peak reverse gate voltage			10	V
$P_D$	Power dissipation	$T_C = 25^\circ\text{C}$		357	W

**Table 10 • Electrical Characteristics**

Symbol	Characteristic	Test Conditions		Min	Typ	Max	Unit
$V_T$	On-state Voltage	$I_T = 60 \text{ A}$	$T_J = 25^\circ\text{C}$	1.41	0.85	10	V
$V_{TO}$	Direct on state threshold voltage		$T_J = 125^\circ\text{C}$				
$r_T$	On-state Slope resistance		$T_J = 125^\circ\text{C}$				$\text{m}\Omega$
$V_{GT}$	Gate trigger voltage		$T_J = 25^\circ\text{C}$		1.5		V
$I_{GT}$	Gate trigger current				50		mA
$R_{thJC}$	Junction-to-case thermal resistance					0.35	$^\circ\text{C}/\text{W}$

### 3.5 Thermal and Package Characteristics

This section shows the thermal and package characteristics of the device.


**Table 11 • Package Characteristics**

Symbol	Characteristic	Min	Max	Unit		
$V_{ISOL}$	RMS Isolation Voltage, any terminal to case t =1 min, 50/60 Hz	4000		V		
$T_J$	Operating junction temperature range	-40	150	$^\circ\text{C}$		
	Q3, CR1	-40	175			
$T_{JOP}$	Recommended junction temperature under switching conditions	-40	$T_{Jmax} - 25$			
$T_{STG}$	Storage temperature range	-40	125			
$T_C$	Operating case temperature	-40	125			
Torque	Mounting torque	To Heatsink	M5	2.5	4.7	N.m
Weight	Package weight			160		g


### 3.6 Typical SiC MOSFET Performance Curves

This section shows the typical performance curves of the MSCSM70VM10C4AG SiC MOSFET.


**Figure 3 • Maximum Thermal Impedance**




**Figure 4 • Output Characteristics at  $T_J = 25^{\circ}\text{C}$**




**Figure 5 • Output Characteristics at  $T_J = 175^{\circ}\text{C}$**













**Figure 6 • Normalized RDS(on) vs. Temperature**



**Figure 7 • Transfer Characteristics**




**Figure 8 • Capacitance vs. Drain Source Voltage****Figure 9 • Gate Charge vs. Gate Source Voltage****Figure 10 • Body Diode Char,  $T_J = 25^\circ\text{C}$** **Figure 11 • 3<sup>rd</sup> Quadrant Char,  $T_J = 25^\circ\text{C}$** **Figure 12 • Body Diode Char,  $T_J = 175^\circ\text{C}$** **Figure 13 • 3<sup>rd</sup> Quadrant Char,  $T_J = 175^\circ\text{C}$** 



**Figure 14 • Switching Energy vs. Current****Figure 15 • Turn-on Energy vs. Rg****Figure 16 • Operating Frequency vs. Drain Current****Figure 17 • Turn-off Energy vs. Rg**

### 3.7

### Typical SiC Diode Performance Curves

This section shows the typical performance curves of the MSCSM70VM10C4AG SiC diodes (CR2 and CR3).



**Figure 18 • Maximum Thermal Impedance**

**Figure 19 • Forward Characteristics****Figure 20 • Capacitance vs. Reverse Voltage**

### 3.8

#### Typical CR1 Diode Curves


This section shows the typical performance curves of the MSCSM70VM10C4AG CR1 diode.

**Figure 21 • Maximum Thermal Impedance****Figure 22 • Forward Characteristics**

## 4 Package Specification

This section shows the package outline of the MSCSM70VM10C4AG device. All dimensions are in millimeters.

### Figure 23 • Package Outline



See application note APT0501 - Mounting Instructions for SP4 Power Modules on [www.microsemi.com](http://www.microsemi.com).



**Microsemi**  
2355 W. Chandler Blvd.  
Chandler, AZ 85224 USA

Within the USA: +1 (480) 792-7200  
Fax: +1 (480) 792-7277

[www.microsemi.com](http://www.microsemi.com) © 2020 Microsemi and its corporate affiliates. All rights reserved. Microsemi and the Microsemi logo are trademarks of Microsemi Corporation and its corporate affiliates. All other trademarks and service marks are the property of their respective owners.

Microsemi's product warranty is set forth in Microsemi's Sales Order Terms and Conditions. Information contained in this publication is provided for the sole purpose of designing with and using Microsemi products. Information regarding device applications and the like is provided only for your convenience and may be superseded by updates. Buyer shall not rely on any data and performance specifications or parameters provided by Microsemi. It is your responsibility to ensure that your application meets with your specifications. THIS INFORMATION IS PROVIDED "AS IS." MICROSEMI MAKES NO REPRESENTATIONS OR WARRANTIES OF ANY KIND WHETHER EXPRESS OR IMPLIED, WRITTEN OR ORAL, STATUTORY OR OTHERWISE, RELATED TO THE INFORMATION, INCLUDING BUT NOT LIMITED TO ITS CONDITION, QUALITY, PERFORMANCE, NON-INFRINGEMENT, MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. IN NO EVENT WILL MICROSEMI BE LIABLE FOR ANY INDIRECT, SPECIAL, PUNITIVE, INCIDENTAL OR CONSEQUENTIAL LOSS, DAMAGE, COST OR EXPENSE WHATSOEVER RELATED TO THIS INFORMATION OR ITS USE, HOWEVER CAUSED, EVEN IF MICROSEMI HAS BEEN ADVISED OF THE POSSIBILITY OR THE DAMAGES ARE FORESEEABLE. TO THE FULLEST EXTENT ALLOWED BY LAW, MICROSEMI'S TOTAL LIABILITY ON ALL CLAIMS IN RELATED TO THIS INFORMATION OR ITS USE WILL NOT EXCEED THE AMOUNT OF FEES, IF ANY, YOU PAID DIRECTLY TO MICROSEMI FOR THIS INFORMATION. Use of Microsemi devices in life support, mission-critical equipment or applications, and/or safety applications is entirely at the buyer's risk, and the buyer agrees to defend and indemnify Microsemi from any and all damages, claims, suits, or expenses resulting from such use. No licenses are conveyed, implicitly or otherwise, under any Microsemi intellectual property rights unless otherwise stated.

Microsemi Corporation, a subsidiary of Microchip Technology Inc. (Nasdaq: MCHP), and its corporate affiliates are leading providers of smart, connected and secure embedded control solutions. Their easy-to-use development tools and comprehensive product portfolio enable customers to create optimal designs which reduce risk while lowering total system cost and time to market. These solutions serve more than 120,000 customers across the industrial, automotive, consumer, aerospace and defense, communications and computing markets. Headquartered in Chandler, Arizona, the company offers outstanding technical support along with dependable delivery and quality. Learn more at [www.microsemi.com](http://www.microsemi.com).

MSCC-0344-DS-01075

# X-ON Electronics

Largest Supplier of Electrical and Electronic Components

***Click to view similar products for Discrete Semiconductor Modules category:***

***Click to view products by Microchip manufacturer:***

Other Similar products are found below :

[M252511FV](#) [M254043](#) [DD260N12K-A](#) [DD380N16A](#) [DDB6U144N16R](#) [DDB6U145N16L](#) [DR7306](#) [APT20M11JFLL](#) [APT2X101DL40J](#)  
[APT2X21DC60J](#) [APT2X30D40J](#) [APT2X30D60J](#) [APT2X31DQ120J](#) [APT39M60J](#) [APT47M60J](#) [APT50DF170HJ](#) [APT50M50JLL](#)  
[APT50M75JLLU3](#) [APT50N60JCCU2](#) [APT58M80J](#) [APT80F60J](#) [DZ540N26K](#) [B522F-2-YEC](#) [MSTC90-16](#) [MT16HTF12864AZ-800G1](#)  
[MT18HTF12872PZ-667G1](#) [MT18HTF25672FDZ-667H1D6](#) [MT18HTF25672PZ-80EH1](#) [MT18RTF25672FDZ-667H1D6](#)  
[MT36HTF51272FZ-667H1D4](#) [MT36HTF51272FZ-667H1D6](#) [MT8HTF12864HTZ-667H1](#) [MT9HTF6472PZ-667G1](#) [MT9HVF12872PZ-80EH1](#) [MT9HVF6472PZ-667G1](#) [ND104N16K](#) [25.163.0653.1](#) [25.163.2453.0](#) [25.163.4253.0](#) [25.190.2053.0](#) [25.194.3453.0](#) [25.320.4853.1](#)  
[25.320.5253.1](#) [25.325.3653.1](#) [25.326.3253.1](#) [25.326.3553.1](#) [25.330.1653.1](#) [25.330.4753.1](#) [25.330.5253.1](#) [25.334.3253.1](#)