




Power Matters.TM

VRF152G

50V, 300W, 175MHz

RF POWER VERTICAL MOSFET

The VRF152G is designed for broadband commercial and military applications at frequencies to 175MHz. The high power, high gain, and broadband performance of this device make possible solid state transmitters for FM broadcast or TV channel frequency bands.



FEATURES

- Improved Ruggedness $V_{(BR)DSS} = 130V$
- 300W with 16dB Typical Gain @ 175MHz, 50V
- Excellent Stability & Low IMD
- Common Source Configuration
- RoHS Compliant
- 5:1 Load VSWR Capability at Specified Operating Conditions
- Nitride Passivated
- Refractory Gold Metallization
- High Efficiency Replacement for MRF151G

Maximum Ratings

All Ratings: $T_c = 25^\circ\text{C}$ unless otherwise specified

Symbol	Parameter	VRF152G	Unit
V_{DSS}	Drain-Source Voltage	130	V
I_D	Continuous Drain Current @ $T_c = 25^\circ\text{C}$	40	A
V_{GS}	Gate-Source Voltage	± 40	V
P_D	Total Device dissipation @ $T_c = 25^\circ\text{C}$	500	W
T_{STG}	Storage Temperature Range	-65 to 150	$^\circ\text{C}$
T_J	Operating Junction Temperature	200	

Static Electrical Characteristics

Symbol	Parameter	Min	Typ	Max	Unit
$V_{(BR)DSS}$	Drain-Source Breakdown Voltage ($V_{GS} = 0V$, $I_D = 100\text{mA}$)	130			
$R_{DS(ON)}$	Drain-Source On-State Resistance ($I_{D(ON)} = 10\text{A}$, $V_{GS} = 10\text{V}$)		.13	.20	V
I_{DSS}	Zero Gate Voltage Drain Current ($V_{DS} = 50\text{V}$, $V_{GS} = 0\text{V}$)			50	μA
I_{GSS}	Gate-Source Leakage Current ($V_{DS} = \pm 20\text{V}$, $V_{GS} = 0\text{V}$)			1.0	μA
g_{fs}	Forward Transconductance ($V_{DS} = 10\text{V}$, $I_D = 10\text{A}$)	5.0	6.2		mhos
$V_{GS(TH)}$	Gate Threshold Voltage ($V_{DS} = 10\text{V}$, $I_D = 100\text{mA}$)	2.9	3.6	4.4	V

Thermal Characteristics

Symbol	Characteristic	Min	Typ	Max	Unit
$R_{\theta JC}$	Junction to Case Thermal Resistance			0.35	$^\circ\text{C/W}$

CAUTION: These Devices are Sensitive to Electrostatic Discharge. Proper Handling Procedures Should Be Followed.

Dynamic Characteristics

VRF152G

Symbol	Parameter	Test Conditions	Min	Typ	Max	Unit
C_{iss}	Input Capacitance	$V_{GS} = 0V$ $V_{DS} = 50V$ $f = 1MHz$		383		pF
C_{oss}	Output Capacitance			215		
C_{rss}	Reverse Transfer Capacitance			18		

Functional Characteristics

Symbol	Parameter	Min	Typ	Max	Unit
G_{PS}	$f = 175MHz, V_{DD} = 50V, I_{DQ} = 500mA, P_{out} = 300W$	14	16		dB
η_D	$f = 175MHz, V_{DD} = 50V, I_{DQ} = 500mA, P_{out} = 300W$	50	55		%
Ψ	$f = 175MHz, V_{DD} = 50V, I_{DQ} = 500mA, P_{out} = 300W$ 5:1VSWR - All Phase Angles	No Degradation in Output Power			

1. To MIL-STD-1311 Version A, test method 2204B, Two Tone, Reference Each Tone

Microsemi reserves the right to change, without notice, the specifications and information contained herein.

Typical Performance Curves




FIGURE 1, Output Characteristics




FIGURE 2, Transfer Characteristics




FIGURE 3, Capacitance vs Drain-to-Source Voltage




FIGURE 4, Forward Safe Operating Area

Typical Performance Curves

VRF152G




Figure 5. Maximum Effective Transient Thermal Impedance Junction-to-Case vs Pulse Duration




Figure 7, 175 MHz Test Circuit

R1 - 100 Ohms, 1/2 W

R2 - 1.0 k Ohm, 1/2W

C1 - Arco 424

C3,C4,C7,C8,C9 - 1000 pF Chip


C5, C10 - 0.1 μ F ChipC11 - 0.47 μ F Ceramic Chip, Kemet 1215 or Equivalent (100V)

C12 - Arco 422

L1 - 10 Turns AWG #18 Enamelled Wire. Close Wound, 1/4" I.D.

L2 - Ferrite Beads of Suitable Material for 1.5 - 2.0 μ H Inductance
Unless Otherwise Noted, All Chip Capacitors are ATC Type 100
or Equivalent.T1 - 9:1 RF Transformer, Can be made of 15 - 18 Ohms
Semirigid Co - Ax, 62 - 90 Mils O.D.T2 - 1:4 RF Transformer, Can be made of 16 - 18 Ohms Semirigid
Co - Ax, 70 - 90 Mils O.D.Board Material - 0.062" Fiberglass (G10), 1 oz. Copper Clad, 2
sides, $\epsilon_r = 5.0$ NOTE: For stability, the input transformer T1 must be loaded with
ferrite toroids or beads to increase the common mode inductance.
For operation below 100 MHz. The same is required for the output
transformer.

- Pin 1. Drain
2. Drain
3. Gate
4. Gate
5. Source



HAZARDOUS MATERIAL WARNING

The ceramic portion of the device between leads and mounting flange is beryllium oxide. Beryllium oxide dust is highly toxic when inhaled. Care must be taken during handling and mounting to avoid damage to this area. These devices must never be thrown away with general industrial or domestic waste.

Package Dimensions (inches)
All Dimensions are $\pm .005$

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for RF MOSFET Transistors category:

Click to view products by Microchip manufacturer:

Other Similar products are found below :

[MRF492](#) [MRFE8VP8600HR5](#) [ARF1511](#) [ARF465BG](#) [BF 2030 E6814](#) [BLF861A](#) [DU1215S](#) [DU28200M](#) [UF28100M](#) [DU2820S](#) [MRF426](#)
[ARF468AG](#) [ARF468BG](#) [MAPHST0045](#) [DU2860U](#) [MRFE6VP5300NR1](#) [BF2040E6814HTSA1](#) [LET9060S](#) [MRF136Y](#) [BF999E6327HTSA1](#)
[SD2931-12MR](#) [BF998E6327HTSA1](#) [AFT05MS006NT1](#) [MRF141](#) [MRF171](#) [MRF172](#) [MRF174](#) [SD2942](#) [QPD1020SR](#) [BF 1005S E6327](#)
[MRF134](#) [MRF136](#) [MRF137](#) [MRF141G](#) [MRF151A](#) [MRF151G](#) [MRF157](#) [MRF158](#) [MRF160](#) [MRF166C](#) [MRF171A](#) [MRF177](#) [UF2840G](#)
[TGF3021-SM](#) [ARF1510](#) [ARF448BG](#) [ARF449AG](#) [ARF466BG](#) [VRF150](#) [VRF3933](#)