

Features

- Low Leakage
- Low Clamping Voltage
- Moisture Sensitivity Level 1
- Halogen Free. "Green" Device (Note 1)
- Epoxy Meets UL 94 V-0 Flammability Rating
- Lead Free Finish/RoHS Compliant ("P" Suffix Designates RoHS Compliant. See Ordering Information)

ESD Protection Device

Maximum Ratings


IEC61000-4-2 (ESD)	Air	$\pm 30\text{KV}$
	Contact	$\pm 30\text{KV}$
Peak Pulse Power (8/20 μs) ^(Note 2)	P_{PK}	250W
Operating Junction Temperature Range	T_J	-55°C to +150°C
Storage Temperature Range	T_{STG}	-55°C to +150°C

Note :


1. Halogen free "Green" products are defined as those which contain <900ppm bromine, <900ppm chlorine (<1500ppm total Br + Cl) and <1000ppm antimony compounds.

2. Non-repetitive current pulse 8/20 μs exponential decay waveform according to IEC61000-4-5.

Internal Structure




Marking Code




MCC Part No.	Device Code
ESD3V3T2B	3B.
ESD7V0T2B	7B.
ESD12VT2B	12B.
ESD15VT2B	15B.
ESD24VT2B	6RS.
ESD27VT2B	27B.
ESD36VT2B	36B.

SOT-23




DIM	INCHES		MM		NOTE
	MIN	MAX	MIN	MAX	
A	0.110	0.120	2.80	3.04	
B	0.083	0.104	2.10	2.64	
C	0.047	0.055	1.20	1.40	
D	0.034	0.041	0.85	1.05	
E	0.067	0.083	1.70	2.10	
F	0.018	0.024	0.45	0.60	
G	0.0004	0.006	0.01	0.15	
H	0.035	0.043	0.90	1.10	
J	0.003	0.007	0.08	0.18	
K	0.012	0.020	0.30	0.51	
L	0.007	0.020	0.20	0.50	

Suggested Solder Pad Layout



Symbol	Parameter
V_{RWM}	Peak Reverse Working Voltage
I_R	Reverse Leakage Current @ VRWM
V_{BR}	Breakdown Voltage @ IT
IT	Test Current
I_{PP}	Maximum Reverse Peak Pulse Current
V_C	Clamping Voltage @ IPP
P_{PK}	Peak Pulse Power
C_J	Junction Capacitance



Electrical Characteristics @ 25°C (Unless Otherwise Specified)

ESD3V3T2B

Parameter	Symbol	Conditions	Min.	Typ.	Max.	Units
Reverse Working Voltage	V_{RWM}				3.3	V
Reverse Breakdown Voltage	V_{BR}	$I_T=1\text{mA}$	5			V
Reverse Leakage Current	I_R	$V_{RWM}=3.3\text{V}$			0.5	μA
Clamping Voltage ^{Note1}	V_C	$I_{PP}=1\text{A}, t_p=8/20\mu\text{s}$			9	V
Clamping Voltage ^{Note1}	V_C	$I_{PP}=25\text{A}, t_p=8/20\mu\text{s}$			16	V
Junction Capacitance	C_J	$V_R=0\text{V}, f=1\text{MHz}$		100		pF
Dynamic Resistance ^{Note2}	R_{DYN}	TLP, $t_p=100\text{ns}$		0.18		Ω

ESD7V0T2B

Parameter	Symbol	Conditions	Min.	Typ.	Max.	Units
Reverse Working Voltage	V_{RWM}				7	V
Reverse Breakdown Voltage	V_{BR}	$I_T=1\text{mA}$	7			V
Reverse Leakage Current	I_R	$V_{RWM}=7\text{V}$			0.5	μA
Clamping Voltage ^{Note1}	V_C	$I_{PP}=1\text{A}, t_p=8/20\mu\text{s}$			13	V
Clamping Voltage ^{Note1}	V_C	$I_{PP}=17\text{A}, t_p=8/20\mu\text{s}$			15	V
Junction Capacitance	C_J	$V_R=0\text{V}, f=1\text{MHz}$		65		pF
Dynamic Resistance ^{Note2}	R_{DYN}	TLP, $t_p=100\text{ns}$		0.37		Ω

ESD12VT2B

Parameter	Symbol	Conditions	Min.	Typ.	Max.	Units
Reverse Working Voltage	V_{RWM}				12	V
Reverse Breakdown Voltage	V_{BR}	$I_T=1\text{mA}$	13			V
Reverse Leakage Current	I_R	$V_{RWM}=12\text{V}$			0.5	μA
Clamping Voltage ^{Note1}	V_C	$I_{PP}=1\text{A}, t_p=8/20\mu\text{s}$			20	V
Clamping Voltage ^{Note1}	V_C	$I_{PP}=10\text{A}, t_p=8/20\mu\text{s}$			30	V
Junction Capacitance	C_J	$V_R=0\text{V}, f=1\text{MHz}$		35		pF
Dynamic Resistance ^{Note2}	R_{DYN}	TLP, $t_p=100\text{ns}$		0.28		Ω

ESD15VT2B

Parameter	Symbol	Conditions	Min.	Typ.	Max.	Units
Reverse Working Voltage	V_{RWM}				15	V
Reverse Breakdown Voltage	V_{BR}	$I_T=1\text{mA}$	16			V
Reverse Leakage Current	I_R	$V_{RWM}=15\text{V}$			0.5	μA
Clamping Voltage ^{Note1}	V_C	$I_{PP}=1\text{A}, t_p=8/20\mu\text{s}$			20	V
Clamping Voltage ^{Note1}	V_C	$I_{PP}=9\text{A}, t_p=8/20\mu\text{s}$			30	V
Junction Capacitance	C_J	$V_R=0\text{V}, f=1\text{MHz}$		30		pF
Dynamic Resistance ^{Note2}	R_{DYN}	TLP, $t_p=100\text{ns}$		0.4		Ω

ESD24VT2B

Parameter	Symbol	Conditions	Min.	Typ.	Max.	Units
Reverse Working Voltage	V_{RWM}				24	V
Reverse Breakdown Voltage	V_{BR}	$I_T=1\text{mA}$	26			V
Reverse Leakage Current	I_R	$V_{RWM}=24\text{V}$			0.5	μA
Clamping Voltage ^{Note1}	V_C	$I_{PP}=1\text{A}, t_p=8/20\mu\text{s}$			34	V
Clamping Voltage ^{Note1}	V_C	$I_{PP}=7\text{A}, t_p=8/20\mu\text{s}$			44	V
Junction Capacitance	C_J	$V_R=0\text{V}, f=1\text{MHz}$		20		pF
Dynamic Resistance ^{Note2}	R_{DYN}	TLP, $t_p=100\text{ns}$		0.83		Ω

ESD27VT2B

Parameter	Symbol	Conditions	Min.	Typ.	Max.	Units
Reverse Working Voltage	V_{RWM}				27	V
Reverse Breakdown Voltage	V_{BR}	$I_T=1\text{mA}$	31			V
Reverse Leakage Current	I_R	$V_{RWM}=27\text{V}$			0.5	μA
Clamping Voltage ^{Note1}	V_C	$I_{PP}=1\text{A}, t_p=8/20\mu\text{s}$			50	V
Clamping Voltage ^{Note1}	V_C	$I_{PP}=6\text{A}, t_p=8/20\mu\text{s}$			70	V
Junction Capacitance	C_J	$V_R=0\text{V}, f=1\text{MHz}$		15		pF
Dynamic Resistance ^{Note2}	R_{DYN}	TLP, $t_p=100\text{ns}$		1.1		Ω

ESD36VT2B







Parameter	Symbol	Conditions	Min.	Typ.	Max.	Units
Reverse Working Voltage	V_{RWM}				36	V
Reverse Breakdown Voltage	V_{BR}	$I_T=1\text{mA}$	38			V
Reverse Leakage Current	I_R	$V_{RWM}=36\text{V}$			0.5	μA
Clamping Voltage ^{Note1}	V_C	$I_{PP}=1\text{A}, t_p=8/20\mu\text{s}$			55	V
Clamping Voltage ^{Note1}	V_C	$I_{PP}=5\text{A}, t_p=8/20\mu\text{s}$			90	V
Junction Capacitance	C_J	$V_R=0\text{V}, f=1\text{MHz}$		13		pF
Dynamic Resistance ^{Note2}	R_{DYN}	TLP, $t_p=100\text{ns}$		0.9		Ω

Note :

1. Non-repetitive current pulse 8/20 μs exponential decay waveform according to IEC61000-4-5.

2. TLP parameter: $Z_0=50\Omega$, $t_p=100\text{ns}$, $t_r=2\text{ns}$, averaging window from 60ns to 80ns. RDYN is calculated from 4A to 16A.

Curve Characteristics



Ordering Information

Device	Packing
Part Number-TP	Tape&Reel: 3Kpcs/Reel

IMPORTANT NOTICE

Micro Commercial Components Corp. reserves the right to make changes without further notice to any product herein to make corrections, modifications , enhancements , improvements , or other changes . **Micro Commercial Components Corp.** does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights ,nor the rights of others . The user of products in such applications shall assume all risks of such use and will agree to hold **Micro Commercial Components Corp.** and all the companies whose products are represented on our website, harmless against all damages. **Micro Commercial Components Corp.** products are sold subject to the general terms and conditions of commercial sale, as published at
<https://www.mccsemi.com/Home/TermsAndConditions>.

LIFE SUPPORT

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

CUSTOMER AWARENESS

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. **MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources.** MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Micro Commercial Components (MCC) manufacturer:

Other Similar products are found below :

[1.5KE100A-TP](#) [1.5KE110A-TP](#) [1.5KE150A-TP](#) [1.5KE150CA-TP](#) [1.5KE15CA-TP](#) [1.5KE200A-TP](#) [1.5KE200CA-TP](#) [1.5KE20A-TP](#)
[1.5KE20CA-TP](#) [1.5KE220A-TP](#) [1.5KE220CA-TP](#) [1.5KE22A-TP](#) [1.5KE22CA-TP](#) [1.5KE24A-TP](#) [1.5KE24CA-TP](#) [1.5KE250A-TP](#)
[1.5KE250CA-TP](#) [1.5KE27A-TP](#) [1.5KE27CA-TP](#) [1.5KE300CA-TP](#) [1.5KE30A-TP](#) [1.5KE30CA-TP](#) [1.5KE33A-TP](#) [1.5KE33CA-TP](#)
[1.5KE350CA-TP](#) [1.5KE36A-BP](#) [1.5KE36A-TP](#) [1.5KE400A-TP](#) [1.5KE400CA-TP](#) [1.5KE43A-TP](#) [1.5KE43CA-TP](#) [1.5KE43CA-TP-HF](#)
[1.5KE440CA-TP](#) [1.5KE47A-TP](#) [1.5KE51CA-TP](#) [1.5KE56A-TP](#) [1.5KE56CA-TP](#) [1.5KE6.8A-TP](#) [1.5KE68A-TP](#) [1.5KE68CA-TP](#) [1.5KE8.2A-TP](#) [1.5KE82A-TP](#) [1.5KE82CA-TP](#) [10A01-TP](#) [10A02](#) [15KP120CA-TP](#) [15KP17A-TP](#) [15KP200A-TP](#) [15KP240CA-TP](#) [15KP33CA-TP](#)