

Obsolete



Micro Commercial Components



Micro Commercial Components
20736 Marilla Street Chatsworth
CA 91311
Phone: (818) 701-4933
Fax: (818) 701-4939

MB3505W
THRU
MB3510W

Features

- Mounting Hole For #8 Screw
High Conductivity Metal Case
Any Mounting Position
Halogen free available upon request by adding suffix "-HF"
Epoxy meets UL 94 V-0 flammability rating
Moisture Sensitivity Level 1
Lead Free Finish/Rohs Compliant (Note1) ("P" Suffix designates Compliant. See ordering information)
UL Recognized File # E165989

Maximum Ratings

- Operating Temperature: -55°C to +150°C
Storage Temperature: -55°C to +150°C
Mounting Torque: 20 in-lbs Maximum

Table with 5 columns: MCC Catalog Number, Device Marking, Maximum Recurrent Peak Reverse Voltage, Maximum RMS Voltage, Maximum DC Blocking Voltage. Rows include MB3505W through MB3510W.


Electrical Characteristics @ 25°C Unless Otherwise Specified

Table with 4 columns: Parameter, Symbol, Value, Conditions. Rows include Average Forward Current, Peak Forward Surge Current, Maximum Forward Voltage Drop Per Element, and Maximum DC Reverse Current At Rated DC Blocking Voltage.

Notes: 1. High Temperature Solder Exemption Applied, see EU Directive Annex Notes 7

35 Amp Single Phase Bridge Rectifier
50 to 1000 Volts


MB-35W



DIMENSIONS table with columns for DIM, INCHES (MIN, MAX), MM (MIN, MAX), and NOTE. Rows A through H.


MB3505W thru MB3510W

Figure 1
Typical Forward Characteristics




Instantaneous Forward Current - Amperes *versus*
Instantaneous Forward Voltage - Volts

Figure 2
Typical Reverse Characteristics




Instantaneous Reverse Leakage Current - MicroAmperes *versus*
Percent Of Rated Peak Reverse Voltage - Volts

Figure 3
Forward Derating Curve



Average Forward Rectified Current - Amperes *versus*
Case Temperature - °C

Figure 4
Peak Forward Surge Current



Peak Forward Surge Current - Amperes *versus*
Number Of Cycles At 60Hz - Cycles



Micro Commercial Components

Ordering Information

Device	Packing
(Part Number)-BP	Bulk;400Pcs/Ctn

Note : Adding "-HF" suffix for halogen free, eg. Part Number-BP-HF

IMPORTANT NOTICE

Micro Commercial Components Corp. reserves the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes. **Micro Commercial Components Corp.** does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold **Micro Commercial Components Corp.** and all the companies whose products are represented on our website, harmless against all damages.

LIFE SUPPORT

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

CUSTOMER AWARENESS

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. **MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources.** MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.

www.mccsemi.com

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Micro Commercial Components \(MCC\)](#) manufacturer:

Other Similar products are found below :

[6A05-TP](#) [P6KE6.8CA-TP](#) [1N4002T&R](#) [3SMAJ5950B-TP](#) [3SMAJ5918B-TP](#) [MD130S16M5-BP](#) [GS1Z-LTP](#) [MBRB1060CTH-TP](#)
[MCQ15N10B-TP](#) [MBRB10150-BP](#) [5.0SMLJ22CAHE3-TP](#) [BAT64-05W-TP](#) [MUR860F-BP](#) [5.0SMLJ26CAHE3-TP](#) [BCV27-TP](#)
[MBRB1645CT-TP](#) [MURD1040C-TP](#) [ER1J-LTP](#) [MMSZ4688-TP](#) [MMXZ5231B-TP](#) [SMBJ5361B-TP](#) [5KP48A-TP](#) [BSS138W-TP](#) [KBP310G-](#)
[BP](#) [SM4003PL-TP](#) [SMBj30CA-TP](#) [SMBJ5357B-TP](#) [SMBJP6KE12CA-TP](#) [MF200K06F4-BP](#) [DL5237B-TP](#) [SK510AFL-TP](#) [RB551V-30-TP](#)
[SRV05-4A-TP](#) [GBJ3508-BP](#) [GBJ1008-BP](#) [SMBJ200A](#) [BAS70WT-05-TP](#) [MBR16100FCT-BP](#) [BAT54W-TP](#) [SMF12CA-TP](#) [GBU10M-BP](#)
[ER3J-TP](#) [353-8003-KIT](#) [10A05-TP](#) [SK153-TP](#) [BR106-BP](#) [2SC2383P-O-TP](#) [1EZ24D5-TP](#) [BZT52C12-TP](#) [SK32B-LTP](#)