

Features

- Output Current in Excess of 0.5 Ampere
- Internal Thermal Overload Protection
- Internal Short-circuit Current Limiting
- High Power Dissipation Capability
- Moisture Sensitivity Level 1
- Epoxy Meets UL 94 V-0 Flammability Rating
- Halogen Free Available Upon Request By Adding Suffix "-HF"
- Lead Free Finish/RoHS Compliant ("P" Suffix designates RoHS Compliant. See ordering information)

Maximum Ratings

Parameter	Symbol	Value	Unit
Input Voltage	VI	35	V
Power Dissipation	P _D	1.25	W
Operating Junction Temperature (ÄÜa) * ^	T _{OPR}	0~125	°C
Storage Temperature Range	T _{STG}	-65~125	°C
Thermal Resistance junction to Ambient	$R_{ extsf{ heta}JA}$	100	°C/W

Three-Terminal Positive Voltage Regulators





Electrical Characteristics

(V_i=10V, I_o=350mA, 0°C < T_j < 125 °C,C_i=0.33uF, C_o=0.1uF,Unless Otherwise Specified)

Parameter	Symbol	Test Conditions	Min	Тур	Max	Unit
Output Voltage	Vo	T _j =25°C	4.8	5.0	5.2	V
		7V≤V _i ≤20V,5mA≤I _o ≤350mA, P _D =15W	4.75	5.0	5.25	V
Load Regulation	∆Vo	5mA≤l₀≤500mA,Tj=25°C	-	15	100	mV
		5mA≤l₀≤200mA,Tj=25°C	-	5.0	50	mV
Line Regulation	∆Vo	7.0V≤V₁≤25V,I₀=0.5A	-	3.0	100	mV
		8.0V≤V₁≤25V,I₀=0.5A	-	1.0	50	mV
Quiescent Current	lq	T _j =25°C	-	4.2	6.0	mA
Quiescent Current Change	∆lq	8V≤Vi≤25V,I₀=200mA, 5mA≤I₀≤350mA	-	-	0.8	mA
			-	-	0.5	mA
Output Noise Voltage	V _N	10Hz≤f≤120Hz	-	40	200	μV
Ripple Rejection	RR	8V≤Vi≤18V, f=120Hz,I₀=0.3A,Tj=25°C	62	80	-	dB
Dropout Voltage	V _d	I _o =0.35A,T _j =25°C	-	2.0	2.5	V
Output Short Circuit Current	I _{sc}	V _i =10V, T _j =25°C	-	300	-	mA
Peak Output Current	I _{PK}	T _j =25°C	-	0.7	-	А

Typcial Application





Curve Characteristics



Figure 1.Peak Output Current versus Dropout Voltage



Figure 3. Ripple Rejection versus Frequency

T_J = 125°C

20

VI, INPUT VOLTAGE (Vdc)

T_J = 25°C

T_J = 125°C

10

15

T_J = 25°C

V_O = 5.0 V I_O = 0.5 A

30

35



Figure 2. Dropout Voltage versus Junction Temperature



Figure 4. Ripple Rejection versus Output Current



Figure 5. Bias Current versus Input Voltage

25

Figure 6. Bias Current versus Output Current

4.0

3.0

2.0

1.0

0

0

5.0

IB, BIAS CURRENT (mA)

40



Ordering Information

Device	Packing
Part Number-TP	Tape&Reel:2.5Kpcs/Reel

Note : Adding "-HF" Suffix For Halogen Free, eg. Part Number-TP-HF

IMPORTANT NOTICE

Micro Commercial Components Corp. reserves the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes. *Micro Commercial Components Corp*. does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold *Micro Commercial Components Corp*. and all the companies whose products are represented on our website, harmless against all damages. *Micro Commercial Components Corp*. products are sold subject to the general terms and conditions of commercial sale, as published at

https://www.mccsemi.com/Home/TermsAndConditions.

LIFE SUPPORT

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

CUSTOMER AWARENESS

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. **MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources**. MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Linear Voltage Regulators category:

Click to view products by Micro Commercial Components (MCC) manufacturer:

Other Similar products are found below :

LV56831P-E LV5684PVD-XH MCDTSA6-2R L7815ACV-DG PQ3DZ53U LV56801P-E TLE42794G L78L05CZ/ISX L78LR05DL-MA-E 636416C 714954EB BA033LBSG2-TR LV5680P-E L78M15CV-DG TLS202B1MBV33HTSA1 L79M05T-E TLS202A1MBVHTSA1 L78LR05D-MA-E NCV317MBTG NTE7227 LV5680NPVC-XH LT1054CN8 MP2018GZD-5-Z MP2018GZD-33-Z MIC5281-3.3YMM RT9078-28GQZ MC78L06BP-AP TA48LS05F(TE85L,F) TA78L12F(TE12L,F) TC47BR5003ECT TCR2LN12,LF(S TCR2LN28,LF(S TCR2LN30,LF(S TCR3DF295,LM(CT TCR3DF40,LM(CT BA178M20CP-E2 L78M12ABDT LM7812SX/NOPB LR645N3-G-P003 LR645N3-G-P013 ZXTR2005P5-13 SCD7812BTG TCR3DF335,LM(CT ZXTR2012K-13 TLE42994E V33 ZXTR2008K-13 ZXTR2005K-13 LA5693D-E L88R05DL-E ADP3300ARTZ-2.7RL7