

ROHS

Micro Commercial Components 20736 Marilla Street Chatsworth CA 91311

Phone: (818) 701-4933 Fax: (818) 701-4939 R2500 THRU R3000

Features

- Halogen free available upon request by adding suffix "-HF"
- High Voltage
- Low Leakage
- Low Forward Voltage Drop
- Epoxy meets UL 94 V-0 flammability rating
- Moisture Sensitivity Level 1
- Lead Free Finish/Rohs Compliant (Note1) ("P"Suffix designates Compliant. See ordering information)

Maximum Ratings

Operating Temperature: -55°C to +150°C
 Storage Temperature: -55°C to +150°C


| Microsemi Catalog Number | Device Marking | Maximum Recurrent Peak Reverse Voltage | Maximum RMS Voltage | Maximum DC Blocking Voltage |
|--------------------------------|-------------------|-------------------------------------------------|---------------------------|--------------------------------------|
| R2500 | R2500 | 2500V | 1750V | 2500V |
| R3000 | R3000 | 3000V | 2100V | 3000V |

Electrical Characteristics @ 25°C Unless Otherwise Specified

| Average Forward Current | I _{F(AV)} | 200mA | T _A = 50°C |
|---------------------------------------------------------------|--------------------|---------------|--------------------------------------------------|
| Peak Forward Surge Current | I _{FSM} | 30A | 8.3ms, half sine |
| Maximum Instantaneous Forward Voltage R2500 R3000 | V_F | 3.0V 4.0V | I _{FM} = 0.5A; T _A = 50°C |
| Maximum DC Reverse Current At Rated DC Blocking Voltage | I _R | 5.0μA 50μA | T _A = 25°C T _A = 100°C |
| Typical Junction Capacitance | CJ | 30pF | Measured at 1.0MHz, V _R =4.0V |

Note: 1. High Temperature Solder Exemptions Applied, see EU Directive Annex 7.

200 Milliamp High Voltage Silicon Rectifier 2500 to 3000 Volts




| DIMENSIONS | | | | | | | | | |
|------------|--------|------|-------|------|------|--|--|--|--|
| | INCHES | | MM | | | | | | |
| DIM | MIN | MAX | MIN | MAX | NOTE | | | | |
| Α | .230 | .300 | 5.80 | 7.60 | | | | | |
| В | .104 | .140 | 2.60 | 3.60 | | | | | |
| С | .026 | .034 | .70 | .90 | | | | | |
| D | 1.000 | | 25.40 | | | | | | |

.01

0



Micro Commercial Components



Instantaneous Reverse Current - Micro Amps*versus* Percent Of Rated Peak Reverse Voltage - Volts

60


Volts

40


80

100

120



Average Forward Rectified Current - Amperes/ersus Ambient Temperature -°C



Peak Forward Surge Current - Amperesversus Number Of Cycles At 60Hz - Cycles



Ordering Information:

DevicePackingPart Number-TPTape&Reel: 4Kpcs/ReelPart Number-APAmmo Packing: 3Kpcs/Ammo BoxPart Number-BPBulk: 25Kpcs/Carton

Note: Adding "-HF" suffix for halogen free, eg. Part Number-TP-HF

IMPORTANT NOTICE

Micro Commercial Components Corp. reserves the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes. **Micro Commercial Components Corp.** does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold **Micro Commercial Components Corp.** and all the companies whose products are represented on our website, harmless against all damages.

LIFE SUPPORT

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

CUSTOMER AWARENESS

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources. MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Rectifiers category:

Click to view products by Micro Commercial Components (MCC) manufacturer:

Other Similar products are found below:

70HFR40 RL252-TP 150KR30A 1N5397 NTE5841 NTE6038 SCF5000 1N4002G 1N4005-TR JANS1N6640US 481235F
RRE02VS6SGTR 067907F MS306 70HF40 T85HFL60S02 US2JFL-TP A1N5404G-G ACGRA4007-HF ACGRB207-HF
CLH03(TE16L,Q) ACGRC307-HF ACEFC304-HF NTE6356 NTE6359 NTE6002 NTE6023 NTE6039 NTE6077 85HFR60 40HFR60
70HF120 85HFR80 D126A45C SCF7500 D251N08B SCHJ22.5K SM100 SCPA2 SCH10000 SDHD5K VS-12FL100S10 ACGRA4001-HF D1821SH45T PR D1251S45T NTE5990 NTE6358 NTE6162 NTE5850 SKN300/16