

Features

- Halogen free
- AEC-Q101 Qualified
- · Protects Two Bi-Directional Lines
- Ultra Low Leakage
- · Low Clamping Voltage
- · Moisture Sensitivity Level 1
- Epoxy Meets UL 94 V-0 Flammability Rating
- Lead Free Finish/RoHS Compliant ("P" Suffix Designates RoHS Compliant. See Ordering Information)


Maximum Ratings

- Operating Junction Temperature Range: -55°C to +125°C
- Storage Temperature Range: -55°C to +150°C


MCC Part Number	Device Marking
SM24BHE3	24M

IEC61000-4-2(ESD)	Air Contact	±30KV ±30KV	
IEC61000-4-4 (EFT) @5/50ns		40A	
Peak Pulse Current(8/20μs)	I _{PP}	4A	
Peak Pulse Power (8/20us)	P _{PK}	300W	

Internal Structure




ESD Protection Device



	DIMENSIONS				
DIM INCHES		MM		NOTE	
DIIVI	MIN	MAX	MIN	MAX	NOIL
Α	0.110	0.120	2.80	3.04	
В	0.083	0.104	2.10	2.64	
С	0.047	0.055	1.20	1.40	
D	0.034	0.041	0.85	1.05	
Е	0.067	0.083	1.70	2.10	
F	0.018	0.024	0.45	0.60	
G	0.0004	0.006	0.01	0.15	
Н	0.035	0.043	0.90	1.10	
J	0.003	0.007	0.08	0.18	
K	0.012	0.020	0.30	0.51	
L	0.007	0.020	0.20	0.50	


Suggested Solder Pad Layout





ELECTRICAL CHARACTERISTICS (T_A = 25°C unless otherwise noted)

Symbol	Parameter		
I _{PP}	Maximum Reverse Peak Pulse Current		
V _C	Clamping Voltage @ I _{PP}		
V_{RWM}	Working Peak Reverse Voltage		
I _R	Maximum Reverse Leakage Current @ V _{RWM}		
V_{BR}	Breakdown Voltage @ I _T		
I _T	Test Current		
С	Capacitance @V _R =0 and f =1MHz		




Electrical Characteristics @ 25°C (Unless Otherwise Specified)


Parameter	Symbol	Conditions	Min.	Тур.	Max.	Units
Reverse Working Voltage	V_{RWM}				24	V
Reverse Breakdown Voltage	V_{BR}	I _T = 1mA	27			V
Reverse Leakage Current	I _R	V _{RWM} =24V			0.2	μA
Clamping Voltage	V _C	I _{PP} =1A, t _P =8/20µs			42	V
Clamping Voltage	V _C	I _{PP} =4A, t _P =8/20µs		44	50	V
Junction Capacitance	CJ	$V_R = 0V$, $f = 1MHz$		20		pF



Curve Characteristics

Fig. 1 - 8 X 20µs Pulse Waveform







Ordering Information

Device	Packing
Part Number-TP	Tape&Reel: 3Kpcs/Reel

IMPORTANT NOTICE

Micro Commercial Components Corp. reserves the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes. **Micro Commercial Components Corp**. does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold **Micro Commercial Components Corp**, and all the companies whose products are represented on our website, harmless against all damages.

LIFE SUPPORT

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

CUSTOMER AWARENESS

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources. MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.

Rev.3-2-05132020 4/4 MCCSEMI.COM

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for ESD Suppressors / TVS Diodes category:

Click to view products by Micro Commercial Components (MCC) manufacturer:

Other Similar products are found below:

NTE4902 P4SMAJ15A P4SMAJ26A SMAJ400CA-TP TGL34-47CA ESDAULC45-1BF4 SM1605E3/TR13 SMF20A-TP P4SMAJ12A CPDUR24V-HF CPDQC5V0USP-HF CPDQC5V0-HF MPLAD30KP45CAE3 MMBZ27VCLQ-7-F MMAD1108/TR13 MPLAD30KP24A ACPDQC5V0R-HF DFLT170A-7 NTE4900 NTE4926 NTE4938 SMF22A-TP SMF12A-TP SLVU2.8-TP SMLJ6.5CA-TP SMAJ6.5CA-TP MMAD1108E3/TR13 D5V0M1U2LP3-7 SMAJ400A-TP AOZ8811DT-03 AOZ8831DI-05 AOZ8831DT-03 SMAJ188CA 3SMC33CA BK CPDQC3V3C-HF CPDQC12VE-HF MPLAD30KP170CA 82357120100 5.0SMLJ15CA-TP 5KP18A-TP P6KE8.2A-TP MPLAD30KP43CAE3 SMAJ43A-TP D5V0F6U8LP33-7 TVS5501V10MUT5G 5.0SMLJ24CA-TP SMAJ110CA-TP MPLAD15KP75CAE3 MMAD1103e3/TR13 DFLT40AQ-7