

Features

- Lead Free Finish/RoHS Compliant ("P" Suffix Designates RoHS Compliant. See Ordering Information)
- Ultra-Small Surface Mount Package
- High Reliability
- Epoxy Meets UL 94 V-0 Flammability Rating
- Moisure Sensitivity Level 1
- Halogen Free. "Green" Device (Note 1)

1 Amp Schottky Barrier Rectifier 40 Volts

Maximum Ratings

- Operating Junction Temperature Range: -55°C to +150°C
- Storage Temperature Range: -55°C to +150°C
- Thermal Resistance: 250°C/W Junction to Ambient


| MCC Part Number | Device Marking | Maximum Recurrent Peak Reverse Voltage | Maximum DC Blocking Voltage |
|--------------------|-------------------|---|-----------------------------------|
| SM5819L2 | 4A | 40V | 40V |

Electrical Characteristics @ 25°C Unless Otherwise Specified

| Average Forward Current((Note 2) | I _{F(AV)} | 1.0A | |
|--|--------------------|------------------------------|--|
| Peak Forward Surge Current | I _{FSM} | 10A | 8.3ms, Half Sine |
| Maximum Instantaneous Forward Voltage Drop | V _F | 0.3V 0.4V 0.5V 0.6V | I _F =10mA; I _F =100mA; I _F =500mA; I _F =1.0A; |
| Maximum Reverse Leakage Current | I _R | 0.06mA | V _R =40V |
| Typical Junction Capacitance | CJ | 90pF | Measured at 1.0MHz,V _R =0V |


Note: 1. Halogen free "Green" products are defined as those which contain <900ppm bromine, <900ppm chlorine (<1500ppm total Br + Cl) and <1000ppm antimony compounds.

2. Squre wave : σ = 0.5



| DIMENSIONS | | | | | | |
|------------|--------|-------|-------|------|------|--|
| DIM | INCHES | | MM | | NOTE | |
| | MIN | MAX | MIN | MAX | NOTE | |
| А | 0.013 | 0.022 | 0.34 | 0.55 | | |
| В | 0.000 | 0.002 | 0.00 | 0.05 | | |
| D | 0.037 | 0.043 | 0.95 | 1.08 | | |
| Е | 0.022 | 0.027 | 0.55 | 0.68 | | |
| F | 0.026 | REF. | 0.650 | REF. | | |
| G | 0.016 | 0.024 | 0.40 | 0.60 | | |
| Н | 0.003 | 0.007 | 0.07 | 0.17 | | |
| L | 0.008 | 0.012 | 0.20 | 0.30 | | |

SUGGESTED SOLDER PAD LAYOUT











Fig. 1 - Typical Instantaneous Forward Characteristics








Fig. 2 - Typical Reverse Leakage Characteristics



Ordering Information

| Device | Packing | |
|----------------|----------------------|--|
| Part Number-TP | Tape&Reel10Kpcs/Reel | |

IMPORTANT NOTICE

Micro Commercial Components Corp. reserves the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes. *Micro Commercial Components Corp*. does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold *Micro Commercial Components Corp*. and all the companies whose products are represented on our website, harmless against all damages. *Micro Commercial Components Corp*. products are sold subject to the general terms and conditions of commercial sale, as published at

https://www.mccsemi.com/Home/TermsAndConditions.

LIFE SUPPORT

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

CUSTOMER AWARENESS

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. **MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources**. MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Schottky Diodes & Rectifiers category:

Click to view products by Micro Commercial Components (MCC) manufacturer:

Other Similar products are found below :

MA4E2039 D1FH3-5063 MBR10100CT-BP MBR1545CT MMBD301M3T5G RB160M-50TR RB551V-30 BAS16E6433HTMA1 BAT 54-02LRH E6327 NSR05F40QNXT5G NTE555 JANS1N6640 SB07-03C-TB-H SB1003M3-TL-W SK310-T SK32A-LTP SK34B-TP SS3003CH-TL-E GA01SHT18 CRS10I30A(TE85L,QM MA4E2501L-1290 MBRB30H30CT-1G SB007-03C-TB-E SK32A-TP SK33B-TP SK38B-TP NRVBM120LT1G NTE505 NTSB30U100CT-1G SS15E-TP VS-6CWQ10FNHM3 ACDBA1100LR-HF ACDBA1200-HF ACDBA140-HF ACDBA2100-HF ACDBA3100-HF CDBQC0530L-HF CDBQC0240LR-HF ACDBA260LR-HF ACDBA1100-HF SK310B-TP MA4E2502L-1246 MA4E2502H-1246 NRVBM120ET1G NSR01L30MXT5G NTE573 NTE6081 SB560 PMAD1108-LF SD103ATW-TP