



**RV-8263-C7** 

**Development Board** 

DATE: January 2019 Revision No.: 1 Page 1/3 Tel. +41 32 655 82 82 Headquarters: Micro Crystal AG Muehlestrasse 14 Fax +41 32 655 82 83 CH-2540 Grenchen Internet www.microcrystal.com Switzerland Email sales@microcrystal.com

## **Development Board**


## RV-8263-C7

The RV-8263-C7 is soldered onto the Development Board. Every pin is either accessible at test pins 1 - 8 or at the test vias situated around the device.

The following passive components are already soldered on the board:

| C1  | 10 nF | Decoupling capacitor between $V_{SS}$ and $V_{DD}$                                    |  |
|-----|-------|---|--|
| R1  | 330 Ω | Current limiting resistor for LED   |  |
| LED | green | Supply on, current consumption of the LED has to be considered                        |  |
| R2  | 10 kΩ | Protection resistor to prevent short-circuit between external CLKOE signal and Jumper |  |
| R3  | 10 kΩ | Pull-up resistor INT to VDD   |  |
| R4  | 10 kΩ | Pull-up resistor SCL to V <sub>DD</sub>   |  |
| R5  | 10 kΩ | Pull-up resistor SDA to V <sub>DD</sub>   |  |


#### DEVELOPMENT BOARD



## **Development Board**

#### RV-8263-C7

#### SCHEMATICS



#### PINOUT RV-8263-C7



#### **PIN DESCRIPTION**

| Symbol | Pin # | Description   |
|--------|-------|---|
| NC     | 1     | Not connected. Is internally connected and should be left floating.   |
| VSS    | 2     | Ground  |
| CLKOE  | 3     | Input to enable the CLKOUT pin. If CLKOE is HIGH, the CLKOUT pin is in output mode. When CLKOE is tied to Ground, the CLKOUT pin is LOW.  |
| INT    | 4     | Interrupt Output; open-drain; active LOW; requires pull-up resistor; Used to output alarm, minute, half minute, countdown timer and compensation Interrupt signals  |
| VDD    | 5     | Power Supply Voltage  |
| CLKOUT | 6     | Clock Output; push-pull; controlled by CLKOE. If CLKOE is active HIGH, the CLKOUT pin drives the square wave of 32.768 kHz, 16.384 kHz, 8.192 kHz, 4.096 kHz, 2.048 kHz, 1.024 kHz or 1 Hz (Default value is 32.768 kHz). When CLKOE is tied to Ground, the CLKOUT pin is LOW |
| SCL    | 7     | I2C Serial Clock Input. Requires pull-up resistor.  |
| SDA    | 8     | I2C Serial Data Input-Output. Requires pull-up resistor.  |

Datasheet and Application-Manual are available for download under: www.microcrystal.com

# **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Clock & Timer Development Tools category:

Click to view products by Micro Crystal manufacturer:

Other Similar products are found below :

AD9517-0A/PCBZ AD9517-2A/PCBZ AD9522-4/PCBZ AD9520-5PCBZ AD9553/PCBZ ADCLK914PCBZ LMH2180SDEVAL DSC400-0333Q0032KE1-EVB TDGL013 MAX2880EVKIT# MAX2750EVKIT MAX2752EVKIT ADCLK946PCBZ ADCLK946/PCBZ MAX2622EVKIT EKIT01-HMC1032LP6G Si5332-8IX-EVB RV-2251-C3-EVALUATION-BOARD Si5332-12IX-EVB RV-3029-C2-EVALUATION-BOARD-OPTION-B Si5332-6IX-EVB SKY72310-11-EVB EV1HMC8364LP6G RV-8263-C7-EVALUATION-BOARD EVK9FGV1002 EVK9FGV1008 EV1HMC6832ALP5L EVAL01-HMC830LP6GE EVAL01-HMC911LC4B TS3002DB 125605-HMC702LP6CE LMX2487E-EVM MIKROE-2481 2045 EKIT01-HMC835LP6G EKIT01-HMC834LP6GE TS3006DB DSC-TIMEFLASH2-KIT1 110227-HMC510LP5 110227-HMC513LP5 AD9515/PCBZ ADCLK948/PCBZ ADCLK954/PCBZ 112261-HMC739LP4 ADCLK925/PCBZ AD9522-0/PCBZ AD9520-4/PCBZ AC164147 DFR0469 LMK04133EVAL/NOPB