



BAV19WS/BAV20WS/BAV21WS


Silicon Epitaxial Planar Diode

FEATURES

- Fast Switching Speed
- Surface Mount Package Ideally Suited For Automatic Insertion
- For General Purpose Switching Applications
- High Conductance



Lead-free



APPLICATIONS

- Surface mount fast switching diode

ORDERING INFORMATION

Type No.	Marking	Package Code
BAV19WS	A8	SOD-323
BAV20WS	T2	SOD-323
BAV21WS	T3	SOD-323

MAXIMUM RATING @ Ta=25°C unless otherwise specified

Characteristic	Symbol	BAV19WS	BAV20WS	BAV21WS	Unit
Repetitive Peak Reverse Voltage	V _{RRM}	120	200	250	V
Working Peak Reverse Voltage	V _{RWM}				
DC Reverse Voltage	V _R	100	150	200	V
RMS Reverse Voltage	V _{R(RMS)}	71	106	141	V
Average Rectified Output Current	I _o	200			mA
Non-Repetitive Peak Forward Surge Current @t=1.0 μs	I _{FSM}	2.5			A
@t=1.0 s		0.5			
Repetitive Peak Forward Surge Current	I _{FRM}	625			mA
Power Dissipation	P _d	200			mW
Thermal Resistance Junction to Ambient Air	R _{θJA}	625			°C/W
Operating and Storage Temperature Range	T _j , T _{STG}	-65 to +150			°C



BAV19WS/BAV20WS/BAV21WS

Silicon Epitaxial Planar Diode

ELECTRICAL CHARACTERISTICS @ Ta=25°C unless otherwise specified





Characteristic	Symbol	Min	Max	Unit	Test Condition
Reverse Breakdown Voltage BAV19WS BAV20WS BAV21WS	$V_{(BR)R}$	120 200 250		V	$I_R=100\mu A$
Forward Voltage	V_{FM}	-	1.0 1.25	V	$I_F=100mA$ $I_F=200mA$
Reverse Current BAV19WS BAV20WS BAV21WS	I_R	-	0.1 0.1 0.1	μA	$V_R=100V$ $V_R=150V$ $V_R=200V$
Capacitance between terminals	C_T	-	5	pF	$V_R=0, f=1.0MHz$
Reverse Recovery Time	t_{rr}	-	50	ns	$I_F=I_R=30mA$, $I_{rr}=0.1 \times I_R, R_L=100\Omega$



BAV19WS/BAV20WS/BAV21WS

Silicon Epitaxial Planar Diode

TYPICAL CHARACTERISTICS @ $T_A=25^\circ\text{C}$ unless otherwise specified





BAV19WS/BAV20WS/BAV21WS

Silicon Epitaxial Planar Diode


PACKAGE OUTLINE

Plastic surface mounted package

SOD-323

SOD-323		
Dim	Min	Max
A	1.60	1.80
B	1.20	1.40
C	0.9 Max	
D	0.30 Typical	
E	0.22	0.42
H	0.02	0.1
J	0.1 Typical	
K	2.55	2.75
All Dimensions in mm		

SOLDERING FOOTPRINT



Unit : mm

PACKAGE INFORMATION

Device	Package	Shipping
BAV19WS/20WS/21WS	SOD-323	3000/Tape&Reel

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Diodes - General Purpose, Power, Switching category:

Click to view products by Microdiode Electronics manufacturer:

Other Similar products are found below :

[MMBD3004S-13-F](#) [RD0306T-H](#) [DSE010-TR-E](#) [BAV17-TR](#) [BAV19-TR](#) [1N3611](#) [NTE156A](#) [NTE574](#) [NTE6244](#) [1SS181-TP](#) [1SS193,LF](#)
[1SS400CST2RA](#) [SDAA13](#) [SHN2D02FUTW1T1G](#) [LS4151GS08](#) [FC903-TR-E](#) [1N4449](#) [1N456A](#) [1N4934-E3/73](#) [1N914B](#) [1N914BTR](#)
[1SS226-TP](#) [RFUH20TB3S](#) [D291S45T](#) [BAV300-TR](#) [BAW56DWQ-7-F](#) [BAW75-TAP](#) [MM230L-CAA](#) [IDW40E65D1](#) [JAN1N3600](#) [LL4151-GS18](#) [053684A](#) [SMMSD4148T3G](#) [707803H](#) [NSVDAN222T1G](#) [CDSZC01100-HF](#) [LL4150-M-08](#) [BAV199E6433HTMA1](#) [BAS28-7](#)
[BAW56HDW-13](#) [BAS28 TR](#) [VS-HFA04SD60STR-M3](#) [NSVM1MA152WKT1G](#) [RGP30D-E3/73](#) [BAV99TQ-13-F](#) [BAS21DWA-7](#) [NTE6250](#)
[NTE582-4](#) [NTE582-6](#) [MMDB30-E28X](#)