
PD-9001GO Midspan



Single-port, Outdoor PoE Midspan, IEEE802.3at Compliant



Overview

Microsemi's PD-9001GO Power over Ethernet (PoE) single-port midspan offers a cost effective, fully IEEE 802.3af/802.3at compliant solution for outdoor installations, guaranteeing 30 Watts of power and ensuring safe and reliable operation in outdoor environment of any standard PoE data terminal. It allows wireless LAN access points, security network cameras and other IP terminals to receive power, along with data, over standard Ethernet cables, leaving network infrastructure completely unaltered.

The PD-9001GO also offers surge protection for both the AC and the PoE ports ensuring the indoor equipment is protected from outdoor surges.

PD-9001GO Features

- Outdoor rated: IP66
- Extended temperature range -40C, +65C
- Fully IEEE802.3at standard compliant
- Supports 10/100/1000Mbps data rates
- Plug 'n Play installation (installer does not have to open unit)
- Supports both 802.3af and 802.3at Powered devices
- Includes integral surge protection

PD-9001GO Specifications

No. of Ports	1	
Pass Through Data Rates	10/100/1000 Mbps	
Power over Ethernet Output	Pin Assignment and Polarity: 4/5 (+), 7/8 (-) Output Power Voltage: 55Vdc User Port Power: 30W guaranteed	
Input Power Requirements	AC Input Voltage: 100 to 240 Vac AC Input Current: 1A @100-240 Vac AC Frequency: 50 to 60 Hz	
Dimensions	214 mm x 150 mm x 70 mm 8.42 in. x 5.90 in. x 2.75 in	
Weight	1.65 lbs (750g)	
Indicators	No LED indicators	
Connectors	Shielded rugged RJ-45 (with gasket)	
Environmental Conditions	Operating Ambient Temperature: -40° to 131°F (-40 to 55°C) for 30W -40° to 149°F (-40 to 65°C) for 15.4W	
	Operating Humidity: Maximum 95%, Non-condensing	
	Storage Temperature: -40° to 185°F (-40° to 85°C)	
	Storage Humidity: Maximum 95%, Non-condensing	
	Operating Altitude: Up to 6,560 ft. (2000 m)	
	Weather Rating: IP66, NEMA 4X	
Reliability	MTBF: 150,000 hrs. @25°C	
Thermal Rating	25 BTU/Hr (@240VAC)	
Warranty	1-year	
Regulatory Compliance	IEEE 802.3at (PoE), RoHS Compliant, WEEE Compliant, CE	
Electromagnetic Emission & Immunity	FCC Part 15, Class B EN 55022 Class B EN 55024, EN61000-4-5 Class 5 (6kV CM) VCCI	
Surge Protection	Meets Surge Protection as specified in GR-1089-CORE Issue 4 ITU-T K.20 6 kV on AC lines	
Safety Approvals	UL60950-1 & UL60950-22 GS Mark	
Other Standards and Approvals	Dust and water intrusion: EN60529, Level1P66; NEMA 250, Level 4X ASTM B-117 Corrosion Resistance	

PD-9001GO with outdoor mounting bracket







Ordering Information

Part Number	Name	Description
PD-9001GO/AC	Microsemi PD-9001GO	1-port 802.3at Gigabit PoE Outdoor Midspan
PD-OUT/MBK	Microsemi OUT MBK	Mounting brackets for outdoor unit



One Enterprise, Aliso Viejo, CA 92656 USA Within the USA: +1 (800) 713-4113 Outside the USA: +1 (949) 380-6100 Sales: +1 (949) 380-6136 Fax: +1 (949) 215-4996 email: sales.support@microsemi.com www.microsemi.com

Microsemi Corporation (Nasdaq: MSCC) offers a comprehensive portfolio of semiconductor and system solutions for communications, defense & security, aerospace and industrial markets. Products include high-performance and radiation-hardened analog mixed-signal integrated circuits, FPGAs, SoCs and ASICs; power management products; timing and synchronization devices and precise time solutions, setting the world's standard for time; voice processing devices; RF solutions; discrete components; security technologies and scalable anti-tamper products; Power-over-Ethernet ICs and midspans; as well as custom design capabilities and services. Microsemi is headquartered in Aliso Viejo, Calif., and has approximately 3,400 employees globally. Learn more at www.microsemi.com.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Power over Ethernet - PoE category:

Click to view products by Microsemi manufacturer:

Other Similar products are found below:

PD-3504G/AC PD-9601G/AC PD-3504G/AC-EU 180993-3001 GHOSTBRIDGE-POE EKI-2701MPI-AE EKI-2701MPI-R-AE EKI-2701PSI-AE EKI-2741FHPI-AE PALS400-2482G PALS600-2482G AWPOE PD-9001GC/AC PD-9001GI/DC PD-9001GO-ET/AC PD-9001GR/AT/AC-EU PD-9606GC/AC-EU PD-9612GC/AC-EU PD-9624GC/AC-EU PD-9624GC/AC-US PD-9624GC/AC PD-9501GC/AC-EU PD-6506G/AC/M PD-OUT/MBK/G NPS-30W-B NPS-30W-WOC PD-9501GO-ET/AC PD-9601G/AC-EU PD-OUT/MBK/ET PD-OUT/MBK/S POE14-050-R POE14-137-R POE15M-560E-R POE16R-560L6 POE16S-1AFG-R POE30S-1ATG-R POE370U-480-16N-R POE370U-480-8N-R POE370U-480-8-R POE45-120-R POE576U-16ATN-R POE60D-560G-R POE60S-1BT-R POE60S-4AF-R POE60U-1BT-5 POE90U-1BT6-R POEA30U-1AT-2 POEA30U-1AT-5-R POEA30U-1ATE