

MIKROELEKTRONIKA D.O.O, Batajnički drum 23, 11000 Belgrade, Serbia VAT: SR105917343 Registration No. 20490918 Phone: + 381 11 78 57 600 Fax: + 381 11 63 09 644 E-mail: office@mikroe.com www.mikroe.com

<u>Mikromedia 5 for STM32F4</u> <u>Capacitive FPI with frame</u>



PID: MIKROE-3837

Rich with peripherals

Mikromedia 5 for STM32F4 CAPACITIVE FPI with frame is not limited to multimedia-based applications only. USB, WiFi and RF connectivity options, digital motion sensor, battery charging functionality, piezo-buzzer, SD card reader, RTC, and much more expands its use beyond the multimedia.

Mikromedia 5 for STM32F4 CAPACITIVE FPI with frame has three mikroBUS^M Shuttle connectors, a brand-new addition to the mikroBUS^M standard in the form of a 2x8-pin IDC header with 1.27mm (50mil) pitch. <u>mikroBUS^M</u> Shuttle extension board is an add-on board equipped with the conventional mikroBUS^M socket, which ensures compatibility with 894 <u>Click boards^M</u>.

Awesome graphics on MCU driven TFT

Mikromedia 5 for STM32F4 CAPACITIVE FPI with frame is a compact development board designed as a complete solution for the rapid development of multimedia and GUI-centric applications. By featuring a 5" TFT display with capacitive touch screen driven by the powerful graphics controller that can display the 24-bit color palette (16.7 million colors), along with a DSP-powered embedded sound CODEC IC, represents a perfect solution for any type of multimedia application.

Mikroe produces entire development toolchains for all major microcontroller architectures. Committed to excellency, we are dedicated to helping engineers bring the project development up to speed and achieve outstanding results.



ISO 27001: 2013 certification of informational security management system. ISO 14001: 2015 certification of environmental management system. OHSAS 18001: 2008 certification of occupational health and safety management system.



ISO 9001: 2015 certification of quality management system (QMS).



Time-saving embedded tools

MIKROELEKTRONIKA D.O.O, Batajnički drum 23, 11000 Belgrade, Serbia VAT: SR105917343 Registration No. 20490918 Phone: + 381 11 78 57 600 Fax: + 381 11 63 09 644 E-mail: office@mikroe.com www.mikroe.com

Develop-on & build-in the same board

Mikromedia 5 for STM32F4 CAPACITIVE FPI (FPI stands for Front Panel Integration) with frame is designed as the complete solution. It can be implemented directly into any project, with no additional hardware modifications. At its core, there is a powerful 32-bit_<u>STM32F407ZGT6</u> microcontroller from <u>STMicroelectronics</u>, which provides sufficient processing power for the most demanding tasks. Board has a TFT display with a metal frame, and four mounting holes that enable simple installation in various kinds of industrial appliances. For most uses, a nice casing is all that is needed to turn this product into a high-performance, feature-rich device. This board requires the use of an external programmer and debugger, preferably <u>CODEGRIP</u> or mikroProg. The microcontroller can be programmed and debugged over the JTAG/SWD compatible 2x5 pin header, labeled as <u>PROG/DEBUG</u>.

Mikroe produces entire development toolchains for all major microcontroller architectures. Committed to excellency, we are dedicated to helping engineers bring the project development up to speed and achieve outstanding results.



ISO 27001: 2013 certification of informational security management system. ISO 14001: 2015 certification of environmental management system. OHSAS 18001: 2008 certification of occupational health and safety management system.



ISO 9001: 2015 certification of quality management system (QMS).



MIKROELEKTRONIKA D.O.O, Batajnički drum 23, 11000 Belgrade, Serbia VAT: SR105917343 Registration No. 20490918 Phone: + 381 11 78 57 600 Fax: + 381 11 63 09 644 E-mail: office@mikroe.com www.mikroe.com

Specifications

Туре	mikromedia
Architecture	ARM (32-bit)
Display size	5" 800x480px
Resolution	320x240px
Graphic controller	SSD1963
Touch Screen	Capacitive
Input Voltage	3.3V
Silicon Vendor	STM
mikroBUS No.	3
Frame Type	Metal Frame
Features	Batt. Chg. when OFF,WiFi,USB Type C,USB Host,SD Card,RF,ON/OFF switch,MP3,External DC source,Battery Powered,Battery for RTC,Accel
Display type	mikromedia

Downloads

Mikromedia 5 for STM32F4 CAPACITIVE FPI schematic

Mikromedia 5 for STM32F4 CAPACITIVE FPI Manual

Mikromedia 5 for STM32F4 CAPACITIVE FPI 2D and 3D files

Mikromedia 5 for STM32F4 CAPACITIVE FPI example on libstock

Mikroe produces entire development toolchains for all major microcontroller architectures.

Committed to excellency, we are dedicated to helping engineers bring the project development up to speed and achieve outstanding results.



ISO 27001: 2013 certification of informational security management system. ISO 14001: 2015 certification of environmental management system. OHSAS 18001: 2008 certification of occupational health and safety management system.



ISO 9001: 2015 certification of quality management system (QMS).

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Display Development Tools category:

Click to view products by MikroElektronika manufacturer:

Other Similar products are found below :

KIT 60121-3 S5U13U11P00C100 121CBL02-RPK KIT 60145-3 S5U13748P00C100 DFR0413 DLPLCR90EVM DLPLCR50XEVM MAX20069EVKIT# KIT95000-3 LCD-16396 PIM370 1109 MCIMX-LVDS1 MIKROE-2449 MIKROE-2453 131 DEV-13628 1590 MIKROE-2269 1601 1770 1947 1983 1987 2050 2218 2260 2345 2418 2423 2454 2455 2478 2674 SK-220RD-PI FIT0477 333 334 TE-M321-SDK DFR0428 cs-epapersk-03 338 DEV-14442 FIT0478 cs-paperino-01 OM-E-OLE ALTHSMCMIPILCD ASD2421-R TDP0500T800480PCAP