

MIKROELEKTRONIKA D.O.O, Batajnički drum 23, 11000 Belgrade, Serbia VAT: SR105917343 Registration No. 20490918

Phone: + 381 11 78 57 600 Fax: + 381 11 63 09 644 E-mail: office@mikroe.com

www.mikroe.com

Radiation Click





PID: MIKROE-4036

Radiation Click is a Click board[™] based on <u>BG51</u> radiation sensor from <u>Teviso Sensor</u> <u>Technologies</u>. The function of the BG51 radiation sensor is based on an array of customized PIN diodes. Performance of the Radiation Click board [™] with solid state sensor, in combination with high immunity to electrostatic fields make it a good choice for new state-of-the-art designs as well as for upgrading existing designs of detecting beta and gamma radiation and X-rays.

Radiation Click board $^{\text{\tiny M}}$ is supported by a mikroSDK compliant library, which includes functions that simplify software development. This Click board $^{\text{\tiny M}}$ comes as a fully tested product, ready to be used on a system equipped with the mikroBUS $^{\text{\tiny M}}$ socket.

Mikroe produces entire development toolchains for all major microcontroller architectures.

Committed to excellency, we are dedicated to helping engineers bring the project development up to speed and achieve outstanding results.





health and safety management system.



MIKROELEKTRONIKA D.O.O, Batajnički drum 23, 11000 Belgrade, Serbia VAT: SR105917343 Registration No. 20490918 Phone: + 381 11 78 57 600 Fax: + 381 11 63 09 644 E-mail: office@mikroe.com www.mikroe.com

Specifications

Туре	Environmental
Applications	Equipment for detecting radioactivity in medical environment, Radiation monitors for nuclear safeguards and security, Gamma detector to detect illicit nuclear material, Natural sciences courses and practical lab experiments
On-board modules	BG51 radiation sensor is based on an array of customized PIN diodes
Key Features	Detects beta and gamma radiation and X-rays, Detector sensitivity: 5 cpm/µSv/h, High immunity to RF and electrostatic fields, Linear response over wide temperature range (-30°C to 60°C)
Interface	GPIO
Compatibility	mikroBUS
Click board size	L (57.15 x 25.4 mm)
Input Voltage	5V

Resources

mikroBUS™

mikroSDK

Click board™ Catalog

Click boards™

Downloads

Radiation click example on Libstock

Radiation click 2D and 3D files

BG51 datasheet

Radiation click schematic

Mikroe produces entire development toolchains for all major microcontroller architectures. Committed to excellency, we are dedicated to helping engineers bring the project development up to speed and achieve outstanding results.





health and safety management system.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Multiple Function Sensor Development Tools category:

Click to view products by MikroElektronika manufacturer:

Other Similar products are found below:

MAXWSNENV# STEVAL-MKIT01V1 KT-O2-25%-TB200A-E KT-TVOC-200-TB200A KT-NmHc-200-TB200A SEN0344 PIM520

PIM518 PIM519 PIM502 EVAL-AD7746HDZ AS7022-EVALKIT ALTEHTG2SMIP OB1203SD-U-EVK MIKROE-4265 ARG-LDKT

EV_ICG-20660L GX-F12A-P GX-F15A GX-F6A-P GX-F8B GX-H12A-P GX-H15AI-P GX-H6A-P 1093 MIKROE-2455 MIKROE-2458

MIKROE-2507 MIKROE-2508 MIKROE-2516 MIKROE-2529 1458 MIKROE-1628 176 189 1893 2106 ATQT4-XPRO GX-F12AI-P

GX-F15A-P GX-F8A-P GX-FL15B-P GX-H15A-P GX-H6AI-P GX-H8AI-P GX-H8A-P GX-F15AI-P GX-FL15A-P GX-H15A