

MIKROELEKTRONIKA D.O.O, Batajnički drum 23, 11000 Belgrade, Serbia VAT: SR105917343 Registration No. 20490918

Phone: + 381 11 78 57 600 Fax: + 381 11 63 09 644 E-mail: office@mikroe.com

Bluetooth 2 click





PID: MIKROE-4087

Bluetooth 2 Click features WT41u, a long range class 1, Bluetooth® 2.1 + EDR module. WT41u is a highly integrated and sophisticated Bluetooth® module, containing all the necessary elements from Bluetooth® radio and a fully implemented protocol stack. Therefore WT41u provides an ideal solution for developers who want to integrate Bluetooth® wireless technology into their design with limited knowledge of Bluetooth® and RF technologies. WT41u optimized for long range applications is available with an integrated chip antenna.

Bluetooth 2 click is supported by a mikroSDK compliant library, which includes functions that simplify software development. This Click board $^{\text{TM}}$ comes as a fully tested product, ready to be used on a system equipped with the mikroBUS $^{\text{TM}}$ socket.

The Bluetooth 2 Click is the new and updated version of the famous Bluetooth2 Click.

Mikroe produces entire development toolchains for all major microcontroller architectures.

Committed to excellency, we are dedicated to helping engineers bring the project development up to speed and achieve outstanding results.





health and safety management system.



MIKROELEKTRONIKA D.O.O, Batajnički drum 23, 11000 Belgrade, Serbia VAT: SR105917343 Registration No. 20490918 Phone: + 381 11 78 57 600 Fax: + 381 11 63 09 644 E-mail: office@mikroe.com www.mikroe.com

Specifications

| Туре | BT/BLE |
|------------------|--|
| Applications | Handheld terminals, Industrial devices, Point- of-Sale systems, PCs, Personal Digital Assistants (PDAs), Computer Accessories, Access Points, Automotive Diagnostics Units. |
| On-board modules | Bluetooth 2 Click uses the WT41u module, a fully integrated Bluetooth 2.1 + EDR class 1 module, from Silicon Labs. |
| Key Features | Exceptional radio performance (TX power: +20 dBm, RX sensitivity: -90 dBm). Superior radio performance 110dB link budget provides 1000+ meter line-of-sight connectivity. |
| Interface | GPIO,SPI,UART |
| Compatibility | mikroBUS |
| Click board size | L (57.15 x 25.4 mm) |
| Input Voltage | 3.3V |

Resources

mikroBUS™

mikroBUS™

Click board™ Catalog

Click boards™

Downloads

Bluetooth 2 click example on Libstock

WT41U datasheet

Bluetooth 2 click schematic

Bluetooth 2 click 2D and 3D files

Mikroe produces entire development toolchains for all major microcontroller architectures.

Committed to excellency, we are dedicated to helping engineers bring the project development up to speed and achieve outstanding results.





health and safety management system.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Bluetooth Development Tools - 802.15.1 category:

Click to view products by MikroElektronika manufacturer:

Other Similar products are found below:

DA14580PRODTLKT 1628 SP14808ST MBH7BLZ02-EF-KIT FWM7BLZ20-EB-KIT SP14801-DUT SKY66111-21EK1 SECO-RSL10-TAG-GEVB ENW89857AXKF 3026 MIKROE-2471 MOD-NRF8001 BLE-IOT-GEVB 450-0184 EKSHCNZXZ EVAL_PAN1026 EVAL_PAN1720 EVAL_PAN1740 2267 2479 2487 2633 STEVAL-IDB005V1D STEVAL-IDB001V1 MIKROE-2545 SIPKITSLF001 2995 STEVAL-IDB007V1M 2829 DFR0267 DFR0296 DFR0492 TEL0073 BM-70-CDB WSM-BL241-ADA-008DK STEVAL-BTDP1 ACD52832 TEL0095 ISP1507-AX-TB RN-4871-PICTAIL DA14695-00HQDEVKT-P DA14695-00HQDEVKT-U EVK-NINA-B112 EBSHJNZXZ EKSGJNZWY EKSHJNZXZ BMD-200-EVAL-S ACN BREAKOUT BOARD ACN SKETCH 2269