


MIKROELEKTRONIKA D.O.O, Batajnički drum 23, 11000 Belgrade, Serbia VAT: SR105917343 Registration No. 20490918

Phone: + 381 11 78 57 600 Fax: + 381 11 63 09 644 E-mail: office@mikroe.com

USB to I2C Click





PID: MIKROE-5312

USB to I2C Click is an adapter add-on board with a general-purpose USB master to I2C/UART serial interface. This board features the <u>FT260</u> from <u>FTDI</u>, an interface device controller that provides a bridge between standard USB Human Interface Device (HID) class drivers and an I2C or UART slave devices. The FT260 is highly-integrated with a USB 2.0-compliant full-speed (12Mbps) transceiver, oscillator, LDO regulator, and on-chip eFUSE. It is supported by most operating systems where a custom driver is not required. With the possibility of use as a standalone device, this Click board ™ provides an ideal, fast-to-implement bridge between USB and either UART or I2C peripherals.

USB to I2C Click is supported by a $\underline{\mathsf{mikroSDK}}$ compliant library, which includes functions that simplify software development. This $\underline{\mathsf{Click}}$ board $\underline{\mathsf{mikroBUS}}^{\mathsf{m}}$ comes as a fully tested product, ready to be used on a system equipped with the $\underline{\mathsf{mikroBUS}}^{\mathsf{m}}$ socket.

Mikroe produces entire development toolchains for all major microcontroller architectures.

Committed to excellency, we are dedicated to helping engineers bring the project development up to speed and achieve outstanding results.





health and safety management system.



MIKROELEKTRONIKA D.O.O, Batajnički drum 23, 11000 Belgrade, Serbia VAT: SR105917343 Registration No. 20490918
Phone: + 381 11 78 57 600 Fax: + 381 11 63 09 644 E-mail: office@mikroe.com

www.mikroe.com

Specifications

Туре	USB
Applications	Can be used as a bridge between USB and either UART or I2C peripherals
On-board modules	FT260 - USB device that supports I2C and UART communication through standard USB HID class interfaces from FTDI
Key Features	Full speed HID class USB device, USB2.0 compliant with entire USB protocol handled on the chip, supported by most operation systems, custom driver is not required, I2C Master interface, standalone operation, and more
Interface	I2C,UART,USB
ClickID	No
Compatibility	mikroBUS
Click board size	M (42.9 x 25.4 mm)
Input Voltage	3.3V,5V

Resources

<u>mikroBUS™</u>

mikroSDK

Click board™ Catalog

Click boards™

Downloads


TLV1117 datasheet

MAX40200 datasheet

FT260 datasheet

USB to I2C click 2D and 3D files

USB to I2C click schematic







health and safety management system.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Interface Development Tools category:

Click to view products by MikroElektronika manufacturer:

Other Similar products are found below:

CHA2066-99F TW-DONGLE-USB XR21B1424IV64-0A-EVB STR-FUSB3307MPX-PPS-GEVK MAX7313EVKIT+ P0551

ZSC31010KITV2P1 TDP1204EVM 5346 SI32185ACB10SL1KIT Si32185ACB10SL0EVB RAA2S4252EXT 4901 DFR0979 LIME2SHIELD SC18IS604-EVB MIKROE-5276 CP2104-MINIEK 103030295 LVDS-18B-EVK MIKROE-2335 KIT_MINIWIGGLER_3_USB

KITXMC4XCOMETH001TOBO1 XR20M1170G16-0A-EB XR20M1170G16-0B-EB XR20M1170G24-0B-EB XR20M1172G28-0B-EB

73931-3022 SI871XSOIC8-KIT 1764 1833 TCA8418E-EVM 1862 EVAL-ADM2486EBZ EVAL-ADM2487EEB3Z

EVALISO11811TTOBO1 EVB-USB82514 ATAB663254A-V1.2 AS8650 DB V10 EVAL-ADM2587EEBZ EVAL-ADM3251EEB1Z

EVAL-ADUSB2EBUZ EVAL-ADUSB2EBZ EVAL-CN0160-EB1Z EVAL-CN0185-EB1Z EVB80104-A1 2264 MCP23X17EV PS09-EVA-KIT 237