RTC Board

Manual

All Mikroelektronika's development systems feature a large number of peripheral modules expanding microcontroller's range of application and making the process of program testing easier. In addition to these modules, it is also possible to use numerous additional modules linked to the development system through the I/O port connectors. Some of these additional modules can operate as stand-alone devices without being connected to the microcontroller.

Additional Board

RTC (Real-Time Clock)

A real-time clock is used to keep the real time and date, generate interrupt and provide timer and alarm functions. Due to a battery cell, the operation of the real-time clock is enabled even when the microcontroller's power supply goes off. The real-time clock is linked to a development system via a 2x5 female connector provided on the RTC board and a 2x5 male connector provided on the I/O port of the development system. The real-time clock communicates with the microcontroller using I²C serial communication.

DIP switch SW1 is used to select a development system to connect the RTC board to





Figure 1: RTC board

DIP switch SW1 is used to select a development system to connect the RTC additional board to. This switch also enables connection between the SDA, SCL and INT-RTC pins provided on the *RTC* board and a serial I²C module built into the microcontroller. Figure 3 shows the pinout of the DIP switch SW1.



2x5 female connector enables the additional board to be connected to a development system

Figure 2: RTC board's bottom view

The function of pins provided on the PCF8583P circuit that is used for connection with the microcontroller:

INT - Open drain interrupt output

SCL - Serial clock line
SDA - Serial data line

The function of pins provided on the 2x5 female connector CN1:

- PO SCL pin for EasyAVR and BIGAVR development systems;
- P1 SDA pin for EasyAVR and BIGAVR development systems;
- P2 SCL pin for BIGdsPIC, dsPICPRO, LV32MX and LV24-33 development systems; It is also used as an interrupt pin;
- SDA pin for BIGdsPIC, dsPICPRO, LV32MX and LV24-33 development systems and SCL pin for EasyPIC, BIGPIC, LV18FJ and EasyLV18 development systems;
- SDA pin for EasyPIC, BIGPIC, LV18FJ and EasyLV18 development systems;
- P5 Interrupt pin;




Figure 3: RTC board connection schematic




Figure 4: RTC board connected to a development system

If you want to learn more about our products, please visit our website at www.mikroe.com

If you are experiencing some problems with any of our products or just need additional information, please place your ticket at www.mikroe.com/en/support

If you have any questions, comments or business proposals, do not hesitate to contact us at office@mikroe.com

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Clock & Timer Development Tools category:

Click to view products by MikroElektronika manufacturer:

Other Similar products are found below:

AD9530/PCBZ DSC400-0333Q0032KE1-EVB TDGL013 ADCLK946/PCBZ EKIT01-HMC1032LP6G RV-2251-C3-EVALUATION-BOARD RV-3029-C2-EVALUATION-BOARD-OPTION-B SKY72310-11-EVB EV1HMC6475LC4B EV1HMC8364LP6G

EV1HMC8362LP6G RV-8263-C7-EVALUATION-BOARD EVK9FGV1002 EVK9FGV1008 EV1HMC6832ALP5L EVAL01-HMC911LC4B EVAL01-HMC987LP5E EVAL01-HMC988LP3E TS3002DB 125605-HMC702LP6CE MIKROE-2481 2045 EKIT01-HMC835LP6G EKIT01-HMC834LP6GE TS3006DB 105811-HMC440QS16G DSC-TIMEFLASH2-KIT1 110227-HMC510LP5 110227-HMC513LP5 AD9515/PCBZ AC164147 DFR0469 127102-HMC856LC5 127270-HMC765LP6CE 127272-HMC783LP6CE 127283-HMC807LP6CE 127900-HMC765LP6CE 129021-HMC838LP6CE ADM00791 DC2254A-B 3296 DC1959A-C DC2254A-A DC1562B-G DC2073A-G 129020-HMC838LP6CE 129467-HMC820LP6CE 129470-HMC821LP6CE 129472-HMC822LP6CE 129874-HMC910LC4B