

MAX solutions

Mill-Max Expands its Line of Receptacles with *Organic Fibre Plug*® Solder Barrier -- 14 Styles Offered, Tape & Reel Packaged

Mill-Max's organic fibre plug (OFP®) solder barrier receptacles are discrete sockets for through-hole soldering into printed circuit boards. These open bottom receptacles are fitted with organic fibre plugs to prevent solder, paste or flux from contaminating the internal contact during the placing and soldering process. When the device/mating lead is plugged into the receptacle the OFP® is knocked out allowing the mating lead to pass through the fingers of the internal contact and make a reliable electrical connection.

14 sizes/styles are now available, 13 have standard tape & reel packaging. The advantage of tape & reel packaging for these receptacles is it permits through-hole components to be placed simultaneously with surface mount parts on pick-'n-place assembly lines – eliminating the need to hand place the receptacles in an additional manufacturing step. The OFP® barrier permits the sockets to be vacuum picked from the tape prior to placement in a hole in the circuit board.



The knock-out-bottom feature enables these sockets to be made relatively short compared to many similar receptacles. The reduced length provides two advantages: the receptacles can stand upright and stable in a carrier tape pocket and the protrusion through the PCB is minimal — especially important when working with SMT boards. The open bottom receptacle design eliminates the need to trim long device leads that would otherwise bottom out in a closed receptacle design and also makes them ideal for low profile board stacking applications via the ability to pass through.

The OFP® parts are available as discrete receptacles and can be supplied in bulk or on carrier tape per EIA-481 for industry standard pick and place machines.

All Mill-Max receptacles use a precision-machined brass housing with a press-fit beryllium copper “multi-finger” contact.

(Intrusive reflow (also called "pin-in-paste") is a technique of using conventional through-hole components in a reflow soldering process. The receptacles are placed into plated-through-holes in the circuit board (solder paste has previously been screen printed on pads adjacent to the holes) and the board is reflowed in the same pass as other SMT components. Solder will fill the plated-through-holes and achieve solder joints as reliable as wave soldering. The OFP® barrier prevents solder paste from being picked-up inside the contact during pick 'n place assembly. "Overprinting" paste on the solder mask can be used to adjust the volume of paste required to fill each hole.)

Visit www.mill-max.com/PR626 for more information.

Mill-Max Mfg. Corp. • 190 Pine Hollow Road, Oyster Bay, NY 11771-0300
516-922-6000 • Fax: 516-922-9253 • www.mill-max.com





PIN RECEPTACLES

With Organic Fibre Plug® Solder Barrier
(see specific contact range on pages 216, 217 & 219)



- These through-hole (tubular) receptacles are designed for hand, wave or reflow* soldering. The **ORGANIC FIBRE PLUG®** barrier prevents solder, paste or flux from contaminating the spring contact.
- After soldering, the **OFFP®** barrier is pushed out of the receptacle when the device is plugged in.
- All parts are available as discrete receptacles; but for SMT assembly, certain receptacles are supplied on carrier tape per EIA-481 to feed industry standard pick and place machines.






**Intrusive reflow (also called "pin-in-paste") is a technique of using conventional through-hole components in a reflow soldering process. The receptacles are placed into plated through-holes in the circuit board (solder paste has previously been screen printed on pads adjacent to the holes) and the board is reflowed in the same pass as other SMT components. Solder will fill the plated through-holes and achieve solder joints as reliable as wave soldering. The OFFP® barrier prevents solder paste from being picked-up inside the contact during pick 'n place assembly. "Overprinting" paste on the solder mask can be used to adjust the volume of paste required to fill each hole.*

5359

0577

4015



5359-0-XX-XX-10-XX-10-0
Solder mount in $\varnothing.043 \pm .003$ PTH.
#10 Contact for $\varnothing.012-.017$ pins.
Also available on 16mm wide carrier tape: 3,000 parts per 13" reel.

0577-0-XX-XX-21-XX-10-0
Solder mount in $\varnothing.045 \pm .003$ PTH.
#21 Contact for $\varnothing.015-.022$ pins.
Also available on 12mm wide carrier tape: 3,000 parts per 13" reel.

4015-0-XX-XX-30-XX-10-0
Solder mount in $\varnothing.057 \pm .003$ PTH.
#30 Contact for $\varnothing.015-.025$ pins.
Also available on 8mm wide carrier tape: 5,500 parts per 13" reel.

SPECIFICATIONS

SHELL MATERIAL:
Brass Alloy 360, 1/2 Hard

CONTACT MATERIAL:
Beryllium Copper Alloy 172, HT

SOLDER BARRIER:
Organic Fibre Plug®

DIMENSION IN INCHES

TOLERANCES ON:

LENGTHS: $\pm .005$

DIAMETERS: $\pm .002$

ANGLES: $\pm 2^\circ$

ORDER CODE: XXXX - 0 - XX - XX - XX - XX - XX - 0

BASIC PART # →

SPECIFY PACKAGING:

43 Discrete Receptacles

67 Supplied on 13" Reels

SPECIFY SHELL FINISH:

01 200 μ " TIN/LEAD OVER NICKEL

◇ 80 200 μ " TIN OVER NICKEL (RoHS)

SPECIFY CONTACT FINISH:

◇ 27 30 μ " GOLD OVER NICKEL (RoHS)

02 100 μ " TIN/LEAD OVER NICKEL

◇ 84 100 μ " TIN OVER NICKEL (RoHS)

CONTACT

#10, #21 or #30 CONTACT (DATA ON PAGES 216, 217 & 219)





PIN RECEPTACLES

With Organic Fibre Plug® Solder Barrier
(see specific contact range on pages 220 - 228)



0337	4280	5280	0332
<p>0337-0-XX-XX-15-XX-10-0 Solder mount in $\varnothing.066 \pm .003$ PTH. #15 Contact for $\varnothing.020$-.032 pins. Also available on 8mm wide carrier tape: 6,000 parts per 13" reel.</p>	<p>4280-0-XX-XX-16-XX-10-0 Solder mount in $\varnothing.067 \pm .003$ PTH. #16 Contact for $\varnothing.022$-.034 pins. Also available on 8mm wide carrier tape: 6,000 parts per 13" reel.</p>	<p>5280-0-XX-XX-16-XX-40-0 Solder mount in $\varnothing.067 \pm .003$ PTH. #16 Contact for $\varnothing.022$-.034 pins. Also available on 16mm wide carrier tape: 2,200 parts per 13" reel.</p>	<p>0332-0-XX-XX-18-XX-10-0 Solder mount in $\varnothing.079 \pm .003$ PTH. #18 Contact for $\varnothing.037$-.043 pins. Also available on 16mm wide carrier tape: 2,200 parts per 13" reel.</p>

0479	0375	0353	0384
<p>0479-0-XX-XX-34-XX-10-0 Solder mount in $\varnothing.077 \pm .003$ PTH. #34 Contact for $\varnothing.032$-.046 pins. Also available on 16mm wide carrier tape: 2,000 parts per 13" reel.</p>	<p>0375-0-XX-XX-02-XX-10-0 Solder mount in $\varnothing.087 \pm .003$ PTH. #02 Contact for $\varnothing.040$-.050 pins. Also available on 12mm wide carrier tape: 4,500 parts per 13" reel.</p>	<p>0353-0-XX-XX-03-XX-10-0 Solder mount in $\varnothing.106 \pm .003$ PTH. #03 Contact for $\varnothing.040$-.060 pins. Also available on 12mm wide carrier tape: 1,300 parts per 13" reel.</p>	<p>0384-0-XX-XX-23-XX-10-0 Solder mount in $\varnothing.105 \pm .003$ PTH. #23 Contact for $\varnothing.045$-.065 pins. Also available on 12mm wide carrier tape: 1,700 parts per 13" reel.</p>

0376	0321	3435
<p>0376-0-XX-XX-07-XX-10-0 Solder mount in $\varnothing.133 \pm .003$ PTH. #07 Contact for $\varnothing.065$-.082 pins. Also available on 16mm wide carrier tape: 1,500 parts per 13" reel.</p>	<p>0321-0-XX-XX-08-XX-10-0 Solder mount in $\varnothing.144 \pm .003$ PTH. #08 Contact for $\varnothing.084$-.102 pins. Also available on 16mm wide carrier tape: 1,700 parts per 13" reel.</p>	<p>3435-0-XX-XX-47-XX-04-0 Solder mount in $\varnothing.046 \pm .003$ PTH. #47 Contact for $\varnothing.025$-.036 and .025" square pins.</p>

<p>SPECIFICATIONS SHELL MATERIAL: Brass Alloy 360, 1/2 Hard CONTACT MATERIAL: Beryllium Copper Alloy 172, HT SOLDER BARRIER: Organic Fibre Plug® DIMENSION IN INCHES TOLERANCES ON: LENGTHS: $\pm .005$ DIAMETERS: $\pm .002$ ANGLES: $\pm 2^\circ$</p>	<p>ORDER CODE: XXXX - 0 - XX - XX - XX - XX - XX - 0</p> <p>BASIC PART # →</p> <p>SPECIFY PACKAGING: →</p> <p>43 Discrete Receptacles 67 Supplied on 13" Reels</p> <p>SPECIFY SHELL FINISH: →</p> <p>01 200μ" TIN/LEAD OVER NICKEL ◇ 80 200μ" TIN OVER NICKEL (RoHS)</p> <p style="text-align: center;">CONTACT</p> <p>#02,#07,#08,#15,#16,#18,#23,#34 or #47 CONTACT (DATA ON PAGES 220 - 228)</p>	<p>SPECIFY CONTACT FINISH:</p> <p>◇ 27 30μ" GOLD OVER NICKEL (RoHS) 01 200μ" TIN/LEAD OVER NICKEL ◇ 80 200μ" TIN OVER NICKEL (RoHS)</p>
---	--	--



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Circuit Board Hardware - PCB category](#):

Click to view products by [Mill-Max manufacturer](#):

Other Similar products are found below :

[8919-0-00-15-00-00-03-0](#) [0135-0-15-01-30-27-04-0](#) [5970-1-15-01-32-14-04-0](#) [0149-0-15-15-30-27-04-0](#) [MBI 1 BLUE](#) [7305-0-15-15-47-14-10-0](#) [MLN 150/1 BLACK](#) [8579-0-15-80-11-27-10-0](#) [8579-1-15-15-11-27-10-0](#) [8830-0-15-01-22-14-10-0](#) [8836-0-00-21-00-00-03-0](#) [PRUEF 2 RED](#) [9976-0-00-00-00-00-03-0](#) [PW1616](#) [1215-3-05-00-00-00-01-0](#) [1231](#) [1303-0-15-15-47-14-04-0](#) [1404-3](#) [1404-4](#) [1406-4](#) [1407-3](#) [1406-3](#) [1407-4](#) [1408-3](#) [1424-4](#) [1427-3](#) [1419-4](#) [1426-4](#) [1548-103](#) [1938-0-00-00-00-00-03-0](#) [1942-0-00-00-00-00-03-0](#) [2101-3-00-44-00-00-07-0](#) [2108-2-00-50-00-00-07-0](#) [2109-2-00-44-00-00-07-0](#) [2110-2-00-44-00-00-07-0](#) [2111-2-00-00-00-00-07-0](#) [2113-4-00-44-00-00-07-0](#) [2301-3-00-44-00-00-07-0](#) [2308-1-00-50-00-00-07-0](#) [2313-2-00-00-00-00-07-0](#) [2315-2-01-44-00-00-07-0](#) [2333-1-00-50-00-00-07-0](#) [9000-0-00-00-00-00-03-0](#) [2506-2-00-50-00-00-07-0](#) [2507-2-01-44-00-00-07-0](#) [2508-2-00-44-00-00-07-0](#) [2561-2-00-44-00-00-07-0](#) [9220](#) [9234-0-15-15-30-14-10-0](#) [LAS S G BLACK](#)