

<h3>0501</h3> <p><b>0501-0-15-XX-30-XX-04-0</b> Press-fit in .057 mounting hole</p>	<h3>8427</h3> <p><b>8427-0-15-XX-30-XX-04-0</b> Press-fit in .057 mounting hole</p>	<h3>1434</h3> <p><b>1434-0-15-XX-30-XX-10-0</b> Press-fit in .055 mounting hole</p>	<h3>9970</h3> <p><b>9970-0-15-XX-30-XX-04-0</b> Square press-fit for .032 ±.002 plated thru hole</p>
---	---	---	--

<h3>5970</h3> <p><b>5970-X-15-XX-32-XX-04-0</b> Square press-fit for .032 or .039 ±.002 plated thru hole</p>	<table border="1"> <thead> <tr> <th>Basic Part Number</th> <th>U Square</th> <th>Mounting Hole</th> </tr> </thead> <tbody> <tr> <td>5970-1</td> <td>.028</td> <td>.032</td> </tr> <tr> <td>5970-2</td> <td>.034</td> <td>.039</td> </tr> </tbody> </table>	Basic Part Number	U Square	Mounting Hole	5970-1	.028	.032	5970-2	.034	.039	<h3>0477/0478</h3> <p><b>047X-0-18-XX-30-XX-04-0</b> Solderless press-fit in .038 +.003 / -.002 plated thru hole (use 1.1mm drill prior to plating)</p>	<table border="1"> <thead> <tr> <th>Basic Part Number</th> <th>Board Thickness</th> <th>Length V</th> <th>Length A</th> </tr> </thead> <tbody> <tr> <td>0477-0</td> <td>.062</td> <td>.075</td> <td>.175</td> </tr> <tr> <td>0478-0</td> <td>.125</td> <td>.140</td> <td>.250</td> </tr> </tbody> </table>	Basic Part Number	Board Thickness	Length V	Length A	0477-0	.062	.075	.175	0478-0	.125	.140	.250
Basic Part Number	U Square	Mounting Hole																						
5970-1	.028	.032																						
5970-2	.034	.039																						
Basic Part Number	Board Thickness	Length V	Length A																					
0477-0	.062	.075	.175																					
0478-0	.125	.140	.250																					

<h3>4612</h3> <p><b>4612-0-31-XX-30-XX-04-0</b> Compliant press-fit in .040 ±.003 plated hole. For .060 → .100 thick board</p>	<h3>4613</h3> <p><b>4613-0-31-XX-30-XX-04-0</b> Compliant press-fit in .040 ±.003 plated hole. For .090 → .130 thick board</p>	<h3>0680</h3> <p><b>0680-0-15-XX-32-XX-10-0</b> Solder mount in .051 min. mounting hole</p>	<h3>0149</h3> <p><b>0149-0-15-XX-30-XX-04-0</b> Press-fit in .059 mounting hole</p>
--	--	---	---

<p><b>SPECIFICATIONS</b></p> <p><b>SHELL MATERIAL:</b> Brass Alloy 360, 1/2 Hard</p> <p><b>CONTACT MATERIAL:</b> Beryllium Copper Alloy 172, HT</p> <p><b>DIMENSION IN INCHES</b> <b>TOLERANCES ON:</b> LENGTHS: ±.005 DIAMETERS: ±.002 ANGLES: ± 2°</p>	<p><b>ORDER CODE: XXXX - X - XX - XX - 3X - XX - XX - 0</b></p> <p><b>BASIC PART #</b> →</p> <p><b>SPECIFY SHELL FINISH:</b> →</p> <p><b>01</b> 200μ" TIN/LEAD OVER NICKEL <b>15</b> 10μ" GOLD OVER NICKEL</p> <p><b>SPECIFY CONTACT FINISH:</b> →</p> <p><b>02</b> 200μ" TIN/LEAD OVER NICKEL <b>14</b> 10μ" GOLD OVER NICKEL <b>27</b> 30μ" GOLD OVER NICKEL</p> <p><b>SELECT CONTACT</b></p> <p><b>#30 or #32 CONTACT (DATA ON PAGE 208)</b></p>
--	---

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Circuit Board Hardware - PCB category](#):*

*Click to view products by [Mill-Max manufacturer](#):*

Other Similar products are found below :

[8919-0-00-15-00-00-03-0](#) [0135-0-15-01-30-27-04-0](#) [5970-1-15-01-32-14-04-0](#) [0149-0-15-15-30-27-04-0](#) [MBI 1 BLUE](#) [7305-0-15-15-47-14-10-0](#) [MLN 150/1 BLACK](#) [8579-0-15-80-11-27-10-0](#) [8579-1-15-15-11-27-10-0](#) [8830-0-15-01-22-14-10-0](#) [8836-0-00-21-00-00-03-0](#) [PRUEF 2 RED](#) [9976-0-00-00-00-00-03-0](#) [PW1616](#) [1215-3-05-00-00-00-01-0](#) [1231](#) [1303-0-15-15-47-14-04-0](#) [1404-3](#) [1404-4](#) [1406-4](#) [1407-3](#) [1406-3](#) [1407-4](#) [1408-3](#) [1424-4](#) [1427-3](#) [1419-4](#) [1426-4](#) [1548-103](#) [1938-0-00-00-00-00-03-0](#) [1942-0-00-00-00-00-03-0](#) [2101-3-00-44-00-00-07-0](#) [2108-2-00-50-00-00-07-0](#) [2109-2-00-44-00-00-07-0](#) [2110-2-00-44-00-00-07-0](#) [2111-2-00-00-00-00-07-0](#) [2113-4-00-44-00-00-07-0](#) [2301-3-00-44-00-00-07-0](#) [2308-1-00-50-00-00-07-0](#) [2313-2-00-00-00-00-07-0](#) [2315-2-01-44-00-00-07-0](#) [2317-2-00-50-00-00-07-0](#) [2333-1-00-50-00-00-07-0](#) [9000-0-00-00-00-00-03-0](#) [2506-2-00-50-00-00-07-0](#) [2507-2-01-44-00-00-07-0](#) [2508-2-00-44-00-00-07-0](#) [2561-2-00-44-00-00-07-0](#) [9220](#) [9234-0-15-15-30-14-10-0](#)