



# DUAL-IN-LINE SOCKETS

## SERIES 605, 614 • CARRIER TYPE, LOW PROFILE • OPEN FRAME



- Low profile receptacles sit only 0,79 high above the board
- Removable plastic carriers can be returned for reloading
- Hi-Rel, 3-finger BeCu #11 contact is rated at 3 amps. See page 251 for details
- Series 605 and 614 use MM #1407 & #0548 pins. See page 157 for details
- Insulators are high temperature thermoplastic, suitable for all soldering operations
- For Electrical, Mechanical and Environmental Data, see page 264 for details



Total number of pins				Quantity per tube	ORDERING INFORMATION			
	A	B	C		Length = 3,71 (0,99 Min. Mounting Hole)	Length = 3,94 (0,89 Min. Mounting Hole)		
10	12,6	5,08	7,6	40	614-XX-210-31-007000	605-XX-210-11-480000		
4	5,0	7,62	10,1	102	614-XX-304-31-007000	605-XX-304-11-480000		
6	7,6	7,62	10,1	68	614-XX-306-31-007000	605-XX-306-11-480000		
8	10,1	7,62	10,1	50	614-XX-308-31-007000	605-XX-308-11-480000		
10	12,6	7,62	10,1	40	614-XX-310-31-007000	605-XX-310-11-480000		
14	17,7	7,62	10,1	28	614-XX-314-31-007000	605-XX-314-11-480000		
16	20,3	7,62	10,1	25	614-XX-316-31-007000	605-XX-316-11-480000		
18	22,8	7,62	10,1	22	614-XX-318-31-007000	605-XX-318-11-480000		
20	25,3	7,62	10,1	20	614-XX-320-31-007000	605-XX-320-11-480000		
22	27,8	7,62	10,1	18	614-XX-322-31-007000	605-XX-322-11-480000		
24	30,4	7,62	10,1	16	614-XX-324-31-007000	605-XX-324-11-480000		
28	35,5	7,62	10,1	14	614-XX-328-31-007000	605-XX-328-11-480000		
20	25,4	10,16	12,7	20	614-XX-420-31-007000	605-XX-420-11-480000		
22	27,8	10,16	12,7	18	614-XX-422-31-007000	605-XX-422-11-480000		
24	30,4	10,16	12,7	16	614-XX-424-31-007000	605-XX-424-11-480000		
28	35,5	10,16	12,7	14	614-XX-428-31-007000	605-XX-428-11-480000		
32	40,6	10,16	12,7	12	614-XX-432-31-007000	605-XX-432-11-480000		
24	30,4	15,24	17,7	16	614-XX-624-31-007000	605-XX-624-11-480000		
28	35,5	15,24	17,7	14	614-XX-628-31-007000	605-XX-628-11-480000		
32	40,6	15,24	17,7	12	614-XX-632-31-007000	605-XX-632-11-480000		
36	45,7	15,24	17,7	11	614-XX-636-31-007000	605-XX-636-11-480000		
40	50,8	15,24	17,7	10	614-XX-640-31-007000	605-XX-640-11-480000		
42	53,3	15,24	17,7	9	614-XX-642-31-007000	605-XX-642-11-480000		
48	60,9	15,24	17,7	8	614-XX-648-31-007000	605-XX-648-11-480000		
50	63,5	15,24	17,7	8	614-XX-650-31-007000	605-XX-650-11-480000		
52	66,0	15,24	17,7	7	614-XX-652-31-007000	605-XX-652-11-480000		
50	63,5	22,86	25,3	8	614-XX-950-31-007000	605-XX-950-11-480000		
52	66,0	22,86	25,3	7	614-XX-952-31-007000	605-XX-952-11-480000		
64	81,2	22,86	25,3	6	614-XX-964-31-007000	605-XX-964-11-480000		
<b>SPECIFY PLATING CODE XX =</b>					91	93	41 ◆	43 ◆
Sleeve (Pin)					5,08µm Sn/Pb	5,08µm Sn/Pb	5,08µm Sn	5,08µm Sn
Contact (Clip)					0,25µm Au	0,76µm Au	0,25µm Au	0,76µm Au



**XX=Plating Code  
See Below**



## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [IC & Component Sockets](#) category:*

*Click to view products by [Mill-Max](#) manufacturer:*

Other Similar products are found below :

[0066-3-17-15-30-14-02-0](#) [670](#) [672](#) [673](#) [694-13-640-00-672-000](#) [712-93-120-41-001000](#) [714-93-104-31-018000](#) [8059-4G1-LF](#) [807-22-001-10-001101](#) [807-22-001-10-006101](#) [807-22-001-30-011101](#) [807-22-001-30-012101](#) [807-22-001-30-013101](#) [807-22-001-30-014101](#) [8-1437531-4](#) [8150-6P10](#) [833-93-034-10-001000](#) [851-41-006-10-001000](#) [851-43-008-20-001000](#) [851-43-014-20-001000](#) [851-93-006-20-001000](#) [851-93-010-20-001000](#) [853-43-020-10-001000](#) [86.010.0053.0](#) [116-43-308-41-007000](#) [PX-68LCC](#) [121-13-318-41-001000](#) [121-13-320-41-001000](#) [121-13-308-41-001000](#) [123-43-314-41-801000](#) [123-43-420-41-001000](#) [123-87-320-41-001101](#) [122-13-316-41-001000](#) [123-13-624-41-001000](#) [123-43-306-41-001000](#) [12-3513-11](#) [123-91-320-41-001000](#) [126-43-310-41-002000](#) [AKSUN 37V-T](#) [1437503-9](#) [1437504-1](#) [146-44-308-41-013000](#) [APO-320-G-T](#) [146-43-308-41-012000](#) [160-10-308-00-001000](#) [160-40-320-00-001000](#) [214-99-306-01-670800](#) [232-1270-02-0602](#) [2-382761-4](#) [2-5331677-4](#)