

## Detailed Specifications

<b>Frame Width:</b>	172[mm]
<b>Frame Height:</b>	172[mm]
<b>Frame Depth:</b>	50[mm]
<b>Max. Air Flow:</b>	346[CFM]
<b>Max. Air Flow:</b>	9.8[m3 per min]
<b>Max. Static Pressure:</b>	1.25[In H2O]
<b>Max. Static Pressure:</b>	312[Pa]
<b>Fan Speed:</b>	4600[RPM]
<b>Noise:</b>	62[dB]
<b>Life Expectancy:</b>	25 degree C 100,000 Hours[L10]
<b>Bearing Type:</b>	Ball Bearing
<b>Nominal Voltage:</b>	24[V]
<b>Operating Voltage 0 Lower:</b>	18[V]
<b>Operating Voltage 0 Upper:</b>	26.4[V]
<b>Current:</b>	1.8[A]
<b>Input Power:</b>	43.2[W]
<b>Mass:</b>	950[g]
<b>IP Rating:</b>	IP68/IP69K
<b>Tach / Locked Rotor Output:</b>	No

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [DC Fans](#) category:*

*Click to view products by [MinebeaMitsumi](#) manufacturer:*

Other Similar products are found below :

[614R](#) [AUB0612L](#) [AFB0948HH-S687](#) [G2E085-AA05-10](#) [4318/12T](#) [AUB0912H-F00](#) [3412N/2ME](#) [W2G110-AM39-01](#) [8412GLV](#) [8412NGL-12](#) [6448-384](#) [4114N/17-251](#) [4318/2R](#) [4412F/2D](#) [424JMU](#) [4414/2HH](#) [4112 N/12GL-175](#) [9GA0912F402](#) [9GA0812B20011](#)  
[AFB0824SHBAV1](#) [DV5214/2NP-230](#) [9GA0912H4021](#) [THC1548MGDJJ](#) [9GA0812B2001](#) [GFB1224SHG](#) [8500NU](#) [9WG1212E101-E](#)  
[3241.124](#) [DC0401012V2B-3T0](#) [ASFP14391](#) [ASFP64371](#) [ASFP64391](#) [ASFP84391](#) [ASFP92391](#) [9A0612G402](#) [AD5012HB-C71](#)  
[AD5012MB-C71](#) [ASFP84372](#) [ASFP64372](#) [31100-000440-RS](#) [ASFP14372](#) [ASFP16371](#) [ASFP40770](#) [ASFP42770](#) [ASFP44770](#) [ASFP64392](#)  
[ASFP82392](#) [ASFP84392](#) [ASFP92371](#) [ASFP92392](#)