


SPECIFICATION FOR APPROVAL

CUSTOMER		CUST P/N.	
ITEM	SMD Power Inductors	Description	UT3015N-2R2M
PART NO.	305-96207	DATE	2017.06.23

<p>(1) DIMENSION(UNIT:mm)</p> 		A	3.0±0.2	mm
		B	3.0±0.2	mm
		C	1.5 (Max)	mm
		D	1.5REF	mm
		E	0.9REF	mm
		F	2.78REF	mm
				mm
				mm

(2) ELECTRICAL REQUIREMENTS			
TEST CONDITION	FREQUENCY	VOLTAGE	(3) TEST INSTRUMENTS
			LCR-METER:
L	2.2μH±20%	100KHz 1V	V WK3260B
			V TH2816
DCR	0.079Ω±30%	KHz V	DC RESISTANCE METER:
			V WK3260B
Isat	1.08A(Max)at L drop30%TYP	100KHz 1V	CURRENT SOURCE:
			V TH2816+1320
Irms	2.0A(Max)atΔT=40°C	100KHz 1V	RFIMPENDANCE/MATERIAL ANALYZER
			V TH2816+1320
		MHz V	GW PUNCTURE INSULATION TESTER

(4)TURN:TS(REF)

(5)MATERIAL LIST

ITEM		
1	CORE	LQH 3*3*1.35-1.35 FH20
2	WIRE	G1-H-180Ø0.14mm*7.5Ts
3	EPOXY	DA-1001BK
4	INK	BLACK

REMARK:	APPROVED	CHECKED	DRAWN BY
	姜杰文	姜法寶	王艷

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Fixed Inductors](#) category:

Click to view products by [MINGSTAR](#) manufacturer:

Other Similar products are found below :

[CR32NP-151KC](#) [CR32NP-180KC](#) [CR32NP-181KC](#) [CR32NP-1R5MC](#) [CR32NP-390KC](#) [CR32NP-3R9MC](#) [CR32NP-680KC](#) [CR32NP-820KC](#) [CR32NP-8R2MC](#) [CR43NP-390KC](#) [CR43NP-560KC](#) [CR43NP-680KC](#) [CR54NP-181KC](#) [CR54NP-470LC](#) [CR54NP-820KC](#) [CR54NP-8R5MC](#) [70F224AI](#) [MGDQ4-00004-P](#) [MHL1ECTTP18NJ](#) [MHQ1005P10NJ](#) [MHQ1005P1N0S](#) [MHQ1005P2N4S](#) [MHQ1005P3N6S](#) [MHQ1005P5N1S](#) [MHQ1005P8N2J](#) [PE-51506NL](#) [PE-53601NL](#) [PE-53602NL](#) [PE-53630NL](#) [PE-53824SNLT](#) [PE-92100NL](#) [PG0434.801NLT](#) [PG0936.113NLT](#) [9220-20](#) [9310-16](#) [PM06-2N7](#) [PM06-39NJ](#) [A01TK](#) [1206CS-471XJ](#) [HC2LP-R47-R](#) [HC2-R47-R](#) [HC3-2R2-R](#) [HCF1305-3R3-R](#) [1206CS-151XG](#) [RCH664NP-140L](#) [RCH664NP-4R7M](#) [RCH8011NP-221L](#) [RCP1317NP-332L](#) [RCP1317NP-391L](#) [RCR1010NP-470M](#)