# Coaxial **Matching Pad**

## 50/75Ω

В

MAX 4

(Ó)

### **Maximum Ratings**

Operating Temperature	-55°C to 100°C
Storage Temperature	-55°C to 100°C
RF Input Power	0.25W
Permanent damage may occur if any	of these limits are exceeded.

**Outline Drawing** 

BNC FEMALE CONN

D±.05

В

.62 15.75 49.28

Outline Dimensions (inch mm)

1.94 grams

wt

30.0

D

BNC MALE

CONN

### DC to 2000 MHz

### Features

- excellent VSWR 1.15: typ.
- excellent flatness
- wideband coverage, DC to 2000 MHz

#### **Applications**

impedance matching

## **BMP-5075R+**



CASE STYLE: FF747

Connectors Model 75ΩF-BNC BMP-5075R+ 50ΩM-BNC

+RoHS Compliant The +Suffix identifies RoHS Compliance. See our web site for RoHS Compliance methodologies and qualifications


### **Electrical Specifications**


FREQ. (MHz)	ATTENUATION (dB) Flatness Max.			VSWR (:1) Max.			POWER (W)	
f <sub>L</sub> -f <sub>U</sub>	Nom.	DC-100 MHz	100-1000 MHz	1000-2000 MHz	DC-100 MHz	100-1000 MHz	1000-2000 MHz	
DC-2000	5.7±0.1	0.2	0.3	0.4	1.06	1.22	1.4	0.25

### **Typical Performance Data**

Frequency (MHz)	Attenuation (dB)	VSWR (:1)		
	()	<b>50</b> Ω	<b>75</b> Ω	
10.00	5.71	1.01	1.00	
20.00	5.71	1.01	1.00	
60.00	5.71	1.01	1.00	
100.00	5.72	1.01	1.00	
110.00	5.71	1.01	1.01	
555.00	5.71	1.13	1.04	
1000.00	5.74	1.07	1.12	
1010.00	5.74	1.07	1.12	
1505.00	5.74	1.03	1.09	
2000.00	5.61	1.04	1.25	

### **Electrical Schematic** R1 $\sim$ 50 OHMS MALE 75 OHMS FEMALE R2 ≥ 0





A Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document. B. Electrical specifications and performance data contained in this specification document are based on Min-Circuit's applicable established test performance criteria and measurement instructions. C. The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuit's website at www.minicircuits.com/MCLStore/terms.jsp



### Mini-Circuits

www.minicircuits.com P.O. Box 350166, Brooklyn, NY 11235-0003 (718) 934-4500 sales@minicircuits.com

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for RF Adapters - In Series category:

Click to view products by Mini-Circuits manufacturer:

Other Similar products are found below :

 5916-1103-603
 5918-1103-000
 5919-1503-000
 651A505
 82-5552
 9030-9523-502
 A0407000
 R114703000W
 R1257704000
 R125771001

 R141710000W
 R141723161
 R141730000
 R143730700
 R143770000
 R161703000W
 R161753000W
 R161791500W

 R161791530W
 R201705000
 R222705200
 R222M40010W
 R223703180
 R316754000
 R405006000
 R443162000
 AD78TL
 HRM-513S

 1996352-2
 2157155-1
 252169-75
 AD158
 2101130-1
 252186
 R114704000W
 R114720000W
 R125705001
 R125771000

 R125771001W
 R125791501W
 R127704001
 R127.870.001
 R127872001
 R141717000
 R142710000
 R143703000
 R143704000