

FIXED ATTENUATORS

Designer's Kit K2-UNAT+

MINI-CIRCUITS DESIGNER'S KITS
SPEED UP
 THE SOLUTION!



DC to 6 GHz

UNAT+ Features

- Wideband, 50Ω
- 1 dB through 30 dB attenuation
- Type-N male & female connectors
- Rugged Unibody construction
- Small size 2.1"
- Very low cost



All models are
RoHS compliant

Kit K2-UNAT+ Electrical specifications of each model (13 models, 1 of each, 13 total)

| Model | Freq. (GHz) | Attenuation ² (dB) | | | | | VSWR (:1) | | | | | Input Power (W) | |
|----------|----------------|----------------------------------|------|------|------|------|--------------|------|------|-----------|------|-----------------------|-------------------|
| | | Flatness ¹ | | | | | DC-3 GHz | | | 3-4.5 GHz | | | 4.5-6 GHz Typ. |
| | | Nom. | Typ. | Typ. | Typ. | Typ. | Typ. | Max. | Typ. | Max. | | | |
| UNAT-1+ | DC-6 | 1±0.3 | 0.20 | 0.15 | 0.10 | 0.45 | 1.05 | 1.20 | 1.10 | 1.43 | 1.40 | 1.0 | |
| UNAT-2+ | DC-6 | 2±0.3 | 0.20 | 0.25 | 0.15 | 0.50 | 1.07 | 1.20 | 1.22 | 1.43 | 1.50 | 1.0 | |
| UNAT-3+ | DC-6 | 3±0.3 | 0.20 | 0.10 | 0.10 | 0.35 | 1.05 | 1.20 | 1.22 | 1.43 | 1.50 | 1.0 | |
| UNAT-4+ | DC-6 | 4±0.3 | 0.15 | 0.15 | 0.10 | 1.40 | 1.05 | 1.20 | 1.10 | 1.43 | 1.50 | 1.0 | |
| UNAT-5+ | DC-6 | 5±0.3 | 0.15 | 0.15 | 0.10 | 0.35 | 1.05 | 1.20 | 1.10 | 1.43 | 1.50 | 1.0 | |
| UNAT-6+ | DC-6 | 6±0.3 | 0.15 | 0.15 | 0.15 | 0.40 | 1.05 | 1.20 | 1.20 | 1.43 | 1.50 | 1.0 | |
| UNAT-7+ | DC-6 | 7±0.3 | 0.10 | 0.10 | 0.15 | 0.20 | 1.05 | 1.20 | 1.10 | 1.43 | 1.50 | 1.0 | |
| UNAT-8+ | DC-6 | 8±0.3 | 0.10 | 0.10 | 0.10 | 0.10 | 1.05 | 1.20 | 1.10 | 1.43 | 1.50 | 1.0 | |
| UNAT-9+ | DC-6 | 9±0.3 | 0.15 | 0.10 | 0.10 | 0.15 | 1.05 | 1.20 | 1.10 | 1.43 | 1.50 | 1.0 | |
| UNAT-10+ | DC-6 | 10±0.3 | 0.10 | 0.20 | 0.20 | 0.40 | 1.15 | 1.25 | 1.20 | 1.50 | 1.50 | 1.0 | |
| UNAT-15+ | DC-6 | 15±0.3 | 0.20 | 0.35 | 0.20 | 0.60 | 1.15 | 1.43 | 1.20 | 1.80 | 1.70 | 1.0 | |
| UNAT-20+ | DC-6 | 20±0.3 | 0.45 | 0.45 | 0.40 | 0.75 | 1.15 | 1.25 | 1.20 | 1.43 | 1.30 | 0.5 | |
| UNAT-30+ | DC-6 | 30±0.3 | 1.20 | 0.70 | 0.40 | 2.30 | 1.04 | 1.25 | 1.07 | 1.25 | 1.10 | 0.5 | |

1. Flatness = variation over band divided by 2.

2. Attenuation varies by 0.3dB max. over temperature.



P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661 For quick access to product information see MINI-CIRCUITS CATALOG & WEB SITE

RF/IF & MICROWAVE COMPONENTS

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [RF Development Tools](#) category:

Click to view products by [Mini-Circuits](#) manufacturer:

Other Similar products are found below :

[MAAM-011117](#) [MAAP-015036-DIEEV2](#) [EV1HMC1113LP5](#) [EV1HMC6146BLC5A](#) [EV1HMC637ALP5](#) [122410-HMC686LP4E](#) [ADL5363-EVALZ](#) [130437-HMC1010LP4E](#) [EKIT01-HMC1197LP7F](#) [SKYA21001-EVB](#) [SMP1331-085-EVB](#) [EVAL01-HMC1041LC4](#) [MAAL-011111-000SMB](#) [MAAM-009633-001SMB](#) [107712-HMC369LP3](#) [107780-HMC322ALP4](#) [SP000416870](#) [EV1HMC520ALC4](#) [EV1HMC244AG16](#) [EV1HMC539ALP3](#) [124694-HMC742ALP5](#) [SC20ASATEA-8GB-STD](#) [MAX2692EVKIT#](#) [SKY12343-364LF-EVB](#) [108703-HMC452QS16G](#) [119197-HMC658LP2](#) [EV1HMC647ALP6](#) [ADL5725-EVALZ](#) [106815-HMC441LM1](#) [UXN14M9PE](#) [SIMSA868-DKL](#) [SIMSA868C-DKL](#) [SKY65806-636EK1](#) [SKY68020-11EK1](#) [SKY67159-396EK1](#) [SKY66181-11-EK1](#) [SKY65804-696EK1](#) [SKY13396-397LF-EVB](#) [SKY13380-350LF-EVB](#) [SKY13355-374LF-EVB](#) [SKY13322-375LF-EVB](#) [SKY12207-478LF-EVB](#) [SE5023L-EK1](#) [SE5004L-EK1](#) [SE2436L-EK1](#) [Se2435L-EK1](#) [CLA4609-086-EVB](#) [SIMSA915C-DKL](#) [SIMSA915-DKL](#) [SIMSA433C-DKL](#)