

RLM-751-2WL+

The Big Deal

- Wideband, 3 to 750 MHz
- Low Insertion Loss, 0.20dB typical
- Fast Recovery Time, 4nSec
- Excellent VSWR 1.13:1 typical
- Low leakage power, 8dBm typical



Product Overview

RLM-751-2W+ constitutes a very reliable limiting component. It exhibits typical output leakage powers of 7.2dBm at 30 and 32dBm input powers throughout the 3 to 750 frequency range. It also presents an excellent delta output power versus the delta input power of 0.3dB/dB typical, within its input power limiting range of 12 to 32dBm. It's low insertion loss combined with the excellent return loss, recovery and response time features, makes this component suitable for many applications.

Key Features

Feature	Advantages						
Diode Limiting	The special combination of diode technologies allows for fast response and recovery times at the same time as low leakage output powers are obtained						
Broad band	Its operational frequency range is suitable for many military and civil applications.						
Input & Output matched	Allows for an easy and power efficient integration of the component when it is placed in a cascaded fashion within a complex system.						
Low Insertion Loss of 0.20 dB typical at the low drive regime.	Minimizes the impact on the overall system's insertion loss for low drive signals.						

Notes
A. Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.
B. Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions.
C. The parts covered by this specification document are subject to Mini-Circuit's standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuit's website at www.minicircuits.com/MCLStore/terms.jsp



+5 to +33 dBm Limiter

3 to 750 MHz Broadband **50**Ω


Maximum Ratings

Operating Temperature	-40°C to 85°C
Storage Temperature	-55°C to 100°C
RF Input Power	3W
Permanent damage may occur if any o	of these limits are exceeded.

Pin Connections

INPUT	1
OUTPUT	4
GROUND	2,3,5,6


Outline Drawing



Outline Dimensions (inch)

А	в	С	D	Е	F	G	н
.25	.31	.16	.100	.040	.055	.060	.065
6.35	7.87	4.06	2.54	1.02	1.40	1.52	1.65
J	к	L	М	Ν	Р	Q	wt.
							wt. grams

Demo Board MCL P/N: TB-393 Suggested PCB Layout (PL-258)



NOTES: 1. TRACE WIDTH IS SHOWN FOR ROGERS R04350B WITH DIELECTRIC THICKNESS .030" ± .002"; COPPER: 1/2 02. EACH SIDE. FOR OTHER MATERIALS TRACE WIDTH MAY NEED TO BE WODFIED. 2. BOTTOM SIDE OF THE PCB IS CONTINUOUS GROUND PLANE. DENOTES PCB COPPER LAYOUT WITH SMOBC (SOLDER MASK OVER BARE COPPER)

DENOTES COPPER LAND PATTERN FREE OF SOLDER MASK

Notes
A. Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.
B. Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions.
C. The parts covered by this specification document are subject to Mini-Circuit's standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and memedies thereunder, please visit Mini-Circuit's website at www.minicircuits.com/MCLStore/terms.jsp

Features

- wideband, 3 to 750 MHz
- low insertion loss 0.20 dB typ.
- fast recovery time, 4nsec typ.
- excellent VSWR 1.13:1 typ.
- · low output power, 8.0 dBm typ.

Applications

- military, hi-rel applications
- stabilizing generator outputs
- reducing amplitude variations
- · protects low noise amplifiers and other devices from ESD or input power damage

RLM-751-2WL+



Generic photo used for illustration purposes only CASE STYLE: TT1224

+RoHS Compliant The +Suffix identifies RoHS Compliance. See our web site for RoHS Compliance methodologies and qualifications

Electrical Specifications

Parameter	Condition	Min.	Тур.	Max.	Units				
Frequency Range		3		750	MHz				
Linear Range									
Max Input Power	less than 0.1 dB compression	—	_	-10	dBm				
Insertion Loss	less than -10 dBm input power	-	0.20	0.9	dB				
VSWR	less than -10 dBm input power	_	1.13	1.6	:1				
Limiting Range									
Input Power	>1dB compression filtered signal frequency	+5	—	+33	dBm				
Output Power		—	+8.0	_	dBm				
	Input Power Range (dBm)								
	5 to 12	-	0.3	—					
Δ Output/ Δ 1dB Input	12 to 20	_	0.3	—					
	20 to 25	-	0.3	_	dB/dB				
	25 to 30	-	0.13	_					
	30 to 33	_	0.05	_					
Recovery Time	1 watt pulse 50 μsec PW 1kHz duty cycle recovery to within 90% of final value.	_	4	—	nsec				
Response Time	-30 to +30 dBm input 50 µsec PW 1 kHz duty cycle	—	7.2	_	nsec				

Typical Performance Data


	I. Loss (dB) in Linear	in Linear	Power Output (dBm)				Δ Output / Δ 1dB Input						
	Range	Range	+5 dBm	+12 dBm	+20 dBm	+25 dBm	+30 dBm	+33 dBm	+5 to +12 dBm	+12 to +20 dBm	+20 to +25 dBm	+25 to +30 dBm	+30 to +33 dBm
	at -10 dBm	at -10 dBm	Input	Input	Input	Input	Input	Input	Input	Input	Input	Input	Input
4.00	0.10	1.22	-0.25	1.90	4.00	5.77	7.51	9.38	0.31	0.26	0.35	0.35	0.62
100.00	0.08	1.05	0.52	1.92	4.22	6.08	7.41	8.99	0.20	0.29	0.37	0.27	0.53
150.00	0.10	1.06	0.53	2.09	4.34	6.12	7.27	8.19	0.22	0.28	0.36	0.23	0.31
200.00	0.13	1.08	0.5	2.45	4.78	7.04	7.19	8.58	0.28	0.29	0.45	0.03	0.46
250.00	0.15	1.10	0.48	1.96	4.04	6.08	7.69	7.84	0.21	0.26	0.41	0.32	0.05
300.00	0.18	1.13	0.52	2.29	4.65	6.43	7.04	7.30	0.25	0.30	0.36	0.12	0.09
400.00	0.22	1.18	0.46	2.10	4.41	5.70	6.32	6.49	0.23	0.29	0.26	0.12	0.06
500.00	0.26	1.23	0.45	1.93	4.41	5.17	5.94	6.65	0.21	0.31	0.15	0.15	0.24
600.00	0.31	1.28	0.37	1.76	4.41	4.68	7.57	8.65	0.20	0.33	0.05	0.58	0.36
700.00	0.36	1.33	0.37	1.71	4.17	4.36	5.10	5.57	0.19	0.31	0.04	0.15	0.16
760.00	0.39	1.37	0.36	1.72	3.83	3.98	8.40	8.86	0.19	0.26	0.03	0.88	0.15


REV A M151107 RLM-751-2WL+ ED-14543 AV/CP/AM 200813 Page 2 of 3





www.minicircuits.com P.O. Box 350166, Brooklyn, NY 11235-0003 (718) 934-4500 sales@minicircuits.com

















Notes A. Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document. B. Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance oriteria and measurement instructions. G. The parts covered by this specification document are subject to Mini-Circuit shandard limited warranty and terms and conditions (collectively, "Standard Terms"). Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuit's website at www.minicircuits.com/MCLStore/terms.jsp

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for RF Wireless Misc category:

Click to view products by Mini-Circuits manufacturer:

Other Similar products are found below :

R41572000 HMC598-SX RX98-4 MABT-011000-14235P W2SW0001-SHLD HMC1110-SX HMC579-SX R417703118 MA4BN1840-1 HMC443LP4ETR HMC561LP3ETR ADL5390ACPZ-REEL7 ADA4304-2ACPZ-R2 ADA4304-2ACPZ-R7 ADA4304-3ACPZ-R2 ADA4304-4ACPZ-R2 ADA4304-4ACPZ-R7 ADA4304-3ACPZ-R7 HMC760LC4B HMC577LC4B HMC370LP4E HMC443LP4E HMC444LP4E HMC445LP4E HMC448 HMC448LC3B HMC1096LP3ETR HMC561 HMC573LC3BTR HMC575LP4 HMC576 HMC576LC3BTR HMC578LC3B HMC578LC3BTR HMC578-SX HMC598 HMC814 HMC814LC3B HMC814LC3BTR SML1 MADRCC0004 MADRCC0007 MAX2045ETJ+ CMX881E1 SA606DK/01,118 MAX1005CEE+ MAX9990ETP+ MADRCC0005 MADRCC0006 HMC448LC3BTR