



MMS-112-01-L-DH



MMS-112-02-F-SH



MMS-116-02-L-DV



MMS-108-01-L-SV

(2.00 mm) .0787"

MMS SERIES

# TIGER CLAW™ SOCKET STRIP

**Board Mates:**  
TMMH, TMM,  
MTMM, MMT, TW,  
LTMM, ZLTMM, TSH

**Cable Mates:**  
TCMD

## SPECIFICATIONS

For complete specifications see [www.samtec.com?MMS](http://www.samtec.com?MMS)

**Insulator Material:**  
Black LCP  
**Contact Material:**  
Phosphor Bronze  
**Plating:**  
Sn or Au over  
50 μ" (1.27 μm) Ni  
**Current Rating (MMS/TMM):**  
3.9 A per pin  
(2 pins powered)  
**Operating Temp Range:**  
-55 °C to +125 °C with Gold  
-55 °C to +105 °C with Tin  
**Insertion Depth:**  
DH = (2.13 mm) .084" to  
(2.79 mm) .110",  
SH = (2.13 mm) .084"  
minimum or pass-through  
Top Entry DV/SV = (2.13 mm)  
.084" to (4.32 mm) .170"  
Bottom Entry DV/SV =  
(4.27 mm) .168" minimum  
(Plus board)  
**RoHS Compliant:**  
Yes

## PROCESSING

**Lead-Free Solderable:**  
Yes  
**SMT Lead Coplanarity:**  
(0.15 mm) .006" max\*  
\*(.004" stencil solution  
may be available; contact  
IPG@samtec.com)

## RECOGNITIONS

For complete scope  
of recognitions see  
[www.samtec.com/quality](http://www.samtec.com/quality)



FILE NO. E111394

## ALSO AVAILABLE (MOQ Required)

- Alignment Pin (-DV only)
- Locking clips and Through-hole pass-through options
- Other platings

**Note:**  
Some lengths, styles and  
options are non-standard,  
non-returnable.

<b>MMS</b>	<b>1</b>	<b>NO. PINS PER ROW</b>	<b>01</b>	<b>PLATING OPTION</b>	<b>ROW OPTION</b>	<b>OTHER OPTION</b>
<b>02 thru 40</b>				<b>-F</b> = Gold flash on contact, Matte Tin on tail	<b>-SV</b> = Single Vertical	<b>-“XX”</b> = Polarized Position
				<b>-L</b> = 10 μ" (0.25 μm) Gold contact, Matte Tin on tail	<b>-SH</b> = Single Horizontal	
					<b>-DV</b> = Double Vertical	
					<b>-DH</b> = Double Horizontal	

<b>MMS</b>	<b>1</b>	<b>NO. PINS PER ROW</b>	<b>02</b>	<b>PLATING OPTION</b>	<b>ROW OPTION</b>	<b>OTHER OPTION</b>
<b>02 thru 40</b>				<b>-F</b> = Gold flash on contact, Matte Tin on tail	<b>-SV</b> = Single Vertical	<b>-“XX”</b> = Polarized Position
				<b>-L</b> = 10 μ" (0.25 μm) Gold contact, Matte Tin on tail	<b>-SH</b> = Single Horizontal	<b>-K</b> = (5.50 mm) .217" DIA Polyimide Film Pick & Place Pad (-SV & -DV only) (-SV = 3 positions min.) (-DV = 4 positions min.)
					<b>-DV</b> = Double Vertical	<b>-M</b> = Metal Pick & Place Pad (4 positions min.) (-DV only)
					<b>-DH</b> = Double Horizontal	<b>-P</b> = Plastic Pick & Place Pad (4 pos. min., -SV only) (5 pos. min., -DV only)
						<b>-TR</b> = Tape & Reel Packaging

Due to technical progress, all designs, specifications and components are subject to change without notice.

[WWW.SAMTEC.COM](http://WWW.SAMTEC.COM)

All parts within this catalog are built to Samtec's specifications.  
Customer specific requirements must be approved by Samtec and identified in a Samtec customer-specific drawing to apply.

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Headers & Wire Housings](#) category:*

*Click to view products by [Samtec](#) manufacturer:*

Other Similar products are found below :

[95000-104TRLF](#) [10135584-644402LF](#) [DF62W-EP2022PCA](#) [95000-106TRLF](#) [DF62W-2022SCA](#) [DF62W-EP2022PC](#) [2203348](#) [DF62W-2022SC](#) [1084018](#) [1029039](#) [1084017](#) [802-10-012-10-002000](#) [1112640](#) [1112639](#) [000-34000](#) [0009482033](#) [0009507031](#) [57102-S06-03LF](#) [57202-S52-04LF](#) [PCN6-15S-2.5E](#) [0039019024](#) [58102-G61-06LF](#) [582553-1](#) [0009485154](#) [0009508121](#) [0022285053](#) [0050291907](#) [018731A](#) [LY20-4P-DT1-P1E-BR](#) [02.125.8002.8](#) [60101931](#) [60598-1 \(Cut Strip\)](#) [M1625-3R/100](#) [61062-3](#) [61082-181009](#) [636-1427](#) [638009-1](#) [641938-9](#) [641991-4](#) [644168-1](#) [647662-1](#) [65039-019ELF](#) [65781-018](#) [65781-047](#) [65817-002LF](#) [65817-015LF](#) [65863-015LF](#) [66207-023LF](#) [67016-026LF](#) [67046-001LF](#)