

This document was generated on 08/25/2021 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

| Part Number: | 0003091121 | | | |
|--|--|--|-------------------------------|---|
| Status: | Active | | | |
| Overview: | | cket Connectors | | |
| Description: | Standard .093" Pin and Socket Connectors 2.36mm Diameter Standard .093" Pin and Socket Receptacle Housing, 12 Circuits, 3 | | | |
| Description. | | ithout Passive Locking Ramps | | |
| | | | | |
| Documents: | | | | |
| Drawing (PDF) | | Product Specification PS-02-09-001 (PDF) | | |
| <u>3D Model (PDF)</u> | | Product Specification PS-42477-001 (PDF) | | |
| 3D Model | | RoHS Certificate of Compliance (PDF) | | |
| | | | Series imag | e - Reference only |
| Agency Certification | ı | | | |
| CSA | | LR19980 | EU ELV | |
| UL | | E29179 | Not Relevant | |
| | | | | |
| General | | | EU RoHS | <u>China RoHS</u> |
| Product Family | | Crimp Housings | Compliant | |
| Series | | <u>1360</u> | REACH SVHC | |
| Application | | Power, Wire-to-Wire | Not Contained Per - | |
| Comments | | 12.5A max. can be achieved when housing is used with | D(2021)4569-DC (8 | |
| Overview | | 42477 or 42478 terminals Standard .093" Pin and Socket Connectors | July 2021) | |
| Product Name | | Standard .093" Pin and Socket Connectors Standard .093" | Halogen-Free | |
| UPC | | 800753614727 | Status | |
| UPC | | 800753014727 | Low-Halogen | |
| Physical | | | | n, please visit <u>Contact US</u> |
| Circuits (maximum) | | 12 | China ROHS | Green Image |
| Color - Resin | | Natural | ELV | Not Relevant |
| Flammability | | 94V-2 | RoHS Phthalates | Not Contained |
| Gender | | Receptacle | | |
| Glow-Wire Capable | | No | | |
| Lock to Mating Part | | None | Search Parts in t | his Series |
| Material - Resin | | Nylon | <u>1360</u> Series | |
| Net Weight | | 5.797/g | | |
| Number of Rows | | 3 | Mates With | |
| Packaging Type | | Bag | <u>03092121</u> , <u>3099</u> | |
| Panel Mount | | Yes | <u>03032121</u> , <u>3033</u> | |
| Pitch - Mating Interface Pitch - Termination In | | 5.03mm 5.03mm | | |
| Stackable | lienace | No | Use With | |
| Temperature Range - | Operating | -40° to +105°C | 1189 Crimp Term | |
| | oporating | | | Male PC Tail Terminals, Tail Terminals, 1380 |
| Material Info | | | | inals, <u>1381</u> Female Crimp |
| Engineering Number | | 1360-R | | Crimp Terminals, <u>1434</u> |
| Poforonco Drowing | Numbors | | Male Crimp Term | |
| Reference - Drawing Product Specification | | PS-02-09-001, PS-42477-001 | | |
| Sales Drawing | | SD-1360-X-001 | | |
| Sales Diawing | | | | |

This document was generated on 08/25/2021 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Pin & Socket Connectors category:

Click to view products by Molex manufacturer:

Other Similar products are found below :

 6450822-1
 770392-1
 794042-1
 796885-1
 8-794535-1
 PLR3455ACS-222
 R929991004
 R929993003
 1403611-1
 1-480349-5
 152302-5

 153211-2
 1586092-1
 1586129-1
 1586681-4
 1586700-1
 1586368-1
 1586380-1
 1586616-1
 1586680-5
 16-06-0038
 164164-5
 1-6609930-1

 172296-1
 19-09-2035
 200503-1
 200788-2
 2029090-4
 2029095-4
 925061-7
 293734-4
 293737-2
 1-765362-4
 1871534-1
 200833-4

 2008625-2
 2029027-2
 2029096-4
 R929991002
 R929993000
 319-10-101-00-005000
 319-10-102-00-001000
 319-10-104-00

 001000
 319-10-105-00-001000
 319-10-112-00-006000
 39-01-8019
 319-10-101-00-001000
 319-10-102-00-005000