

## This document was generated on 04/06/2020 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:	<u>0760685001</u>		
Status:	Active		
Overview:	SFP+ and SFP Interconnect	Solutions	
Description:		Plus (SFP+) Stacked 2-by-6 Multi-Port Press Fit	
Description.		Ports, EMI Metal Gasket, 240 Circuits, Tin (Sn) Tails	
	Connector without Lightpipe	Ports, Elvir Metal Gasket, 240 Circuits, Till (SII) Tails	
Documents:			and the second se
<u>3D Model</u>		Application Specification AS-76090-001-001 (PDF)	
Drawing (PDF)		Packaging Specification PK-75451-001-001 (PDF)	
<u>3D Model (PDF)</u>		RoHS Certificate of Compliance (PDF)	Series image - Reference only
Application Specifica	tion AS-75310-001-001 (PDF)		Series image - Reference only
Agency Certification	n		<u>EU ELV</u>
CSA		LR19980	Not Relevant
UL		E29179	EU RoHS China RoHS
General			Compliant
Product Family		I/O Connectors	REACH SVHC
Series		76068	Not Contained Per -
		Module-to-Board	ECHA_01_2020 (16
Application			January 2020
Component Type Electrical Model		Receptacle Yes	Halogen-Free
Overview		SFP+ and SFP Interconnect Solutions	Status
Product Name			Low-Halogen
		SFP Plus, SFP+ N/A	For more information, please visit <u>Contact US</u>
Type UPC		N/A 800756907505	For more information, please visit <u>contact os</u>
UPC		800756907505	China ROHS Green Image
Physical			ELV Not Relevant
Boot Color		N/A	RoHS Phthalates Not Contained
Circuits (Loaded)		240	
Circuits (maximum)		240	
Circuits Detail		240	
Color - Resin		Black	Search Parts in this Series
Durability (mating cycles max)		100	76068 Series
Flammability		94V-0	
Gender		Female	Use With
Keying to Mating Part		None	759510999 SFP Dust Plug
Lock to Mating Part		Yes	
Material - Metal		High Performance Alloy (HPA)	Application Tooling   FAQ
Material - Plating Ma	tina	Gold	Tooling specifications and manuals are
Material - Plating Ter	0	Tin	found by selecting the products below.
Material - Resin		High Temperature Thermoplastic	Crimp Height Specifications are then
Net Weight		114.014/g	contained in the Application Tooling
Number of Rows		2	Specification document.
Orientation		Right Angle	Global
PC Tail Length		2.07mm	Description Product #
PCB Locator		Yes	Stacked Multi-Port 622029950
PCB Retention		Yes	Extraction Tool, 2 by
PCB Thickness - Rec	commended	1.57mm	6
Packaging Type		Tray	2-by-6 SFP Stacked 622030155
Panel Mount		No	Multi-Port Insertion
Pitch - Mating Interfa	се	0.80mm	Tool
Pitch - Termination Ir		0.80mm	
Plating min - Mating		0.762µm	
Plating min - Termina	ation	0.762µm	
Polarized to Mating F		Yes	
Polarized to PCB		Yes	

Ports 12 Surface Mount Compatible (SMC) No Temperature Range - Operating -40° to +85°C Termination Interface: Style Through Hole - Compliant Pin Waterproof / Dustproof No Electrical 0.5A Current - Maximum per Contact Grounding to Panel None Shield Type EMI Gasket Shielded Yes 120V AC (RMS)/DC Voltage - Maximum Solder Process Data N/A Lead-freeProcess Capability **Material Info Reference - Drawing Numbers** Application Specification AS-75310-001-001, AS-76090-001-001 Electrical Model Document EE-76090-001 Packaging Specification PK-75451-001-001 S-Parameter Model SP-76090-001 Sales Drawing SD-76068-001

## This document was generated on 04/06/2020 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for I/O Connectors category:

Click to view products by Molex manufacturer:

Other Similar products are found below :

571763P 58098-0628 61-168618-12P D38999/20FJ29SB L/C 72.250.1628.2 72.250.2428.2 74720-0505 747680210 76.350.0729.0 76871-1403 FCN-244F080-G/1 FCN-260A9920 FCN-268D024-G/2F#10X-R10 MP-5T180MUNNA-005 MP-5XRJ45UNNB-003 PCS-E50FA PCS-XE26LKA PCS-XE26MA+ PCS-XES68MS+ G38A71314B 91-569719-35R 9776-18-6 DX40-50P(55) 1571250010 157-22500-3 MS3471L14-19P L/C 171224-6031 1888020-8 91-569786-35H 91-569786-35M 91-644626-35P 172501-4002 172501-6002 FCN-260C008-A/L0 FCN-260C024-AL0 FCN-261Z008 FCN-268D008-G/1K 2000314-1 200331-1 2007498-2 PCR-E28LMDAG1+ PCR-E36FC+ PCS-E28FS+ PCS-XE26SLFD+ PCS-XE26SLFDT+ G38A71214B HDRA-E68W1LFDTC-SL+ HDR-E14MSG1+ R88A-CNK81S CRT1-ATT02