

This document was generated on 05/05/2020 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:	0761505020		
Status:	Active		
			27111-
Overview:		or and Cable Assembly System	
Description:		nt-Angle Daughtercard Receptacle, Right Guided, 10	
	Columns, 180 Circuits, Plate	ed Through Hole Dimension 0.39mm, Lead-Free	
Documents:			
<u>3D Model</u>		Application Specification AS-76060-9999-001 (PDF)	Martin Contraction
<u>3D Model (PDF)</u>		Packaging Specification PK-70873-589-001 (PDF)	
Drawing (PDF) Symbol Footprint Data SYM-76150-5020 (PDF)		Series image - Reference only	
Product Specification PS-76060-999-001 (PDF) RoHS Certificate of Compliance (PDF)			Series image Thereferee only
Application Specifica	tion AS-76060-990-001 (PDF)		
			<u>EU ELV</u>
Agency Certificatio	n		Not Relevant
UL		E29179	EU RoHS China RoHS
			Compliant
General			REACH SVHC
Product Family		Backplane Connectors	Not Contained Per -
Series		<u>76150</u>	ECHA_01_2020 (16
Application		Conventional, Coplanar, Daughtercard	January 2020
Application Tooling E	Documents	TM-622018799	Halogen-Free
Component Type		PCB Receptacle	Status
Electrical Model		Yes	Low-Halogen
Overview		Impact Backplane Connector and Cable Assembly	For more information, please visit <u>Contact US</u>
		System	Tormore momation, please visit <u>contact oo</u>
Product Name		Impact	China ROHS Green Image
UPC		883906217068	ELV Not Relevant
Physical			RoHS Phthalates Not Contained
Circuits (Loaded)		180	,
Circuits (maximum)		180	
Color - Resin		Black	Search Parts in this Series
Durability (mating cy	cles max)	200	<u>76150</u> Series
First Mate / Last Break		No	<u>10150</u> Selles
Flammability		94V-0	
Guide to Mating Part		Yes	Mates With
Keying to Mating Par		None	76145 Impact 100 Ohm Vertical Backplane
Material - Metal	-	High Performance Alloy (HPA)	Header
Material - Plating Ma	tina	Gold	
Material - Plating Ter		Tin	Application Tooling FAQ
Material - Resin		High Temperature Thermoplastic	Tooling specifications and manuals are
Net Weight		27.622/g	found by selecting the products below.
Number of Columns		10	Crimp Height Specifications are then
Number of Pairs		6	contained in the Application Tooling
Number of Rows		18	Specification document.
Orientation		Right Angle	Global
PC Tail Length		1.20mm	Description Product #
PCB Locator		No	Daughter Card <u>622018661</u>
PCB Retention		Yes	Signal Module
PCB Thickness - Red	commended	1.00mm	Assembly Press-In
Packaging Type		Tray	Tool for 6-Pair by 10-
Pitch - Mating Interfa		1.90mm	Column Assemblies
Pitch - Termination Ir	nterface	1.90mm	Impact Daughter <u>622024300</u>
Plating min - Mating		0.762µm	Card Extraction Tool
Polarized to PCB		Yes	
Stackable		No	
Temperature Range	- Operating	-55° to +85°C	

Termination Interface: Style

Through Hole - Compliant Pin

0.75A 25.0 Gbps

100Ω N/A

30V AC (RMS)/DC

No

Electrical

Current - Maximum per Contact Data Rate Impedance Shield Type Shielded Voltage - Maximum

Material Info

Reference - Drawing Numbers

Application Specification Electrical Model Document Packaging Specification Product Specification S-Parameter Model Sales Drawing Symbol/Footprint Data

AS-76060-990-001, AS-76060-9999-001 EE-76150-001, EE-76560-0001 PK-70873-589-001 PS-76060-999-001 SP-76150-001, SP-76560-0001 SD-76150-004-001 SYM-76150-5020

This document was generated on 05/05/2020 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for DIN 41612 Connectors category:

Click to view products by Molex manufacturer:

Other Similar products are found below :

09231126901 PCN10F-24P-2.54DS(72) 004.767 02221602702 024069 602427301412000 013275 691327-1 74670-0732 74680-0340 75880-0015 76453-0014 86093159ALF 923454 QLC260R 120X10099X 120X10019X 120X10089X 120X10129X 121A10039X 121A10309X 122A10019X 122A10029X 122A10249X 122A10669X 122A11089X 122A13089X 122A10089X 122A10129X 122A10349X 122A13359X 1377391-4 1393583-2 1393726-7 140X10059X 140X10129X 143-1913-000 143-1908-000 1484472-1 173052 2110070-1 2110070-2 CBC20T00-008FDS5-0-1-002VR 983-0SE12-12P6 17041102202 172699-5036 173051 PCN10-96S-2.54DSA(77) 2-1393557-4 2-1437084-2