

This document was generated on 09/21/2019 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:	<u>0761651627</u>		
Status:	Active		
Overview:		nnector and Cable Assembly System	
Description:			
Description:		ir Vertical Backplane Header, Unguided, Dual Endwall, 16	
		, Pin Length 4.90mm, Plated Through Hole Dimension 0.39mm,	
	Lead-Free		
Documents:			
3D Model		Application Specification AS-76060-9999-001 (PDF)	
Drawing (PDF)		Packaging Specification PK-70873-7700-001 (PDF)	
3 ()	<u>n PS-76060-999-001 (PD</u>		Series image - Reference only
	ition AS-76060-999-001 (PD		
Application Specifica			EU ELV
Agency Certificatio	n		Not Relevant
UL		E29179	
02		220110	EU RoHS China RoHS
General			Compliant
Product Family		Backplane Connectors	REACH SVHC
Series		<u>76165</u>	Not Contained Per -
Application		Conventional, Mezzanine	ED/71/2019 (16 July
Application Tooling [Documents	TM-622018799	2019)
Component Type	· · · · ·	PCB Header	Halogen-Free
Overview		Impact Backplane Connector and Cable Assembly	Status
		System	Low-Halogen
Product Name		Impact	For more information, please visit Contact
UPC		883906225780	
010		000000220700	China ROHS Green Image
Physical			ELV Not Relevant
Circuits (Loaded)		144	RoHS Phthalates Not Contained
Circuits (maximum)		144	,
Color - Resin		Black	
Durability (mating cycles max)		200	Search Parts in this Series
First Mate / Last Break		No	
Flammability		94V-0	76165 Series
Guide to Mating Part		No	
Keying to Mating Part		None	Mates With
Material - Metal		High Performance Alloy (HPA)	76170 Impact 100 Ohm Daughtercard
Material - Plating Ma	tina	Gold	
Material - Plating Termination		Tin	Use With
Material - Resin		High Temperature Thermoplastic	75234 Backplane Free Standing Guide I
Net Weight		3.923/g	
Number of Columns		16	Application Tealing EAO
Number of Pairs		3	Application Tooling <u>FAQ</u>
Number of Rows		9	Tooling specifications and manuals are
Orientation		Vertical	found by selecting the products below.
PC Tail Length		1.40mm	Crimp Height Specifications are then
PCB Locator		No	contained in the Application Tooling
PCB Retention		None	Specification document.
PCB Thickness - Re	commended	1.00mm	Global
			Description Product #
Packaging Type		Tray	Backplane Insertion <u>621005800</u>
Pitch - Mating Interface		1.90mm	Tool for Signal
Pitch - Termination Interface		1.90mm	Contact
Plating min - Mating		0.762µm	Backplane Header <u>621009610</u>
Polarized to PCB		No	Removal Tool for
Stackable		No	GbX U-Series, GbX
Temperature Range Termination Interface		-55° to +85°C	I-Trac, Impact, or Z-
	s. Stulo	Through Hole - Compliant Pin	PACK TinMan

Backplane Module <u>622018651</u> Installation, Press-In Tool

Electrical

Current - Maximum per Contact Data Rate Impedance Shield Type Shielded Voltage - Maximum

Material Info

Reference - Drawing Numbers Application Specification Packaging Specification Product Specification Sales Drawing Symbol/Footprint Data 0.75A 25.0 Gbps 100Ω N/A No 30V AC (RMS)/DC

AS-76060-990-001, AS-76060-9999-001 PK-70873-7700-001 PS-76060-999-001 SD-76165-001-001 SYM-76165-1627

This document was generated on 09/21/2019 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for DIN 41612 Connectors category:

Click to view products by Molex manufacturer:

Other Similar products are found below :

09231126901 PCN10F-24P-2.54DS(72) 004.767 02221602702 024069 602427301412000 013275 691327-1 74670-0732 74680-0340 75880-0015 76453-0014 86093159ALF 923454 QLC260R 120X10099X 120X10019X 120X10089X 120X10129X 121A10039X 121A10309X 122A10019X 122A10029X 122A10249X 122A10669X 122A11089X 122A13089X 122A10089X 122A10129X 122A10349X 122A13359X 1377391-4 1393583-2 1393726-7 140X10059X 140X10129X 143-1913-000 143-1908-000 1484472-1 173052 2110070-1 2110070-2 CBC20T00-008FDS5-0-1-002VR 983-0SE12-12P6 17041102202 172699-5036 173051 PCN10-96S-2.54DSA(77) 2-1393557-4 2-1437084-2