

This document was generated on 10/04/2021 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:	<u>1051330031</u>		\frown	\sim
Status:	Active	Active		
		SB Type-A, USB Type-B, and USB Type-C Plugs and Receptacles		4
Description:	Micro-USB B Receptacle with Flange, Vertical, Surface Mount, 9.80mm Height, 2.30mm Solder Tabs, Lead-Free			
Documents:				Now I
3D Model		Product Specification PS-47642-001-001 (PDF)	\mathbf{v}	NT IL
<u>3D Model (PDF)</u>		Packaging Specification PK-105133-003-001 (PDF)		
Drawing (PDF)		RoHS Certificate of Compliance (PDF)		
<u> </u>			Series image - Reference only	
Agency Certificatio	n			-
UL		E107635	EU ELV	
General			Not Relevant	
Product Family		I/O Connectors	EU RoHS	China RoHS
Series		105133	Compliant	<u>onna Rono</u>
Application		Wire-to-Board	REACH SVHC	
Comments		Signal contacts 1.0A, Power contacts 1.8A	Not Contained Per -	
Component Type		Receptacle	D(2021)4569-DC (8	
Overview		USB Connectors: USB Type-A, USB Type-B, and USB	July 2021)	
Overview		Type-C Plugs and Receptacles		
Product Name		USB	Halogen-Free Status	
Standard		USB 2.0		
		Micro-B	Low-Halogen	
Type UPC		887191460277	For more information	n, please visit <u>Contact US</u>
UFC		887191400277	China ROHS	Green Image
Physical			ELV	Not Relevant
Circuits (Loaded)		5	RoHS Phthalates	Not Contained
Circuits (maximum)		5	,	
Color - Resin		Black		
Durability (mating cycles max)		10000	Search Ports in this Series	
Flammability		94V-0	Search Parts in this Series	
Gender		Female	<u>105133</u> Series	
Keying to Mating Part		Yes		
Lock to Mating Part		No		
Material - Metal		Copper Alloy		
Material - Plating Mating		Gold over Palladium Nickel		
Material - Plating Termination		Gold		
Material - Resin		Liquid Crystal Polymer		
Mounting Style		Vertical		
Net Weight		0.550/g		
Number of Rows		1		
Orientation		Vertical		
PCB Retention		None	None	
Packaging Type		Embossed Tape on Reel	Embossed Tape on Reel	
Panel Mount		No		
Pitch - Mating Interfa	ace	0.65mm		
Pitch - Termination I		0.65mm		
Polarized to Mating F		Yes		
Ports		1		
Surface Mount Com	patible (SMC)	No		
Temperature Range - Operating		-30° to +85°C		
Termination Interface		Surface Mount		
Waterproof / Dustproof		No		

Electrical

Current - Maximum per Contact Voltage - Maximum

Material Info

Reference - Drawing Numbers Packaging Specification Product Specification Sales Drawing 1.8A, 1.0A 30V AC (RMS)

PK-105133-003-001 PS-47642-001-001 SD-105133-031-001

This document was generated on 10/04/2021 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for USB Connectors category:

Click to view products by Molex manufacturer:

Other Similar products are found below :

65-647-8-BK-BU 950 952 E8144-B01021-L A-USB A-LP-SMT-C MUSBA511N5 MUSBD11135 217450-1 CA 6 W LD KMBVX-TH-5S-B30 896-30-004-00-00000 KUSBVX-BS1N-W30 KUSBX-AP-KIT-SCBLK KUSBX-AS2N-W KUSBX-SMT2AP1S-W KUSBX-SMT2AP1S-W30 935 957 30-498-6 17-210051 1734082-1 30-1574 30-470 30-489 30-541 30-572-3 MAB 8 SN V A-USB A-2P-C MIKROE-1451 USBFTV2PEM2G USBFTVC6ZN KUSBX-AS2N-W30 KUSBX-SLAS1N-W KUSBX-SMT-AS1N-W30 4689-1 1-1734084-2 E8110-001-01 MUSBA81130 33UBARS1-04SW11 33UBAR-04SW11 USBF21ZNSCC USBBFTV6ZC 10135326-001LF M9177/3-1 USB-A-S-F-B-VT 925 4198 690-024-633-031 KUSBEX-BSFS1N-W USBFTVC6MRG