



SCALE 1:1

NOTES:
 RATED VOLTAGE: 3 contacts 60V AC/DC
 4 contacts 30V AC/DC
 RATED CURRENT: 3A
 PROTECTION CLASS: IP67
 TEMPERATURE: -25°C / +80°C

CONTACT POSITION FRONT VIEW:

3 POLES (2 WIRES)		3 POLES		4 POLES	
PIN	WIRE	PIN	WIRE	PIN	WIRE
1	BROWN	1	BROWN	1	BROWN
2	---	2	---	2	WHITE
3	BLUE	3	BLUE	3	BLUE
4	N/U	4	BLACK	4	BLACK
5	---	5	---	5	---

TABLE 1

POS	QTY	DESCRIPTION	MATERIAL	FINISH
1	-	CABLE	SEE SHEET 2	SEE SHEET 2
2	3 / 4	CONTACT FEMALE	CuNi2Si	Cu/Ni2
3	-	OVERMOLD	TPU OR PVC	BLACK OR YELLOW
4	1	INSERT FEMALE	ELASTOLLAN	BLACK
5	1	LABEL YELLOW	VINYL	-
	-	PRINTING FOR CABLES I02	-	-

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION

EC NO: 118614 DRWN: FGAIK CHK'D: APPR: BBRAUCH	2017/01/09	GENERAL TOLERANCES (UNLESS SPECIFIED) ANGULAR TOL ± 1.0 ° 4 PLACES ± 3 PLACES ± 2 PLACES ± 0.05 1 PLACE ± 0.3 0 PLACES ± 0.5 DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS	DIMENSION UNITS	SCALE				
	2017/06/27		MM	2:1				
			DRWN BY	DATE				
			FGAIK	2016/05/16				
			CHK'D BY	DATE	CSE M8SNAP XP AC FE RA XM SE UNSH			
			APPR BY	DATE	PRODUCT CUSTOMER DRAWING			
			BBRAUCH	2017/06/27				
			DRAWING SIZE	THIRD ANGLE PROJECTION	SERIES	MATERIAL NUMBER	CUSTOMER	
			A3		120088	SEE SHEET 2	GENERAL MARKET	
					DOCUMENT NUMBER	DOC TYPE	DOC PART	SHEET NUMBER
					1200888086	PSD	000	1 OF 2

ENGINEERING NO. - NUMERICAL CODE (Available parts see table 2. Other parts available upon request).

OPTIONS

50X001XXXMXXXX

50=Snap
Nano Change
Single Ended

Poles:
2=2 Poles
3=3 Poles
4=4 Poles

Heads style:
001=Plug Female
90° Angled

Cable type: See Table 3

Unit:
M=Meter

Length
Examples:
005=0.5 unit
010=1 unit
100=10 units

Overmold color:
Blank (Standard)=Black
Y=Yellow

H= 2 pcs. of I/D Carrier PVC Transparent
(Cables lxx always with
2 pcs. I/D Carrier)



TABLE 2

POS.	MOLEX PN	ENGINEERING NO.	L [mm]
1	1200290006	502001I02M020	2000
2	1200888146	502001I02M020Y	2000
3	1200290007	502001I02M050	5000
4	1200290008	502001I02M100	10000
5	1200888147	502001I02M100Y	10000
6	1200888086	503001E02M020	2000
7	1200888010	503001E02M050	5000
8	1200888064	503001E02M100	10000
9	1200888128	503001H08M020	2000
10	1200888159	503001H08M050	5000
11	1200888184	503001H08M050H	5000
12	1200888152	503001H08M150	15000
13	1200888153	503001H08M200	20000
14	1200888087	503001I02M020	2000
15	1200888088	503001I02M030	3000
16	1200888089	503001I02M100	10000
17	1200888090	503001P02M020	2000
18	1200888091	503001P02M050	5000
19	1200888161	503001P02M100	10000
20	1200888185	503001P02M100H	10000
21	1200888124	504001E02M020	2000
22	1200888100	504001E02M030	3000
23	1200888101	504001E02M100	10000
24	1200888126	504001H08M020	2000
25	1200888149	504001P02M002	200
26	1200888151	504001P02M015	1500
27	1200888125	504001P02M020	2000
28	1200888102	504001P02M030	3000
29	1200888103	504001P02M050	5000

TABLE 3

CABLE TYPE	NO. OF WIRES	CROSS SECTION	CABLE JACKET	UL	CSA	STATIC: TEMP. / BENDING RADIUS	DYNAMIC: TEMP. / BENDING RADIUS	DRAG CHAIN
E02	3 / 4	0.25mm ²	PVC BLACK	UL 1729/2464	C22.2 I/II A/B 80°C 300V	-30°C to +80°C / 10xO.D.	-10°C to +80°C / 15xO.D.	-
H08	3 / 4	0.25mm ²	PUR BLACK LS0H	UL 10493/21198	C22.2 I/II A/B 80°C 300V	-40°C to +80°C / 5xO.D.	-25°C to +80°C / 10xO.D.	2 000 000 cycles, Temp max 60°C
I02	2 / 3 / 4	0.25mm ²	PVC (CEI) GREY	-	-	-30°C to +70°C	-5°C to +70°C	-
P02	3 / 4	0.25mm ²	PUR / PVC BLACK	-	-	-30°C to +80°C / 7xO.D.	-5°C to +80°C / 15xO.D.	-

CABLE LENGTH TOLERANCES

OVER [mm]	UP TO AND INCLUDING [mm]	TOLERANCES [mm]
0	305	+19
305	915	+45
915	1830	+56
1830	3660	+89
3660	7320	+165
7320	14640	+317
14640	30500	+610
30500	>	+2% of finished length

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION

2017/01/09 2017/06/27	2017/06/27	GENERAL TOLERANCES (UNLESS SPECIFIED)	DIMENSION UNITS	SCALE	
		ANGULAR TOL ± 1.0 °	MM	1:1	
		4 PLACES ±	DRWN BY	DATE	
		3 PLACES ±	FGAIK	2016/05/16	
EC NO: 118614 DRWN: FGAIK CHK'D: BBRAUCH APP: BBRAUCH	REV	2 PLACES ± 0.05	CHK'D BY	DATE	CSE M8SNAP XP AC FE RA XM SE UNSH PRODUCT CUSTOMER DRAWING
		1 PLACE ± 0.3	APPBY	DATE	
		0 PLACES ± 0.5	BBRAUCH	2017/06/27	
		DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS	DRAWING SIZE	THIRD ANGLE PROJECTION	
A		A3			SERIES: 120088 MATERIAL NUMBER: SEE TABLE 2 CUSTOMER: GENERAL MARKET
					DOCUMENT NUMBER: 1200888086 DOC TYPE: PSD DOC PART: 000 SHEET NUMBER: 2 OF 2

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Sensor Cables / Actuator Cables](#) category:

Click to view products by [Molex](#) manufacturer:

Other Similar products are found below :

[60963](#) [60964](#) [703000D02F2002](#) [703001D02F0602](#) [703001D02F300](#) [704000D02F120](#) [773032K02F030](#) [802027107404-1](#) [802027213811-1](#)
[804001A09M150](#) [805001A09M0502](#) [84914-0235](#) [84914-0237](#) [885030A09M020](#) [8R4J30E03C3003](#) [1200651332](#) [1200651713](#) [1200660844](#)
[1200660845](#) [1200661173](#) [1200680071](#) [1200720053](#) [1200720081](#) [1200720099](#) [1200720217](#) [1200800231](#) [1200860125](#) [1200870123](#)
[1200980102](#) [1200650267](#) [1200650298](#) [1200660183](#) [1200660782](#) [1200660849](#) [1200661295](#) [1200661297](#) [1200661342](#) [1200661343](#)
[1200670080](#) [1200670220](#) [1200680331](#) [1200720252](#) [1200730184](#) [1200860344](#) [1200870359](#) [1200870643](#) [1200980008](#) [1200980031](#)
[1210502211](#) [1210400542](#)