

This document was generated on 08/30/2021 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: 1300230004 Status: Active Overview: Push-Button Pendant Products Description: Super-Safeway Single Button, 3 Pin, Single-Pole, Single-Throw, Normally Open, 10A, Snap Action Switch, NBR/PVC Switch Boot, 125/250V AC, Mini-Change Connection Documents: Description: Datasheet (PDE) Application Specification 1300230001APPSPEC-000 Datasheet (PDE) Series image - Reference only Agency Certification UL E70531 EU RoHS China RoHS Product Family Push Buttons / Testers Saries 130023 Enclosure Rating Weather Resistant Overview Push-Button Pendant Products Not Reviewed Product Name Special China RoHS Not Reviewed Satus Cord Diameter NA NA Otherwiewed Satus Satus Physical NA No Not Reviewed Satus Satus Satus Satus Cord Diameter NA NA NA Not Reviewed Satus Satus Satus Satus Physical Cord Diameter NA NA Not Reviewed Satus Satus						
Status: Active Overview: Push-Button Pendant Products Description: Super-Safeway Single Button, 3 Pin, Single-Pole, Single-Throw, Normally Open, 10A, Snap Action Switch, NBR/PVC Switch Boot, 126/250V AC, Mini-Change Connection Documents: Datasing (PDE) Application Specification 1300230001APPSPEC-000 RoHS Certificate of Compliance (PDF) Application Specification 1300230001APPSPEC-000 RoHS Certificate of Compliance (PDF) (PDF) Erotosian Agency Certification E70531 General Frequency Certification 1300230003 Product Family Push Buttons / Testers Series 130023 Enclosure Rating Weather Resistant Overview Push-Button Pendant Products Product Name Super-Safeway Type Status UPC 78678855509 Physical Cord Diameter Cord Jameter N/A Cord Length N/A Renegency Stop N/A Renegency Stop N/A Potes 1 Electrical Series Cord Torpe N/A Potes	Part Number:	1300230004				
Overview: Push-Button Pendant Products Description: Super-Safeway Single Button, 3 Pin, Single-Pole, Single-Throw, Normally Open, 10A, Snap Action Switch, NBR/PVC Switch Boot, 125/250V AC, Mmi-Change Connection Decuments: Decuments: Drawing (PDF) Datasheet (PDF) Application Specification 1300230001APPSPEC-000 RoHS Certificate of Compliance (PDE) (PDF) Product Family Product Family Push Buttons / Testers Sories 130023 Enclosure Rating Weather Resistant Overview Push-Button Pendant Products Product Family Push-Button Pendant Products Product Name Specification Push-Safeway UPC 7867885509 Physical Cord Iangth Cord Diameter N/A Cord Grip Body Size N/A Cord Grip Body Size N/A Remergency Step No Number of Speeds Single Poles 1 Electrical Carton Poles 1 Electrical Electrical Cord Type NA Voltage - Maximum 125V AC / 250V	Status:			AC		
Description: Super-Safeway Single Button, 3 Pin, Single-Pole, Single-Throw, Normally Open, 10A, Snap Action Switch, NBR/PVC Switch Boot, 125/250V AC, Mini-Change Connection Documents: Datasheet (PDF) Application Specification 1300230001APPSPEC-000 Datasheet (PDF) Application Specification 1300230001APPSPEC-000 Datasheet (PDF) Reference only Series image - Reference only Agency Certification E70531 General Product Family Product Rating Weather Resistant Overview Push-Button Preducts Product Name Super-Safeway Type Enabling Switch, PushButton Pendant Products Physical Cord Grip Body Size Cord Diameter N/A Cord Top Body Size N/A Cord Top Body Size N/A Cord Top Body Size N/A Material - Body N/A Poles 1 Electrical <	Overview [.]					
Snap Action Switch, NBR/PVC Switch Boot, 125/250V AC, Mini-Change Connection Documents: Drawing (PDF) Application 1300230001APPSPEC-000 RoHS Certificate of Compliance (PDF) Series image - Reference only Agency Certification UL E70531 Series China RoHS General Product Family Push Buttons / Testers Series China RoHS Series 130023 Push-Button Pendant Products Not Reviewed Product Name Super-Safeway Not Reviewed Safeward Type Enabling Switch, PushButton Pendant Products Not Reviewed Sofeward Product Length N/A Not Reviewed Sofeward Cord Diameter N/A NA China ROHS Not Reviewed Cord Gip Body Size N/A Not Reviewed Sofes Status Sofes Status Number of Speeds Single Safes Sofo/g Not Reviewed Secret Status Cord Top Body Size N/A Not Reviewed Secret Status Soft Reviewed Secret Status Deles 1 Electrical Soft Reviewed Secarch Parts in this Series Soft Reviewed<						
Drawing (PDE) Application Specification 1300230001APPSPEC-000 Datasheet (PDE) RoHS Certificate of Compliance (PDF) Series image - Reference only Agency Certification UL E70531 EU LV Not Relevant Series image - Reference only Seneral Product Family Push Buttons / Testers China RoHS Not Reviewed Series 130023 Not Reviewed REACH SVHC Not Reviewed Product Name Super-Safeway Not Reviewed Not Reviewed Not Reviewed Product Name Super-Safeway Not Reviewed Status Not Reviewed Product Name Super-Safeway Not Reviewed Status Not Reviewed Product Name Super-Safeway Not Reviewed Status Not Reviewed Cord Grip Body Size N/A EU V Not Reviewed EU V Not Reviewed Cord Grip Body Size N/A EU V Not Reviewed RoHS Phitalates Not Reviewed Immegration Speeds Single Scarch Parts in this Series 130023 Series 130023 Series Electrical Cord Type N/A Electrical Search Parts in this Series 130023 Series Poles 1					1.000	
Drawing (PDF) Application Specification 1300230001APPSPEC-000 Datasheet (PDF) RoHS Certificate of Compliance (PDF) Description (PDF) Agency Certification 1300230001APPSPEC-000 E70531 Series image - Reference only Agency Certification 1300230001APPSPEC-000 E70531 EU Rely Series image - Reference only Year Push Buttons / Testers Source China RoHS Not Reviewed Product Family Push-Button Pendant Products Not Reviewed REACH SVHC Not Reviewed Product Name Super-Safeway Not Reviewed Status Not Reviewed Product Name Super-Safeway Not Reviewed Status Not Reviewed Product Name Super-Safeway Not Reviewed Status Not Reviewed Cord Grip Body Size N/A EU V Not Reviewed EU V Not Reviewed Cord Grip Body Size N/A EU V Not Reviewed EU V Not Reviewed Remergency Stop No Material - Body Nylon Not Reviewed Search Parts in this Series 130023 Series Proles 1 Electrical Cord Type Carton Parestription V/A Source Series<		·			13	
Application Specification 130023001APPSPEC-000 RoHS Certificate of Compliance (PDF) Series Series <thseries< th=""> Series Series<td>Documents:</td><td></td><td></td><td></td><td></td></thseries<>	Documents:					
(PDE) Series image - Reference only Agency Certification E70531 General Push Buttons / Testers Product Family Push Buttons / Testers Series 130023 Enclosure Rating Weather Resistant Overview Push-Button Pendant Products Product Name Super-Safeway Type Enabling Switch, PushButton Pendant Station UPC 78678855509 Physical Cord Diameter Cord Diameter N/A Cord Grip Body Size N/A Cord Grip Body Size N/A Material - Body Nyion Net Weight 70.760/g Number of Speeds Single Packaging Type Carton Poles 1 Electrical Carton Yorkey N/A Yorkey Agency Carton Poles 1 Electrical Engineering Number Cord Type N/A Yorkey Status Poles 1 Electrical Engineering Number						
Agency Certification Series image - Reference only UL E70531 General Product Family Push Buttons / Testers Series 130023 Enclosure Rating Weather Resistant Overview Push-Button Pendant Products Product Name Super-Safeway Type Enabling Switch, PushButton Pendant Station UPC 78678855509 Physical Cord Diameter Cord Diameter N/A Cord Diameter N/A Cord Length N/A Emergency Stop No Naterial - Body Nylon Net Weight 70.760/g Number of Speeds Single Packaging Type Carton Poles 1 Electrical Electrical Cord Type N/A Voltage - Maximum 125V AC / 250V AC Material Info Engineering Number Engineering Number 55504		on 1300230001APPSPEC-000	RoHS Certificate of Compliance (PDF)			
Agency Certification E70531 UL E70531 General Product Family Product Family Push Buttons / Testers Series 130023 Enclosure Rating Weather Resistant Overview Push-Button Pendant Products Product Name Super-Safeway Type Enabling Switch, PushButton Pendant Station UPC 78678855509 Physical Cord Diameter Cord Diameter N/A Cord Length Not Reviewed Emergency Stop No Naterial - Body Nylon Net Weight 70.760/g Number of Speeds Single Packaging Type Carton Poles 1 Electrical Electrical Cord Type N/A Voltage - Maximum 125V AC / 250V AC Material Info Engineering Number Engineering Number 55504	(<u>PDF)</u>			Sorios imag	Poforonco only	
UL E70531 EU ELV Not Relevant General Not Relevant Product Family Push Buttons / Testers Series 130023 Enclosure Rating Weather Resistant Overview Push-Button Pendant Products Product Name Super-Safeway Type Enabling Switch, PushButton Pendant Station UPC 7867885509 Physical China ROHS Cord Diameter N/A Cord Length N/A Cord Length N/A Cord Length N/A Remergency Stop No Material - Body Nylon Number of Speeds Single Packaging Type Carton Poles 1 Electrical Electrical Cord Type N/A Voltage - Maximum 125V AC / 250V AC						
Not RelevantProduct FamilyPush Buttons / TestersSeries130023Enclosure RatingWeather ResistantOverviewPush-Button Pendant ProductsProduct NameSuper-SafewayTypeEnabling Switch, PushButton Pendant StationUPC7867885509PhysicalCord DiameterCord DiameterN/ACord Grip Body SizeN/ACord Grip Body SizeN/ACord Grip Body SizeN/ACord SignerNot ReviewedEmergency StopNoMaterial - BodyNylonNet weight70.760/gNumber of SpeedsSinglePackaging TypeCartonPoles1ElectricalElectricalCord JignerN/AVoltage - Maximum125V AC / 250V ACMaterial InfoEngineering NumberEngineering Number55504			E70531	ELLELV		
GeneralProduct FamilyPush Buttons / TestersEU RoHSChina RoHSSeries130023Not ReviewedEnclosure RatingWeather ResistantREACH SVHCOverviewPush-Button Pendant ProductsNot ReviewedProduct NameSuper-SafewayHalogen-FreeTypeEnabling Switch, PushButton Pendant StationStatusUPC78678855509Not ReviewedPhysicalCord Grip Body SizeN/ACord DiameterN/AChina ROHSCord Grip Body SizeN/ARoHSCord LengthN/ARoHSCord JameterN/ARoHSCord JameterN/ARoHSCord LengthN/ARoHSCord JameterN/ARoHSCord JameterN/ARoHSCord JameterN/ARoHSCord JameterN/ARoHSCord LengthN/ARoHSCord Jameter70.760/gNumber of SpeedsSinglePackaging TypeCartonPoles1ElectricalICord TypeN/AVoltage - Maximum125V AC / 250V ACMaterial InfoIEngineering Number55504	UL		E70331			
Series 130023 Enclosure Rating Weather Resistant Overview Push-Button Pendant Products Product Name Super-Safeway Type Enabling Switch, PushButton Pendant Station UPC 78678855509 Physical Not Reviewed Cord Diameter N/A Cord Diameter N/A Cord Length N/A Emergency Stop No Material - Body Nylon Number of Speeds Single Packaging Type Carton Poles 1 Electrical Cord Type Cord Type N/A Voltage - Maximum 125V AC / 250V AC				Not Kelevant		
Enclosure RatingWeather ResistantREACH SVHCOverviewPush-Button Pendant ProductsNot ReviewedProduct NameSuper-SafewayHalogen-FreeTypeEnabling Switch, PushButton Pendant StationHalogen-FreeUPC78678855509Not ReviewedPhysicalCorid DiameterN/ACord DiameterN/AChina ROHSCord Grip Body SizeN/AChina ROHSCord Grip Body SizeN/ARoHS PhthalatesCord Grip Body SizeN/ARoHS PhthalatesCord Grip Body SizeN/ARoHS PhthalatesCord Grip Body SizeN/ARoHS PhthalatesCord Grip Body SizeNoNot ReviewedEmergency StopNoRoHS PhthalatesNumber of SpeedsSingleSearch Parts in this SeriesPoles1ElectricalCord TypeN/AVoltage - Maximum125V AC / 250V ACMaterial InfoEngineering NumberEngineering Number55504					<u>China RoHS</u>	
OverviewPush-Button Pendant ProductsNot ReviewedProduct NameSuper-SafewayHalogen-FreeTypeEnabling Switch, PushButton Pendant StationStatusUPC78678855509StatusPhysicalCord DiameterN/ACord DiameterN/AChina ROHSCord Grip Body SizeN/AELVCord LengthN/ACord LengthN/AEmergency StopNoMaterial - BodyNylonNet Weight70.760/gNumber of SpeedsSinglePoles1ElectricalCord TypeCord TypeN/AVoltage - Maximum125V AC / 250V ACMaterial InfoEngineering NumberEngineering Number55504						
Product NameSuper-SafewayHalogen-FreeTypeEnabling Switch, PushButton Pendant StationStatusUPC78678855509Not ReviewedPhysicalFor more information, please visit Contact USCord DiameterN/AChina ROHSCord Grip Body SizeN/AELVCord Grip Body SizeN/ACord LengthN/AEmergency StopNoMaterial - BodyNylonNet Weight70.760/gNumber of SpeedsSinglePackaging TypeCartonPoles1ElectricalElectricalCord TypeN/AVoltage - Maximum125V AC / 250V ACMaterial InfoEngineering NumberEngineering Number55504						
Type UPCEnabling Switch, PushButton Pendant Station 78678855509Status Not ReviewedPhysical Cord DiameterN/AFor more information, please visit Contact USCord DiameterN/AChina ROHSNot ReviewedCord Grip Body SizeN/AELVNot ReviewedCord Grip Body SizeN/ARoHSNot ReviewedCord LengthN/ARoHSNot ReviewedEmergency StopNoRoHSNot ReviewedMaterial - BodyNylonRoHSNot ReviewedNumber of SpeedsSingleSearch Parts in this SeriesPackaging TypeCarton130023 SeriesPoles1Isover 250V ACMaterial Info Engineering Number55504						
UPC78678855509Not ReviewedPhysicalFor more information, please visit Contact USCord DiameterN/AChina ROHSNot ReviewedCord Grip Body SizeN/AChina ROHSNot ReviewedCord LengthN/ARoHS PhthalatesNot ReviewedCord LengthN/ARoHS PhthalatesNot ReviewedEnergency StopNoRoHS PhthalatesNot ReviewedMaterial - BodyNylonNumber of SpeedsSingleNumber of SpeedsSingleSearch Parts in this SeriesPoles1130023 SeriesElectricalICord TypeN/AVoltage - Maximum125V AC / 250V ACMaterial Info55504						
Physical For more information, please visit Contact US Cord Diameter N/A Cord Grip Body Size N/A Cord Length N/A Cord Length N/A Emergency Stop No Material - Body Nylon Net Weight 70.760/g Number of Speeds Single Packaging Type Carton Poles 1 Electrical Cord Type Cord Type N/A Voltage - Maximum 125V AC / 250V AC Material Info 55504						
PhysicalN/AChina ROHSNot ReviewedCord DiameterN/AELVNot ReviewedCord Grip Body SizeN/ARoHSPhysicalCord LengthN/ARoHSNot ReviewedEmergency StopNoRoHSNot ReviewedMaterial - BodyNylonRoHSNot ReviewedNet Weight70.760/gSearch Parts in this SeriesNumber of SpeedsSingleSearch Parts in this SeriesPackaging TypeCarton130023 SeriesPoles1ElectricalCord TypeN/AVoltage - Maximum125V AC / 250V ACMaterial Info55504	UPC		10010033309		n plaasa visit Contact LIS	
Cord Grip Body SizeN/AELVNot RelevantCord LengthN/ARoHS PhthalatesNot ReviewedEmergency StopNoMaterial - BodyNylonNet Weight70.760/gNumber of SpeedsSinglePackaging TypeCartonPoles1ElectricalCord TypeN/AVoltage - Maximum125V AC / 250V ACMaterial Info55504	Physical				n, please visit <u>contact 05</u>	
Cord LengthN/ARoHS PhthalatesNot ReviewedEmergency StopNoMaterial - BodyNylonNet Weight70.760/gNumber of SpeedsSinglePackaging TypeCartonPoles1ElectricalCord TypeN/AVoltage - Maximum125V AC / 250V ACMaterial InfoEngineering Number55504				China ROHS	Not Reviewed	
Emergency StopNoMaterial - BodyNylonNet Weight70.760/gNumber of SpeedsSinglePackaging TypeCartonPoles1ElectricalCord TypeCord TypeN/AVoltage - Maximum125V AC / 250V ACMaterial InfoEngineering Number55504						
Material - BodyNylonNet Weight70.760/gNumber of SpeedsSinglePackaging TypeCartonPoles1ElectricalCord TypeN/AVoltage - Maximum125V AC / 250V ACMaterial Info55504				RoHS Phthalates	Not Reviewed	
Net Weight70.760/gNumber of SpeedsSinglePackaging TypeCartonPoles1ElectricalCord TypeN/AVoltage - Maximum125V AC / 250V ACMaterial InfoEngineering Number55504						
Number of SpeedsSingleSearch Parts in this SeriesPackaging TypeCartonPoles1ElectricalCord TypeN/AVoltage - Maximum125V AC / 250V ACMaterial InfoEngineering Number55504						
Packaging Type Carton Poles 1 Electrical N/A Cord Type N/A Voltage - Maximum 125V AC / 250V AC Material Info 55504			•	Search Parts in t	his Series	
Poles 1 Electrical V/A Cord Type N/A Voltage - Maximum 125V AC / 250V AC Material Info 55504	-			130023 Series		
Electrical N/A Cord Type N/A Voltage - Maximum 125V AC / 250V AC Material Info 55504				,		
Cord TypeN/AVoltage - Maximum125V AC / 250V ACMaterial Info Engineering Number55504						
Voltage - Maximum125V AC / 250V ACMaterial Info Engineering Number55504			N1/A			
Material Info Engineering Number 55504						
Engineering Number 55504			120V AU / 200V AU			
Reference - Drawing Numbers	Engineering Number		55504			
	Reference - Drawing	Numbers				
Application Specification 1300230001_APPSPEC-000			1300230001_APPSPEC-000			
Sales Drawing SD-130023-005-001						

This document was generated on 08/30/2021 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Pushbutton Switches category:

Click to view products by Molex manufacturer:

Other Similar products are found below :

 8940K2012
 LW1L-M1C10V-A
 LW1L-M1C70-A
 LW2L-A1C20M-GD
 LW2L-M1C20M-A
 60324L
 M22-D-R-GB0/K11
 M7E-HRN2

 67021K512
 67081K512X
 701PB580
 7190K101
 7199K101
 810K12910
 810KSV30B
 MML21EA2ADK
 MML21KA3ABK

 MML23KA3AC05K-001
 MML23KW3AA01W
 8418K2
 8442K3
 8450K1
 860K11911T01A
 861901
 861K11911T01A07

 861K13810T00A14
 861K13911
 8646AB6X718UL
 8646ABUL
 9001KXRK
 907AYY100
 PMHD155A1
 95-313.000

 9533CD4+U574+U4922
 95-414.000
 99-450.837
 99-453.837
 PV3H2B0NN-341
 1203MRA
 A22NZBGANGA
 A22NZBMMNGA

 A22NZBNANGA
 A22NZMPATRA
 A2PMA1X03EC56
 A3A-5123-02
 A3A-7140
 A3A-7340
 A3U-TMW-A2C-5M
 A595