

## This document was generated on 07/31/2021 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

NEMA ConfigurationNEMA L16-20REACOverviewHeavy-Duty Industrial Wiring DevicesNot ReProduct NameSafewayHalogReceptacle TypeSingleStatusSpecialtyN/ANot ReTypeConnectorFor modeUPC78678870677ChinaPhysicalImageNoFlangeNoRoHSFlip LidNoRoHSGenderFemaleFemaleLocking BladeYesYes		
Documents:       RoHS Certificate of Compliance (PDE)         Brachure (PDE)       RoHS Certificate of Compliance (PDE)         Agency Certification       EU EL         CSA       LR6837         UL       E10176         General       Not R         Product Family       Wiring Devices         Series       130145         IP Rating       N/A         NEMA Configuration       NEMA L16-20         Overview       Heavy-Duty Industrial Wiring Devices         Product Name       Safeway         Receptacle Type       Single         Specialty       N/A         Type       Connector         UPC       7678870677         Physical       Filange         Filange       No         Flange       No         Poles       3-pole/4-wire         Electrical       20.0A         Gender       Kod         Length       N/A         Vole       No         Cord Type       N/A         Current - Maximum per Contact       20.0A         GFCI       No         Voltage - Maximum       30/480V	-	
Drawing (PDF)       RoHS Certificate of Compliance (PDF)         Brochure (PDF)       Agency Certification         CSA       LR6837         UL       E10176         General       FU EL         Product Family       Wiring Devices         Series       130145         IP Rating       N/A         NEMA Configuration       NEMA L16-20         Overview       Heavy-Duty Industrial Wiring Devices         Product Name       Safeway         Product Name       Safeway         Product Name       Safeway         Recaptacle Type       Single         Specialty       N/A         Type       Connector         UPC       78678870677         Physical       Fermale         Length       N/A         Length       N/A         Length       N/A         Poles       3-pole/4-wire         Electrical       20.0A         GFC1       No         Cord Type       No         Voltage - Maximum       32/ 480V	12	
CSALR6837ULE10176GeneralEU ELProduct FamilyWiring DevicesSeries130145IP RatingN/ANMA ConfigurationNEMA L16-20OverviewHeavy-Duty Industrial Wiring DevicesProduct NameSafewaySafewayHalogReceptacle TypeSingleSpecialtyN/ATypeConnectorUPC78678870677ChinaELertricalElengthN/ALocking BladeYesPoles3-pole/4-wireElectricalCord TypeN/AConnector1300OverviewNoGenderFemaleLengthN/ALocking BladeYesPoles3-pole/4-wireElectricalK/ACurrent - Maximum per Contact20.0ACiffClNoLighted ConnectorNoVoltage - Maximum30/480V	1 10	
ULE10176GeneralEU ELProduct FamilyWiring DevicesSeries130145IP RatingN/ANEMA ConfigurationNEMA L16-20OverviewHeavy-Duty Industrial Wiring DevicesProduct NameSafewayReceptacle TypeSingleSpecialtyN/AUPC78678870677PhysicalNoFlangeNoFlip LidNoGenderFemaleLengthN/ALocking BladeYesPoles3-pole/4-wireElectricalN/ACurrent - Maximum per Contact20.0AGFCINoLighted ConnectorNoLighted ConnectorNoSeal3/2 480V	Sorios imao	e - Reference only
GeneralEU EL Not ReProduct FamilyWiring DevicesSeries130145IP RatingN/ANEMA ConfigurationNEMA L16-20OverviewHeavy-Duty Industrial Wiring DevicesProduct NameSafewayReceptacle TypeSingleSpecialtyN/AUPC78678870677PhysicalConnectorFlangeNoFlugConnectorUPC78678870677ChinaELVFlangeNoFlugSafewayRocking BladeYesPoles3-pole/4-wireElctricalNoCurrent - Maximum per Contact20.0AGFCINoLighted ConnectorNoLighted ConnectorNo	Series inay	e - Nelelence Only
GeneralNot RoProduct FamilyWiring DevicesNot RoSeries130145EU RoIP RatingN/ANot RoNEMA ConfigurationNEMA L16-20REACOverviewHeavy-Duty Industrial Wiring DevicesNot RoProduct NameSafewayHalogReceptacle TypeSingleStatusSpecialtyN/ANot RoTypeConnectorFor modUPC7678870677ChinaPhysicalFermaleELVFlangeNoRoHSGenderFermaleELVLengthN/ASealLocking BladeYes3-pole/4-wirePolesN/ASealCord TypeN/ASealCurrent - Maximum per Contact20.0AGFC1NoCurrent - Maximum per ContactLighted ConnectorNoVotage - MaximumWid 480V		
Product FamilyWiring DevicesSeries130145IP RatingN/ANEMA ConfigurationNEMA L16-20OverviewHeavy-Duty Industrial Wiring DevicesProduct NameSafewayReceptacle TypeSingleSpecialtyN/ATypeConnectorUPC78678870677PhysicalFemaleFlip LidNoGenderFemaleLengthN/ALocking BladeYesPoles3-pole/4-wireElectricalCurrent - Maximum per ContactCord TypeNoCurrent - Maximum per Contact20.0AGFC1NoLighted ConnectorNoGerderSalouXLighted ConnectorYesSolo X480VYed X80V		
Series130145EU RoIP RatingN/ANot RrNEMA ConfigurationNEMA L16-20REACOverviewHeavy-Duty Industrial Wiring DevicesNot RrProduct NameSafewayHalogReceptacle TypeSingleStatusSpecialtyN/ANot RrTypeConnectorVPCUPC78678870677ChinaPhysicalNoRoHSFlip LidNoRoHSGenderFemaleELVLengthN/ASeauLocking BladeYesSole/4-wirePolesN/ASeauCord TypeN/ANoCurrent - Maximum per Contact20.0AGFC1NoLighted ConnectorNoUPCNoLighted ConnectorNoVotage - Maximum30/480V	leviewed	
IP Rating     N/A     Not Rel       NEMA Configuration     NEMA L16-20     REAC       Overview     Heavy-Duty Industrial Wiring Devices     Not Re       Product Name     Safeway     Halog       Receptacle Type     Single     Status       Specialty     N/A     Not Re       Type     Connector     For mod       UPC     78678870677     China       Physical     ELV     Flange       Flip Lid     No     RoHS       Gender     Female     ELV       Length     N/A     No       Locking Blade     Yes     3-pole/4-wire       Poles     3-pole/4-wire     130'       Electrical     No     Keart       Current - Maximum per Contact     20.0A     No       GFC1     No     Lighted Connector       Uighted Connector     No     Lighted Connector       Viewei - Maximum     30' 480V     480V	oHS	China RoHS
OverviewHeavy-Duty Industrial Wiring DevicesNot ReProduct NameSafewayHalogReceptacle TypeSingleStatusSpecialtyN/ANot ReTypeConnectorFor modUPC78678870677ChinaPhysicalELVFlangeNoFlip LidNoGenderFemaleLengthN/ALocking BladeYesPoles3-pole/4-wireElectricalContactCord TypeN/ACurrent - Maximum per Contact20.0AGFCINoLighted ConnectorNoLighted ConnectorNoLighted ConnectorNoVerentNoSecond ConnectorN/ACurrent - Maximum per Contact20.0AGFCINoLighted ConnectorNoVerentNoLighted ConnectorNoVerentNoLighted ConnectorNoVerent3Ø 480V	Reviewed	
Product NameSafewayReceptacle TypeSingleSpecialtyN/ATypeConnectorUPC78678870677ChinaELVPhysicalFlangeNoFlip LidNoGenderFemaleLengthN/ALocking BladeYesPoles3-pole/4-wireElectricalCord TypeN/ACurrent - Maximum per Contact20.0AGFCINoLighted ConnectorNoVoltage - Maximum3Ø 480V	CH SVHC	
Receptacle TypeSingleStatusSpecialtyN/ANot ReTypeConnectorFor modelUPC78678870677ChinaPhysicalImageImageFlangeNoELVFlangeNoGenderFemaleLengthN/ALocking BladeYesPoles3-pole/4-wireElectricalImageCord TypeN/ACurrent - Maximum per Contact20.0AGFCINoLighted ConnectorNoVotage - Maximum3Ø 480V	Reviewed	
SpecialtyN/ANot RedTypeConnectorFor modeUPC78678870677ChinaPhysicalELVFlangeNoFlip LidNoGenderFemaleLengthN/ALocking BladeYesPoles3-pole/4-wireElectricalCord TypeN/ACurrent - Maximum per Contact20.0AGFCINoLighted ConnectorNoVoltage - Maximum30/ 480V	<u>gen-Free</u>	
Type UPCConnector 78678870677For mo China ELVPhysicalKoELVFlangeNoRoHSFlip LidNoRoHSGenderFemaleSeanLengthN/ASeanLocking BladeYes1301Poles3-pole/4-wire1301ElectricalV/ASeanCord TypeN/ASeanCurrent - Maximum per Contact20.0ANoGFCINoNoLighted ConnectorNoVoltage - Maximum3Ø 480V	S	
UPC 78678870677 Physical ELV Flange No Gender Female No Gender Female N/A Locking Blade Yes Poles 3-pole/4-wire 1307 Electrical Cord Type N/A Current - Maximum per Contact 20.0A GFCI No Lighted Connector No Voltage - Maximum 30/480V	Reviewed	
PhysicalChina ELVFlangeNoRoHSFlip LidNoRoHSGenderFemaleRoHSLengthN/ASeatLocking BladeYes1301Poles3-pole/4-wire1301ElectricalCord TypeN/ACurrent - Maximum per Contact20.0AGFCINoLighted ConnectorNoVoltage - Maximum3Ø 480V	ore informatic	on, please visit Contact US
PhysicalELVFlangeNoRoHSFlip LidNoRoHSGenderFemaleImageLengthN/ASeanLocking BladeYes1301Poles3-pole/4-wire1301ElectricalCord TypeN/ACurrent - Maximum per Contact20.0AGFCINoLighted ConnectorNoVoltage - Maximum3Ø 480V	50110	
FlangeNoRoHSFlip LidNoGenderFemaleLengthN/ALocking BladeYesPoles3-pole/4-wireElectricalCord TypeN/ACurrent - Maximum per Contact20.0AGFCINoLighted ConnectorNoVoltage - Maximum3Ø 480V	ROHS	Not Reviewed
Flip LidNoGenderFemaleLengthN/ALocking BladeYesPoles3-pole/4-wireElectricalCord TypeN/ACurrent - Maximum per Contact20.0AGFCINoLighted ConnectorNoVoltage - Maximum3Ø 480V		Not Reviewed
GenderFemaleLengthN/ALocking BladeYesPoles3-pole/4-wireElectricalCord TypeN/ACurrent - Maximum per Contact20.0AGFCINoLighted ConnectorNoVoltage - Maximum3Ø 480V	Phinalates	Not Reviewed
Length Locking Blade PolesN/ASear Yes 3-pole/4-wireElectrical Cord Type Current - Maximum per Contact GFCI Lighted Connector Voltage - MaximumN/ASear Yes 3Ø 480V		
Locking BladeYesPoles3-pole/4-wireElectricalCord TypeN/ACurrent - Maximum per Contact20.0AGFCINoLighted ConnectorNoVoltage - Maximum3Ø 480V		
Poles3-pole/4-wireElectricalCord TypeN/ACurrent - Maximum per Contact20.0AGFCINoLighted ConnectorNoVoltage - Maximum3Ø 480V	arch Parts in t	this Series
ElectricalCord TypeN/ACurrent - Maximum per Contact20.0AGFCINoLighted ConnectorNoVoltage - Maximum3Ø 480V	)145 Series	
Cord TypeN/ACurrent - Maximum per Contact20.0AGFCINoLighted ConnectorNoVoltage - Maximum3Ø 480V		
Current - Maximum per Contact20.0AGFCINoLighted ConnectorNoVoltage - Maximum3Ø 480V		
GFCINoLighted ConnectorNoVoltage - Maximum3Ø 480V		
Lighted ConnectorNoVoltage - Maximum3Ø 480V		
-		
Material Info		
Engineering Number 27T76		
Reference - Drawing Numbers         Sales Drawing       1301450039-000		

## This document was generated on 07/31/2021 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for AC Power Plugs & Receptacles category:

Click to view products by Molex manufacturer:

Other Similar products are found below :

 739W-X2/03-BACK1
 85447L
 1301460003
 1301520016
 1301520008
 14W07
 15W07
 22806
 929662-1
 27W75
 27W81
 962160-1

 29W08MB
 29W82
 26W
 26W76BLK
 27W47
 27W48
 28W
 28W81
 29W47MB
 HDR-E14FG1+
 30-9717-25
 43305
 85266
 5262DW
 22801

 22804
 25W47
 701W-15/06
 701W-20/27
 26W75
 27T76
 29T48
 739W-20/XX
 1301860536
 1301520018
 1301520021
 1301520020

 8210GY
 29W48
 3011-06
 A52S22A
 739W-X2/XX3
 26T49
 2707
 26W47-W
 1301450073
 RECWALLBOXBA
 1301490033