

This document was generated on 10/05/2021 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:	1451300303			
Status:	Active			
Overview:	Nano-Fit Power Connectors			
		Shelf (OTS) Cable Assembly, Single Row, Matte Tin (Sn)		
2000.1010	Plating, 300.00mm Length, 3			5-11
			Part of the second seco	SI.
Documents:			50	Sal
3D Model		Datasheet (PDF)	~	
Drawing (PDF)		RoHS Certificate of Compliance (PDF)		
3D Model (PDF)		<i></i>		
			Series image	e - Reference only
General				
Product Family		Cable Assemblies	EU ELV	
Series		145130	Not Relevant	
Application		Power, Wire-to-Board		China RoHS
Assembly Configuration		Dual Ended Connectors	EU RoHS Compliant	
Connector to Connector	or	Nano-Fit-to-Nano-Fit		
Overmolded		No	REACH SVHC Not Contained Per -	
Overview		Nano-Fit Power Connectors	D(2021)4569-DC (8	
Product Name		Nano-Fit	July 2021)	
Туре		Discrete Wire Assembly	Halogen-Free	
UPC		191130118830	Status	
Physical			Not Low-Halogen	
Cable Length		300.00mm		n, please visit <u>Contact US</u>
Circuits (Loaded)		3		n, please visit <u>Contact US</u>
Color - Resin		Black	China ROHS	Green Image
Gender		Female-Female	ELV	Not Relevant
Lock to Mating Part		Yes	RoHS Phthalates	Not Contained
Material - Metal		High Conductivity Copper		
Material - Plating Matin	a	Matte Tin		
Material - Plating Term		Matte Tin	Cooreh Dorto in 4	hia Cariaa
Material - Resin		Nylon	Search Parts in this Series	
Net Weight		8.004/g	<u>145130</u> Series	
Number of Rows		1		
Packaging Type		Bag	Mates With	
Pitch - Mating Interface		2.50mm	Nano-Fit Vertical Through Hole Headers	
Plating min - Mating		2.540µm	<u>1053091103</u> , <u>1053111103</u> . Nano-Fit Right-	
Plating min - Termination		2.540µm	Angle Through Hole Headers <u>1053131103</u> .	
Single Ended		No	Nano-Fit Vertical SMT Headers 1054311103	
Termination Interface: Style		Crimp or Compression	. Nano-Fit Right-Angle SMT Headers	
Wire Insulation Diameter		1.57mm	<u>1054301103</u> . Nano-Fit Plug Housing	
Wire Size AWG		20	<u>2002771103</u> , <u>200</u>	02 <u>//1203</u>
Wire/Cable Type		UL 1061		
Electrical				
Current - Maximum per	Contact	8.0A		
Voltage - Maximum	Contact	250V AC (RMS)		

Material Info

Reference - Drawing Numbers Sales Drawing

4000095318-000

This document was generated on 10/05/2021 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for DC Power Cords category:

Click to view products by Molex manufacturer:

Other Similar products are found below :

172-4000 172-4101 172-7443-E 21033836407 2J-1865A 2R7006A20A120 426055400-3 MN47A4BC01M010 H-OU-2 CA0002 420680840-3 426451500-3 P162PT4-36 1-832692-4 FJ-VSP 3M 96CB-POWER-B-1.8M2 426040200 CA0006 H-OU-27 1700019464 FJ-VSP 10M MN47B4BC01M040 H-OU-20 2-836917-8 867566-1 804001P03M050G 2050KH1-BK 426013710-3 58257-1069 216603-0037 1011147 1011324 1012028 862545-5 BXC-10567 172-2555 32102-022800-200-RS P29000-M2 P29004-M2 DC.CAB.0201.0150 DC.CAB.0301.0150 DC.CAB.0610.0150 DC.CAB.0700.0150 DC.CAB.1000.0150 DC.CAB.1000.0300 DC.CAB.1100.0150 DC.CAB.1400.0150 DC.CAB.1410.0150 DC.CAB.1500.0150 DC.CAB.1811.0150