

## This document was generated on 10/05/2021 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

	1 <u>451300600</u> Active			
				//8//
	Nano-Fit Power Connectors			
		Shelf (OTS) Cable Assembly, Single Row, Matte Tin (Sn)		
F	Plating, 75.00mm Length, 6 C	ircuits, Biack	3	
Documents: <u>3D Model</u> <u>3D Model (PDF)</u> Drawing (PDF)		Datasheet (PDF) RoHS Certificate of Compliance (PDF)	Series image	e - Reference only
Conorol			Series intage	
General Product Family		Cable Assemblies	EU ELV	
Series		145130	Not Relevant	
Application		Power, Wire-to-Board	NOT Relevant	
Assembly Configuration		Dual Ended Connectors	EU RoHS	China RoHS
Connector to Connector		Nano-Fit-to-Nano-Fit	Compliant	<u> </u>
Overmolded		No	REACH SVHC	
Overview		Nano-Fit Power Connectors	Not Contained Per -	
Product Name		Nano-Fit	D(2021)4569-DC (8	
Type		Discrete Wire Assembly	July 2021)	
UPC		191130118939	Halogen-Free	
		131130113333	<u>Status</u>	
Physical Ochlada an ath		75.00	Not Low-Halogen	
Cable Length		75.00mm	For more informatio	n, please visit <u>Contact US</u>
Circuits (Loaded)		6 Diask	China ROHS	Green Image
Color - Resin		Black	ELV	Not Relevant
Gender		Female-Female Yes	RoHS Phthalates	Not Contained
Lock to Mating Part Material - Metal		High Conductivity Copper		
		Matte Tin		
Material - Plating Mating		Matte Tin		
Material - Plating Termination Material - Resin			Search Parts in this Series	
•		Nylon	<u>145130</u> Series	
Net Weight Number of Rows		6.670/g 1		
Packaging Type		-	Mates With	
Packaging Type Pitch - Mating Interface		Bag 2.50mm	Nano-Fit Vertical	Through Hole Headers
Plating min - Mating		2.540µm	<u>1053091106</u> , <u>105</u>	3111106 . Nano-Fit Right-
Plating min - Termination	2	2.540μm	Angle Through Ho	le Headers <u>1053131106</u> .
Single Ended	1	Νο	Nano-Fit Vertical	SMT Headers <u>1054311106</u>
Termination Interface: St	tyle	Crimp or Compression		ngle SMT Headers
Wire Insulation Diameter		1.57mm		no-Fit Plug Housing
Wire Size AWG		20	<u>2002771106</u> , 200	2771206
Wire/Cable Type		UL 1061	,	
Electrical				
Current - Maximum per (	Contact	8.0A		
Voltage - Maximum		250V AC (RMS)		
Material Info		、 <i>、</i>		

## Material Info

**Reference - Drawing Numbers** Sales Drawing

4000095321-000

This document was generated on 10/05/2021

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for DC Power Cords category:

Click to view products by Molex manufacturer:

Other Similar products are found below :

172-4000 172-4101 172-7443-E 21033836407 2J-1865A 2R7006A20A120 426055400-3 MN47A4BC01M010 H-OU-2 CA0002 420680840-3 426451500-3 P162PT4-36 1-832692-4 FJ-VSP 3M 96CB-POWER-B-1.8M2 426040200 CA0006 H-OU-27 1700019464 FJ-VSP 10M MN47B4BC01M040 H-OU-20 2-836917-8 867566-1 804001P03M050G 2050KH1-BK 426013710-3 58257-1069 216603-0037 1011147 1011324 1012028 862545-5 BXC-10567 172-2555 32102-022800-200-RS P29000-M2 P29004-M2 DC.CAB.0201.0150 DC.CAB.0301.0150 DC.CAB.0610.0150 DC.CAB.0700.0150 DC.CAB.1000.0150 DC.CAB.1000.0300 DC.CAB.1100.0150 DC.CAB.1400.0150 DC.CAB.1410.0150 DC.CAB.1500.0150 DC.CAB.1811.0150