

This document was generated on 09/01/2021 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

| Part Number: | 1451320501 | | |
|--------------------------|--|--------------------------------------|--|
| Status: | Active | | |
| Overview: | Micro-Fit Connector System | em | |
| Description: | Micro-Fit TPA-to-Micro-Fit TPA Off-the-Shelf (OTS) Cable Assembly, Single Row, | | |
| | 150.00mm Length, 5 Circ | | |
| | | | |
| Documents: | | | |
| 3D Model | | Datasheet (PDF) | • |
| 3D Model (PDF) | | RoHS Certificate of Compliance (PDF) | |
| Drawing (PDF) | | | |
| | | | Series image - Reference only |
| General | | | |
| Product Family | | Cable Assemblies | EU ELV |
| Series | | <u>145132</u> | Not Relevant |
| Application | | Power, Wire-to-Board, Wire-to-Wire | |
| Assembly Configuratio | n | Dual Ended Connectors | EU RoHS China RoHS |
| Connector to Connector | or | Micro-Fit TPA Both Ends | Compliant |
| Overmolded | | No | REACH SVHC |
| Overview | | Micro-Fit Connector System | Not Contained Per - |
| Product Name | | Micro-Fit TPA | D(2021)4569-DC (8 |
| Туре | | Discrete Wire Assembly | July 2021) |
| UPC | | 191130115686 | Halogen-Free |
| | | | <u>Status</u> |
| Physical | | | Not Low-Halogen |
| Cable Length | | 150.00mm | For more information, please visit Contact US |
| Circuits (Loaded) | | 5 | China DOUC |
| Color - Resin | | Black | China ROHS Green Image |
| Gender | | Female-Female | ELV Not Relevant |
| Lock to Mating Part | | Yes | RoHS Phthalates Not Contained |
| Material - Metal | | Phosphor Bronze | |
| Material - Plating Matir | | Tin | |
| Material - Plating Term | ination | Tin | Search Parts in this Series |
| Material - Resin | | Nylon | 145132 Series |
| Net Weight | | 7.560/g | |
| Number of Rows | | 1 | Mates With |
| Packaging Type | | Bag | Micro-Fit 3.0 Plug Housing <u>43640</u> |
| Pitch - Mating Interface | | 3.00mm | <pre> <br <="" td=""/></pre> |
| Plating min - Mating | | 1.016µm | <pre> <br <="" td=""/></br></pre> |
| Plating min - Terminati | on | 1.016µm | |
| Single Ended | 0.1 | No | |
| Termination Interface: | | Crimp or Compression | |
| Wire Insulation Diamet | er | 1.85mm | |
| Wire Size AWG | | 20 | |
| Wire/Cable Type | | UL 1061 | |
| Electrical | | | |
| | | | |
| Current - Maximum pe | r Contact | 8.5A | |

Material Info

Reference - Drawing Numbers Sales Drawing

4000095242-000

This document was generated on 09/01/2021

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for DC Power Cords category:

Click to view products by Molex manufacturer:

Other Similar products are found below :

172-4000 172-4101 172-7443-E 21033836407 2J-1865A 2R7006A20A120 426055400-3 MN47A4BC01M010 H-OU-2 CA0002 420680840-3 426451500-3 P162PT4-36 1-832692-4 FJ-VSP 3M 96CB-POWER-B-1.8M2 426040200 CA0006 H-OU-27 1700019464 FJ-VSP 10M MN47B4BC01M040 H-OU-20 2-836917-8 867566-1 804001P03M050G 2050KH1-BK 426013710-3 58257-1069 216603-0037 1011147 1011324 1012028 862545-5 BXC-10567 172-2555 32102-022800-200-RS P29000-M2 P29004-M2 DC.CAB.0201.0150 DC.CAB.0301.0150 DC.CAB.0610.0150 DC.CAB.0700.0150 DC.CAB.1000.0150 DC.CAB.1000.0300 DC.CAB.1100.0150 DC.CAB.1400.0150 DC.CAB.1410.0150 DC.CAB.1500.0150 DC.CAB.1811.0150