

This document was generated on 12/27/2016

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: 0015244745

Status: **Active**

Overview: Disk Drive Power Connector

5.08mm Pitch Disk Drive Power Connection System Header, Vertical, Through Hole, 4 **Description:**

Circuits, Lead-Free, 3.58mm PC Tail Length, without PCB Locator Peg

Documents:

Packaging Specification PK-8981-3000 (PDF) 3D Model RoHS Certificate of Compliance (PDF) **Drawing (PDF)**

Packaging Specification PK-8981-1000 (PDF)

Agency Certification

LR19980 **CSA** UL E29179

General

Product Family PCB Headers

Series 8981

Application Power, Wire-to-Board

MolexKits Yes

Overview **Disk Drive Power Connector**

Product Name Disk Drive Power **UPC** 822348644537

Physical

Breakaway No Circuits (Loaded) 4 Circuits (maximum) Color - Resin Black Durability (mating cycles max) 25 First Mate / Last Break Nο Flammability 94V-0 Glow-Wire Compliant No Guide to Mating Part No Keying to Mating Part None Lock to Mating Part Yes Mated Height 24.00mm


Material - Metal **Phosphor Bronze**

Material - Plating Mating Tin Material - Plating Termination

Material - Resin High Temperature Thermoplastic

Net Weight 1.734/g Number of Rows 1 Orientation Vertical PC Tail Length 3.58mm PCB Locator Nο **PCB** Retention None PCB Thickness - Recommended 1.60mm Packaging Type Tray

Pitch - Mating Interface 5.08mm Plating min - Mating 2.540um Plating min - Termination 2.540um Polarized to Mating Part Yes Polarized to PCB No Shrouded **Fully** Stackable No Surface Mount Compatible (SMC) Yes



EU ELV

Not Relevant

EU RoHS China RoHS

Compliant **REACH SVHC** Not Contained Per -

ED/21/2016 (20 June

2016)

Halogen-Free

Status

Not Low-Halogen

Need more information on product environmental compliance?

Email productcompliance@molex.com Please visit the Contact Us section for any non-product compliance questions.

China ROHS Green Image **ELV** Not Relevant **RoHS Phthalates** Not Contained

Search Parts in this Series

8981 Series

Mates With

15-24-4048 (89814P) Disk Drive Power Connection System Female Crimp Housing with Terminal 02-08-1201 (8980-3C) or 02-08-1202 (8980-3L)

Temperature Range - Operating -40°C to +105°C Termination Interface: Style Through Hole

Electrical

Current - Maximum per Contact 6.5A Voltage - Maximum 250V AC

Solder Process Data

Duration at Max. Process Temperature (seconds) 010

Lead-freeProcess Capability SMC&WAVE

Max. Cycles at Max. Process Temperature 001
Process Temperature max. C 265

Material Info

Engineering Number A-8981-4V5-LF

Reference - Drawing Numbers

Packaging Specification PK-8981-1000, PK-8981-3000

Sales Drawing SD-8981-4V5

This document was generated on 12/27/2016

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Power to the Board category:

Click to view products by Molex manufacturer:

Other Similar products are found below:

```
6450171-4 6450552-7 6600323-8 6643429-1 6646040-2 6651939-1 6766604-1 120959-1 1393557-2 1393532-2 1393532-3 1393532-4 1393557-1 1600812-5 1-6450861-2 1744132-7 1761122-1 1766250-1 1892109-1 2-6450860-5 2-6450870-0 1-6450161-4 1-6450850-6 1-6450869-6 1645526-2 1-6600130-0 2005243-2 377-0020-11130 TE34-12-16P-F0 5-6450830-6 5646956-4 377-0080-11131A 4-6450830-9 4-6600333-3 10125416-4050LF 6600320-3 3-6450860-5 1888123-2 6450166-1 6643978-1 6766605-1 701-15-02109 N11444 6651938-1 6450810-7 46437-1112 1-1589677-8 5646956-5 6450813-2 6450129-4
```