

This document was generated on 08/31/2021 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: Status:	<u>1717222001</u> Active		EU ELV Not Relevant	
Overview: Description:		Quad Small Form Factor Pluggable Plus (zQSFP+) Stacked Integrated 2-by-2 Connector and Cage with Metal EMI Gasket, 152 Circuit, Gold (Au) Over Nickel Plated, No Light Pipe		<u>China RoHS</u>
			Not Contained Per -	
Agency Certification			D(2021)4569-DC (8	
UL		E29179	July 2021)	
General			Halogen-Free	
Product Family		I/O Connectors	<u>Status</u>	
Series		171722	Low-Halogen	
Application		Board-to-Board, Module-to-Board, Wire-to-Board	For more informatio	n, please visit Contact US
Component Type		Receptacle	China ROHS	Green Image
Electrical Model		Yes	ELV	Not Relevant
Overview		qsfp_and_zqsfp_integrated_product_solutions	RoHS Phthalates	Not Contained
Product Name		zQSFP Plus, zQSFP+		Not Contained
Туре		N/A		
UPC		887191261379	Search Parts in t	his Series
Physical			171722 Series	
Circuits (Loaded)		152		
Circuits (maximum)		152	Mates With	
Color - Resin		Black	QSFP Cable Asse	ambly 74757
Durability (mating cycles max)		100		<u>14101</u>
Flammability	yeles maxy	94V-0		
Keying to Mating Pa	art	None		
Lock to Mating Part		Yes		
Material - Metal		Copper Alloy		
Material - Plating Mating		Gold		
Material - Plating Mating Material - Plating Termination		Matte Tin		
Material - Plating Termination Material - Resin		High Temperature Thermoplastic		
Net Weight		62.223/g		
Number of Rows		2		
Orientation		Z Right Angle		
PC Tail Length		1.20mm		
PC Tail Length PCB Locator		Yes		
PCB Retention		Yes		
PCB Retention PCB Thickness - Recommended		1.57mm		
Packaging Type	Joonmondou	Tray		
Panel Mount		N/A		
Pitch - Mating Interf	ace	0.80mm		
Plating min - Mating		0.762µm		
Plating min - Termination		0.762µm		
Plating min - Termination Polarized to Mating Part		Yes		
Polarized to PCB		Yes		
Ports		4		
Surface Mount Compatible (SMC)		No		
Temperature Range - Operating		-40° to +85°C		
Termination Interface: Style		Through Hole - Compliant Pin		
Electrical		0.54		
Current - Maximum per Contact		0.5A		
Grounding to Panel		Yes		
Shield Type		EMI Fingers		
Voltage - Maximum		30V AC (RMS)/DC		

Solder Process Data Lead-freeProcess Capability	N/A
Material Info	
Reference - Drawing Numbers Application Specification	AS-171565-0
Electrical Model Document Packaging Specification	EE-171081-30 PK-171565-00
Product Specification	PS-171565-0
S-Parameter Model	SP-171081-30
Sales Drawing Symbol/Footprint Data	SD-171722-2 SYM-171722-
Test Summary	TS-171565-00

0002-001 3000-001 0001-001 0001-001 3000-001 2000-001 2-2000-001 0001-001

This document was generated on 08/31/2021 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for I/O Connectors category:

Click to view products by Molex manufacturer:

Other Similar products are found below :

 571763P
 58098-0628
 72.250.1628.2
 72.250.2428.2
 74720-0505
 76.350.0729.0
 76871-1403
 FCN-244F080-G/1
 FCN-260A9920
 PCR

 E36PM
 PCS-XE26MA+
 G38A71314B
 1571250010
 157-22500-3
 MS3471L14-19P L/C
 192991-0703
 172501-4002
 172501-6002
 FCN

 260C008-A/L0
 FCN-260C024-AL0
 FCN-261Z008
 2000314-1
 200331-1
 PCR-E36FC+
 PCS-E28FS+
 PCS-XE26SLFD+
 PCS

 XE26SLFDT+
 G730VID08BDC24
 U90B2054081210
 38113800006
 DP3AR020WQ1R200
 Z4.102.0680.0
 500-1040
 500-1052
 500-1054

 ZP-4008-66L
 0709821002
 DX40-20P(55)
 5554841-1
 MS3474W18-8P-LC*
 U90B3054061110
 U65-E04-4020
 ZPF000000000097891

 747360449
 10099439-003C-TRLF
 10137239-001LF
 F0320-001-01
 10137239-001LF
 70289-001LF
 70.060.1028.0