

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: [1719832042](#)
Status: **Active**
Overview: Nano-Pitch I/O Interconnect System
Description: Nano-Pitch I/O Receptacle, Vertical, Through Hole, with Cap, 42 Circuits, Shell Tab Length 3.00mm, Black

Documents:

3D Model	Application Specification AS-173162-0002-001 (PDF)
Drawing (PDF)	Packaging Specification PK-171982-9000-001 (PDF)
3D Model (PDF)	Packaging Specification PK-173307-0001-001 (PDF)
Product Specification PS-173162-0001-001 (PDF)	Symbol Footprint Data SYM-171983-2042-001 (PDF)
Application Specification AS-173162-0001-001 (PDF)	RoHS Certificate of Compliance (PDF)

Agency Certification

UL E29179

General

Product Family	I/O Connectors
Series	171983
Application	Wire-to-Board
Component Type	Receptacle
Overview	Nano-Pitch I/O Interconnect System
Product Name	Nano-Pitch I/O
Type	N/A
UPC	889056257077

Physical

Circuits (Loaded)	42
Circuits (maximum)	42
Color - Resin	Black
Durability (mating cycles max)	250
Gender	Receptacle
Keying to Mating Part	None
Lock to Mating Part	Yes
Material - Metal	Copper Alloy
Material - Plating Mating	Gold
Material - Plating Termination	Tin
Material - Resin	High Temperature Thermoplastic
Net Weight	0.750/g
Number of Rows	2
Orientation	Vertical
PCB Locator	Yes
PCB Retention	Yes
PCB Thickness - Recommended	1.57mm
Packaging Type	Embossed Tape on Reel
Panel Mount	No
Pitch - Mating Interface	0.50mm
Pitch - Termination Interface	0.50mm
Plating min - Mating	0.762µm
Plating min - Termination	2.540µm
Polarized to Mating Part	Yes
Polarized to PCB	Yes
Ports	1
Temperature Range - Operating	-40° to +80°C
Termination Interface: Style	Through Hole
Waterproof / Dustproof	No



Series image - Reference only

EU ELV

Not Relevant

EU RoHS

Compliant

REACH SVHC

Not Contained Per -
D(2021)4569-DC (8
July 2021)

Halogen-Free

Status

Low-Halogen

For more information, please visit [Contact US](#)

China ROHS

ELV

RoHS Phthalates

China RoHS

Green Image

Not Relevant

Not Contained

Search Parts in this Series

[171983 Series](#)

Electrical

Current - Maximum per Contact	0.5A
Grounding to Panel	None
Shielded	No
Voltage - Maximum	30V AC (RMS)/DC

Solder Process Data

Duration at Max. Process Temperature (seconds)	020
Lead-free Process Capability	REFLOW
Max. Cycles at Max. Process Temperature	001
Process Temperature max. C	260

Material Info**Reference - Drawing Numbers**

Application Specification	AS-173162-0001-001, AS-173162-0002-001
Electrical Model Document	EE-171983-0005-002
Packaging Specification	PK-171982-9000-001, PK-173307-0001-001
Product Specification	PS-173162-0001-001
S-Parameter Model	SP-171983-0005-001
Sales Drawing	SD-171983-1000-001
Symbol/Footprint Data	SYM-171983-2042-001

This document was generated on 10/05/2021

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [I/O Connectors](#) category:

Click to view products by [Molex](#) manufacturer:

Other Similar products are found below :

[00110100410](#) [00111400134](#) [01.001.6293.0](#) [0107-001-000](#) [0107-003-000](#) [016020114](#) [16-02-0114](#) [70021-0221](#) [02KR-6H-P](#) [02NR-E4K](#)
[02SUR-32S](#) [02T-JWPF-VSLE-S](#) [03KR-6H-P](#) [03NR-E4K](#) [03R-JWPF-VSLE-S](#) [03ZR-8M-P](#) [04.090.0680.0](#) [04KR-6H-P](#) [04NR-E4K](#) [04R-](#)
[JWPF-VSLE-S](#) [04T-JWPF-VSLE-S](#) [0678008002](#) [06KR-6H-P](#) [0709821002](#) [0747280003](#) [07790000155](#) [08KR-6H-P](#) [08NR-E4K](#) [08T-JWPF-](#)
[VSLE-D](#) [09180009903](#) [100013-0181](#) [100014-1240](#) [100014-1242](#) [100014-1341](#) [100014-1345](#) [1000141447](#) [100014-1448](#) [100014-1541](#)
[100014-1542](#) [100015-1444](#) [1000151445](#) [1000151640](#) [100017-1344](#) [100113-0220](#) [100113-4210](#) [100114-0410](#) [100114-0420](#) [100115-0610](#)
[10017660-001LF](#) [10022676-001LF](#) [10029065-001CLF](#) [10029065-001C-TRLF](#)