

**PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION**

**Part Number:** [1722992110](#)  
**Status:** **Active**  
**Overview:** [Ultra-Fit Power Connectors](#)  
**Description:** Ultra-Fit Vertical Header, 3.50mm Pitch, Dual Row, 10 Circuits, with Solder Clips, Tin (Sn) Plating, Natural, Glow-Wire Capable

**Documents:**

|  |  |
|--|--|
| <a href="#">Drawing (PDF)</a>                                    | <a href="#">Product Specification PS-172323-0001-001 (PDF)</a>     |
| <a href="#">3D Model</a>   | <a href="#">Application Specification AS-172323-0001-001 (PDF)</a> |
| <a href="#">3D Model (PDF)</a>                                   | <a href="#">Packaging Specification PK-172299-9001-001 (PDF)</a>   |
| <a href="#">Product Specification 1723230001-TS-000 (PDF)</a>    | <a href="#">Symbol Footprint Data 1722991110-000 (PDF)</a>         |
| <a href="#">Product Specification 1723231000-PS-CH-000 (PDF)</a> | <a href="#">Symbol Footprint Data SYM-172299-1110-001 (PDF)</a>    |
| <a href="#">Product Specification 1723231000-PS-ES-000 (PDF)</a> | <a href="#">RoHS Certificate of Compliance (PDF)</a>               |
| <a href="#">Product Specification 1723231000-PS-JP-000 (PDF)</a> | <a href="#">Product Literature (PDF)</a>                           |
| <a href="#">Product Specification 1723231000-PS-SK-000 (PDF)</a> |  |

**Agency Certification**


|     |         |
|-----|---------|
| CSA | LR19980 |
| UL  | E29179  |

**General**

|                |   |
|----------------|---|
| Product Family | PCB Headers   |
| Series         | <a href="#">172299</a>  |
| Application    | Power, Wire-to-Board  |
| Comments       | See Product Specification for maximum current rating by circuit size and wire AWG |
| Overview       | <a href="#">Ultra-Fit Power Connectors</a>  |
| Product Name   | Ultra-Fit   |
| UPC            | 887191737775  |

**Physical**

|                                |                        |
|--------------------------------|------------------------|
| Breakaway                      | No                     |
| Circuits (Loaded)              | 10                     |
| Circuits (maximum)             | 10                     |
| Color - Resin                  | Natural                |
| Durability (mating cycles max) | 25                     |
| First Mate / Last Break        | No                     |
| Flammability                   | 94V-0                  |
| Glow-Wire Capable              | Yes                    |
| Guide to Mating Part           | No                     |
| Keying to Mating Part          | Yes                    |
| Lock to Mating Part            | Yes                    |
| Material - Metal               | Copper Alloy           |
| Material - Plating Mating      | Tin                    |
| Material - Plating Termination | Tin                    |
| Material - Resin               | Liquid Crystal Polymer |
| Net Weight                     | 2.790/g                |
| Number of Rows                 | 2                      |
| Orientation                    | Vertical               |
| PC Tail Length                 | 3.20mm                 |
| PCB Locator                    | Yes                    |
| PCB Retention                  | Yes                    |
| PCB Thickness - Recommended    | 1.60mm                 |
| Packaging Type                 | Tray                   |
| Pitch - Mating Interface       | 3.50mm                 |
| Pitch - Termination Interface  | 3.50mm                 |
| Plating min - Mating           | 1.524µm                |



*Series image - Reference only*

**EU ELV**

**Not Relevant**

**EU RoHS**

**Compliant**

**REACH SVHC**

Not Contained Per -  
D(2020)9139-DC (19  
Jan 2021)

**Halogen-Free**

**Status**

**Low-Halogen**

For more information, please visit [Contact US](#)

China ROHS

ELV

RoHS Phthalates

**China RoHS**

Green Image

Not Relevant

Not Contained

**Search Parts in this Series**

[172299 Series](#)

**Mates With**

Ultra-Fit Receptacle Housing [1722584110](#)

|                                |                |
|--------------------------------|----------------|
| Plating min - Termination      | 1.524µm        |
| Polarized to Mating Part       | Yes            |
| Polarized to PCB               | Yes            |
| Shrouded                       | Fully          |
| Surface Mount Compatible (SMC) | Yes            |
| Temperature Range - Operating  | -40° to +105°C |
| Termination Interface: Style   | Through Hole   |

**Electrical**

|                               |                  |
|-------------------------------|------------------|
| Current - Maximum per Contact | 12.0A            |
| Voltage - Maximum             | 400V AC (RMS)/DC |

**Solder Process Data**

|  |      |
|--|------|
| Duration at Max. Process Temperature (seconds) | 090  |
| Lead-free Process Capability                   | WAVE |
| Max. Cycles at Max. Process Temperature        | 002  |
| Process Temperature max. C                     | 260  |

**Material Info****Reference - Drawing Numbers**

|                           |   |
|---------------------------|---|
| Application Specification | AS-172323-0001-001  |
| Packaging Specification   | PK-172299-9001-001  |
| Product Specification     | 1723230001-TS-000, 1723231000-PS-CH-000,<br>1723231000-PS-ES-000, 1723231000-PS-JP-000,<br>1723231000-PS-SK-000, PS-172323-0001-001 |
| Sales Drawing             | SD-172299-1000-000  |
| Symbol/Footprint Data     | 1722991110-000, SYM-172299-1110-001   |

This document was generated on 08/23/2021

**PLEASE CHECK [WWW.MOLEX.COM](http://WWW.MOLEX.COM) FOR LATEST PART INFORMATION**

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Headers & Wire Housings](#) category:*

*Click to view products by [Molex](#) manufacturer:*

Other Similar products are found below :

[892-18-020-10-001101](#) [58102-G61-06LF](#) [582553-1](#) [0009485154](#) [009176003701906](#) [0050291907](#) [LY20-4P-DT1-P1E-BR](#) [02.125.8002.8](#)  
[609-3404](#) [61062-3](#) [622-0430](#) [622-3653LF](#) [63453-116](#) [636-1030](#) [636-1427](#) [636-3427](#) [636-4007](#) [641938-9](#) [641991-4](#) [644827-2](#) [65817-010LF](#)  
[65817-015LF](#) [65863-015LF](#) [66207-023LF](#) [67095-007LF](#) [67601157](#) [68648-049](#) [70.362.1628.0](#) [70-4210](#) [70-4226B](#) [70-4853B](#) [707-5020](#) [707-](#)  
[5028](#) [71.350.2428.0](#) [71918-208LF](#) [71961-016LF](#) [733-134](#) [733-162](#) [754199-000](#) [760-3052](#) [787-8014-00](#) [79531-3000](#) [FCN-360C032-B](#) [FCN-](#)  
[367T-T012/H](#) [FCN-723D010/2](#) [80.063.4001.1](#) [800-90-001-10-001000](#) [800-90-010-10-002000](#) [801-43-002-10-013000](#) [801-43-006-10-002000](#)