

## This document was generated on 04/10/2020 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

| Part Number:                   | 1727040055           |   |  |
|--------------------------------|----------------------|---|--|
| Status:                        |                      |   |  |
|                                | Active               |   |  |
| Overview:                      | FCT D-Sub Connectors |   | FOTILJ FHOR2551  |
| Description:                   |                      | erproof D-Sub Connector, Female, Straight, PCB Through      | Contraction of the Contraction of the Contraction of the Contraction |
|                                |                      | sphorus Plating, Plastic Watertight Frame, Snap-in Bolt, 25 |  |
|                                | Circuits             |   |  |
|                                |                      |   |  |
| Documents:                     |                      |   |  |
| Datasheet (PDF)                |                      | RoHS Certificate of Compliance (PDF)                        |  |
| Brochure (PDF)                 |                      |   |  |
|                                |                      |   | - Series image - Reference only                                      |
| General                        |                      |   |  |
| Product Family                 |                      | D-Sub Products  | EU ELV   |
| Series                         |                      | 172704  | Not Relevant   |
|                                |                      | IP67  | Not Relevant   |
| IP Rating<br>Overview          |                      |   | EU RoHS China RoHS   |
|                                |                      | FCT D-Sub Connectors  | Not Reviewed   |
| Product Category               |                      | D-Sub Connector   | REACH SVHC   |
| Product Name                   |                      | FCT Products  | Not Reviewed   |
| Туре                           |                      | Standard Density  | Halogen-Free   |
| UPC                            |                      | 889056019668  |  |
| Dhysical                       |                      |   | <u>Status</u>  |
| Physical                       |                      | 25  | Not Reviewed   |
| Circuits (Loaded)              |                      | 25  | For more information, please visit <u>Contact US</u>                 |
| Circuits (maximum)             |                      | 25  | China ROHS Not Reviewed  |
| Color - Resin                  |                      | Red   | ELV Not Relevant   |
| Durability (mating cycles max) |                      | 500   |  |
| Gender                         |                      | Female  | RoHS Phthalates Not Reviewed   |
| Material - Contact             |                      | Copper Alloy  |  |
| Material - Resin               |                      | PBT   |  |
| Material - Shell               |                      | Brass   | Search Parts in this Series  |
| Net Weight                     |                      | 18.200/g  | <u>172704</u> Series   |
| Number of Rows                 |                      | 2   |  |
| Orientation                    |                      | Straight  | Mates With   |
| PC Tail Length                 |                      | 11.20mm   | FCT Standard Density D-Sub, Size 3, 25                               |
| PCB Locator                    |                      | Yes   |  |
| PCB Retention                  |                      | Yes   | Position, Plug   |
| PCB Thickness - Rec            | ommended             | 1.60mm  |  |
| Packaging Type                 |                      | Carton  | Use With   |
| Panel Mount                    |                      | Rear  | FCT D-Sub Dust Caps  |
| Panel Mount Method             |                      | Thread-In   |  |
| Pitch - Mating Interfac        | ce                   | 2.84mm  |  |
| Pitch - Termination In         |                      | 2.84mm  |  |
| Plating - Contact              |                      | Gold over Nickel Phosphorus                                 |  |
| Plating - Shell                |                      | Tin   |  |
| Polarized to Mating P          | art                  | Yes   |  |
| Polarized to PCB               |                      | Yes   |  |
| Ports                          |                      | 1   |  |
| Shielded                       |                      | Yes   |  |
| Temperature Range -            | Operating            | -25° to +70°C   |  |
| Termination Style              | Operating            | Through Hole  |  |
|                                | of                   | -   |  |
| Waterproof / Dustproo          |                      | Yes   |  |
| Waterproof / Dustproo          | туре                 | IP67  |  |
| Electrical                     |                      |   |  |
| Current - Maximum pe           | er Contact           | 7.5A  |  |
|                                |                      | 1.0/1   |  |
| Material Info                  |                      |   |  |

## This document was generated on 04/10/2020 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for D-Sub Standard Connectors category:

Click to view products by Molex manufacturer:

Other Similar products are found below :

DCM37S732N DAM15P500 DEV09S364GTLF DEM09P032N DDM50P732N DAM15S332N 173109-2218 173109-2466 173109-2469 173109-2435 56F706-005-LI 56F711-015 015-0341-000 017041-0005 012-9507-114 012-9534-001 609-25P M24308/2-23Z M243082310F M24308/2-36Z M243082411F M24308315F M24308/4-21 M243084437F CT0M22-23SS CT1N36-5SC CT2-16S-17PS CT2-20-15PCAU CT2-24-12PS CT2-24-28PSF127A206 CT6F9767-14-4-14S-5PC CT7-18-10SC CT7-18-10SCAU CT7-18-12SCAU CT7-18-1PC CT7-18-1PCAU CT7-18-1SC CT7-18-21SCAU CT9-16-12PS M83513/01-FC M83723/76W24619 L/C M85049/48-3-2F 69001-865 6STD09PCM99B70X 6STD09SCM99B30X 6STD09SCT99S40X 6STD15PCT99S40X 6STD15SCM99B30X 6STD15SCT99S40X 6STF09PCM05B70X