

This document was generated on 02/20/2021 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:	1728790004		
Status:	Active		
Active		re Card Dowar Connector	
Overview: Description:		ate Wire-to-Board Edge Card Connector, Female, Nylon 6, Black,	
Description.		, Glow-Wire Capable, 4 Circuits	
Replacement Part		/molex/search/partSearch?	
		uery=17215906041721590604	متعقيل المالية فالمتعاد
Documents:			
<u>Drawing (PDF)</u> Product Specification PS-172160-0001-001 (PDF)		RoHS Certificate of Compliance (PDF)	On the transmission of the
Product Specification	PS-172160-0001-001 (F	2DF)	Series image - Reference only
Agency Certification	,		EU ELV
	1	E29179	Not Relevant
UL		223113	Not Nelevant
Application tooling			EU RoHS China RoHS
Application Tooling P	art Link	11-03-0016	Compliant
General			REACH SVHC
Product Family		Edge Card Connectors	Not Contained Per -
Series		172879	D(2020)9139-DC (19
Comments		See Product Specification for maximum current rating by	Jan 2021)
Comments		wire AWG and terminal material.	Halogen-Free
Component Type		Edgecard to Wire	<u>Status</u>
Data Rate		Unrated	Not Low-Halogen
Edge Card Thickness		N/A	For more information, please visit <u>Contact US</u>
High Power Bay (30.0A or more)		No	China ROHS Green Image
Orientation		Right-Angle	ELV Not Relevant
Overview		EdgeMate Wire-to-Edge-Card Power Connector	RoHS Phthalates Not Contained
Product Name		EdgeMate	
Replacement Part Nu	Imber	1721590604	
Replacement Part Number		Non glow-wire	
Standard Based		General	Search Parts in this Series
UPC		889056377058	<u>172879</u> Series
Dhuciaal			
Physical	iguration	12 02	Mates With
(p)ower-(s)ignal Configuration		4p - 0s 1-64 Circuits	Edge Card PCB
Circuit Size Range Circuits (Loaded)			
Circuits (maximum)		4	Use With
Color - Resin		Black	<u>172160</u>
Durability (mating cyc	les max)	25	
Entry Angle		90° Angle	Application Tooling FAQ
Flammability		94V-2	Tooling specifications and manuals are
Keying to Mating Part	t	None	found by selecting the products below.
Material - Plating Mat		N/A	Crimp Height Specifications are then
Material - Resin		Nylon	contained in the Application Tooling
Net Weight		1.791/g	Specification document.
PCB Locator		No	Global
PCB Retention		None	Description Product #
PCB Thickness - Recommended		1.57mm	Extraction Tool <u>11030016</u>
Packaging Type		Bag	for Flat Blade,
Panel Mount		No	3.96mm KK,
Pitch - Mating Interface		3.96mm	2.00mm, 3.96mm
Polarized to Mating Part		No	EdgeMate, and Ultra-
Temperature Range - Operating		-40° to +105°C, -40° to +80°C	Fit Terminals
Termination Interface: Style		Straddle Mount-Edge Card	

Electrical Current - Maximum per Contact Voltage - Maximum	7.0A 250V			
Solder Process Data Lead-freeProcess Capability	N/A			
Material Info				
Reference - Drawing Numbers Product Specification Sales Drawing	PS-172160-0001-001 SD-172879-0000-000			

This document was generated on 02/20/2021 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Standard Card Edge Connectors category:

Click to view products by Molex manufacturer:

Other Similar products are found below :

CR7E-30DB-3.96E(72) 6364499-1 6565204-6 PKC-156 1437274-4 147889-1 1489165-4 EBT15622B2X 1-582587-1 284-0102-12100 286-0052-12101A 30602290100000 307-012-502-202 307-056-520-300 2129318-1 245-062-520-350 287-0032-12101 306-028-525-102 307-072-526-202 345-060-559-303 392-008-559-201 534671-1 341-240-317 345-044-500-300 346-240-318 395-100-524-300 09-07-2032 10035388-802LF 10122859-009LF 10127905-B04B24BLF 530555-1 5-678046-1 73726-0005 66308-1 1-1437275-6 PEC-07-02-T-S-A 346-014-520-801 307-048-502-202 CE100F22-9-C CE100F26-7-C CE100F28-3-D CE156F18-9-C CE156F22-5-D CE156F22-9-C CT100F22-2-D CT100F22-3-D CT100F24-2-D CT100F24-3-D CT100F24-6-C CT156F22-4-D