

## This document was generated on 10/05/2021 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:	4700500000		
Status:	1729520802		•
	Active		
Overview: Description:	Micro-Fit Connector System	using, Dual Row, 8 Circuits, UL 94V-2, Glow-Wire	At all
Description.	Capable, Black	Ising, Dual Row, 8 Circuits, OL 94V-2, Glow-Wile	10000
Documents:			0580
Drawing (PDF)		Packaging Specification 1729520001-PK-000 (PDF)	
<u>3D Model</u>		Test Summary 430450006-TS-000 (PDF)	-
<u>3D Model (PDF)</u>		Test Summary TS-43045-001-001 (PDF)	
	430450001-PS-KO-000 (PDF)	Test Summary TS-43045-002-001 (PDF)	Series image - Reference only
	430450001-PS-SP-000 (PDF)	RoHS Certificate of Compliance (PDF)	
Product Specification	<u>PS-43045-001 (PDF)</u>	Product Literature (PDF)	<u>EU ELV</u>
			Not Relevant
Agency Certification		LR19980	EU RoHS China RoHS
UL		E29179	Compliant
		223173	REACH SVHC
General			Not Contained Per -
Product Family		Crimp Housings	D(2021)4569-DC (8
Series		172952	July 2021)
Application Comments		Power, Wire-to-Board, Wire-to-Wire See Product Specification for maximum current rating	<u>Halogen-Free</u> Status
Commenta		by circuit size and wire AWG by circuit size and wire AWG 	Not Low-Halogen
		product is manufactured from material that has the	For more information, please visit Contact US
		following ratings, tested by independent agencies:	
		a) AGlow Wire Ignition Temperature (GWIT) of	China ROHS Green Image
		at least 775 deg C per IEC 60695-2-13. b) A	ELV Not Relevant RoHS Phthalates Not Contained
		Glow Wire Flammability Index (GWFI) above 850 deg	ROHS Philipalales Not Contained
		Cper IEC 60695-2-12 and hence complies with the requirements set out in the International Standard IEC	
		60335-1 5th edition - household and similar electrical	Counch Dente in this Conice
		appliances - safety, section 30 Resistance to heat	Search Parts in this Series 172952 Series
		and fire. >The customers using this product	
		must determine its suitability for use in their particular	Mates With
		application through testing or other acceptable means	Micro-Fit 3.0 Plug Housing <u>43020</u> , <u>203632</u>
		as described in end-product glow-wire flammability test standard IEC 60695-2-11 and any applicable product	<pre> &gt; Micro-Fit 3.0 Header 43045</pre>
		end-use standard(s). -br>lf it is determined during	
		the customer's evaluation of suitability, that higher	Use With
		performance is required, please contact Molex for	Micro-Fit TPA Retainer <u>172953</u> br>Micro-
		possible product options.	Fit 3.0 Female Terminal <u>43030</u> br>Micro-
Overview		Micro-Fit Connector System	Fit RMF Reduced Mating Force Terminal 46235 br>Micro-Fit 3.0 Pre-Crimped Leads
Product Name		Micro-Fit TPA 889056429764	<u>46235</u> 797580002 , 797580004 , 797580010 ,
		009030429704	797580012
Physical			
Circuits (maximum)		8	
Color - Resin		Black 94V-2	
Flammability Gender		94V-2 Receptacle	
Glow-Wire Capable		Yes	
Keying to Mating Part		None	
Lock to Mating Part		Yes	
Material - Resin		Nylon	
Net Weight		0.669/g	
Number of Rows		2	

Packaging Type Panel Mount Pitch - Mating Interface Polarized to Mating Part Stackable Temperature Range - Operating

## **Material Info**

**Reference - Drawing Numbers** Packaging Specification Product Specification

Sales Drawing Test Summary 1729520001-PK-000 430450001-PS-KO-000, 430450001-PS-SP-000, PS-43045-001 SD-172952-002-001 430450006-TS-000, TS-43045-001-001, TS-43045-002-001

Bag

3.00mm

-40° to +125°C

No

Yes

No

## This document was generated on 10/05/2021 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Headers & Wire Housings category:

Click to view products by Molex manufacturer:

Other Similar products are found below :

 892-18-020-10-001101
 58102-G61-06LF
 582553-1
 0009485154
 009176003701906
 0050291907
 LY20-4P-DT1-P1E-BR
 02.125.8002.8

 609-3404
 61062-3
 622-0430
 622-3653LF
 63453-116
 636-1030
 636-1427
 636-3427
 636-4007
 641938-9
 641991-4
 644827-2
 65817-010LF

 65817-015LF
 65863-015LF
 66207-023LF
 67095-007LF
 67601157
 68648-049
 70.362.1628.0
 70-4210
 70-4226B
 70-4853B
 707-5020
 707 

 5028
 71.350.2428.0
 71918-208LF
 71961-016LF
 733-134
 733-162
 754199-000
 760-3052
 787-8014-00
 79531-3000
 FCN-360C032-B
 FCN 

 367T-T012/H
 FCN-723D010/2
 80.063.4001.1
 800-90-001-10-001000
 800-90-010-10-002000
 801-43-002-10-013000
 801-43-006-10-002000