

This document was generated on 07/31/2021 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

| Part Number: | 1731070186 | | | |
|----------------------------------|--------------------------------|---|----------------------|---|
| Status: | | | | |
| | Active | | | |
| Overview: | | | | |
| | | p Housing, Female, Tin-plated Shell without Dimples, 36 | | · · · · · · · · · · · · • • • • • • • • |
| | Circuits, 32 Unloaded Signal C | ontact Positions | | *0 0 0 0 0 0 0 0 |
| | | | (******* | 000000000000000000000000000000000000000 |
| Documents: | | | | |
| Datasheet (PDF) | | RoHS Certificate of Compliance (PDF) | | |
| Brochure (PDF) | | | | |
| Osmanal | | | Series imag | e - Reference only |
| General Droduct Fomily | | D-Sub Products | - Contoo iniugi | |
| Product Family Series | | | FUELV | |
| • | | <u>173107</u> IP20 | EU ELV | |
| IP Rating Overview | | | Not Relevant | |
| Product Category | | FCT D-Sub Connectors D-Sub Connector | EU RoHS | China RoHS |
| Product Category Product Name | | FCT Products | Compliant | |
| | | | REACH SVHC | |
| Type UPC | | Mixed Layout 889056485623 | Not Reviewed | |
| UPC | | 009000400020 | Halogen-Free | |
| Physical | | | Status | |
| Circuits (Loaded) | | 0 | Not Reviewed | |
| Circuits (maximum) | | 36 | | n, please visit <u>Contact US</u> |
| Color - Resin | | Black | | n, ploade vien <u>eennaar ee</u> |
| Durability (mating cyc | les max) | 500 | China ROHS | Green Image |
| Gender | | Female | ELV | Not Relevant |
| Material - Resin | | PBT | RoHS Phthalates | Not Contained |
| Material - Shell | | Steel | | |
| Net Weight | | 13.300/g | | |
| Number of Rows | | 3 | Search Parts in t | his Sorios |
| Orientation | | Straight | <u>173107</u> Series | |
| PCB Locator | | No | | |
| PCB Retention | | None | | |
| Packaging Type | | Carton | Mates With | |
| Panel Mount | | Rear | | t D-Sub, Size 5, 36W4, |
| Panel Mount Method | | Flange | Plug | |
| Pitch - Mating Interfac | | 2.84mm | | |
| Pitch - Termination In | terface | 2.84mm | Use With | |
| Plating - Shell | | Tin | | n Power, High Voltage, or |
| Polarized to Mating P | art | Yes | Pneumatic Conta | cts |
| Ports | | 1 | | |
| Shielded | | Yes | | |
| Temperature Range - | | -55° to +115°C | | |
| Waterproof / Dustproo | | No | | |
| Waterproof / Dustproo | of Type | IP20 | | |
| Wire Size AWG | | 18, 20, 22, 24, 26, 28 | | |
| Material Info | | | | |
| Engineering Number | | FL36W4S7-K121 | | |
| | | | | |

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for D-Sub Mixed Contact Connectors category:

Click to view products by Molex manufacturer:

Other Similar products are found below :

790-025SF-5P5NMN790-025SJ-7P7NMLDAM-7W2PCL717TWB5W5P3RL717TWB5W5PRM84L717TWP3W3P3003W3PXX56N40X3005W5PXX99E40X3005W5SXX99A30X3005W5SXX99E40X3013W6SCM99A10X3036W4PCM41A10X3036W4SCM99A10XFCE17-E2W2SS-2N0212522-7PII-468-13003W3PXX43A10X3003W3SXX56N40X3005W5PXX88N40X3007W2PAR71E20X3008W8SXX57A30X3009W4PCT57P20X3011W1SXK99A10X3017W2SAR69C40X321WA4PXK99A60X3F3SSC22S41A30XL717TWA7W2PP2SY3RDBM-17W2S-1A8N-A190-A197-1421WA4PCR50E20X09691009009096911000225000969300917609692009147096939090156017W2PCM41B30X790-061SH-36W2NMNA790-044SE-7P3MNPB790-043PE-11P2MPA790-043PB-2P2MPB790-029SB-2P2MEPA790-028PK-9P9MPA790-028PH-54P2MGA790-028PH-36P2MNA790-028PB-2P2MPA790-028PB-2P2MPA027SH-5W5MTEP790-026PH-54P2ZNUG790-026PH-54P2MP790-026PH-36P2ZNUG790-026PH-36P2MG790-026PD-3P3MP