

This document was generated on 07/28/2021 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:	<u>1731070268</u>		
Status: Active Overview: FCT D-Sub Connectors			
	FCT D-Sub Connectors FCT Mixed Layout D-Sub Connector, Male, Right-Angle, PCB Through Hole, Gold Plating, Tin-plated Shell with Dimples, 5 Circuits, 4 Signal Contacts Loaded		$\begin{pmatrix} 1 \\ 0 \end{pmatrix}$ $A^1 \begin{pmatrix} 0^2 \end{pmatrix}$
Description:			
	Plating, Tin-plated Si	nell with Dimples, 5 Circuits, 4 Signal Contacts Loaded	
_			
Documents:			
Datasheet (PDF)		RoHS Certificate of Compliance (PDF)	
Brochure (PDF)			
General			Series image - Reference only
Product Family		D-Sub Products	
Series		173107	EU ELV
IP Rating		IP20	Not Relevant
Overview		FCT D-Sub Connectors	Not Relevant
		D-Sub Connector	EU RoHS China RoHS
Product Category Product Name		FCT Products	Not Reviewed
			REACH SVHC
Type UPC		Mixed Layout 889056918442	Not Reviewed
UPC		889056918442	Halogen-Free
Physical			Status
Circuits (Loaded)		4	Not Reviewed
Circuits (maximum)		5	
Color - Resin		Green	For more information, please visit Contact US
Durability (mating cycles max)		500	China ROHS Not Reviewed
Gender		Male	ELV Not Relevant
Material - Contact		Copper Alloy	RoHS Phthalates Not Reviewed
Material - Resin		PBT	
Material - Shell		Steel	
Net Weight		8.300/g	
Number of Rows		0.300/g	Search Parts in this Series
Orientation		∠ Right-Angle	<u>173107</u> Series
PC Tail Length		11.10mm	
PCB Locator		No	Mates With
PCB Locator PCB Retention		None	FCT Mixed Layout D-Sub, Size 1, 5W1,
PCB Thickness - Recommended		1.60mm	Socket
Pob Thickness - Recommended Packaging Type		Carton	
Panel Mount		Rear	Use With
Panel Mount Method			FCT Coaxial, High Power, High Voltage, or
Pitch - Mating Interface		Flange 2.84mm	Pneumatic Contacts
Pitch - Termination Interface		2.54mm	
Plating - Contact	licitate	Gold over Nickel	
Plating - Shell		Tin	
Polarized to Mating F	Dort	Yes	
Polarized to Mating P	ail	Yes	
Ports		1	
Shielded		i Yes	
		-55° to +130°C	
Temperature Range	- Operaulig		
Termination Style Waterproof / Dustpro	of	Through Hole No	
Waterproof / Dustpro Waterproof / Dustpro		IP20	
Electrical			
Current - Maximum p	per Contact	7.5A	
Material Info			
Engineering Number		FM5W1P5-K120	

This document was generated on 07/28/2021 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for D-Sub Mixed Contact Connectors category:

Click to view products by Molex manufacturer:

Other Similar products are found below :

790-025SF-5P5NMN790-025SJ-7P7NMLDAM-7W2PCL717TWB5W5P3RL717TWB5W5PRM84L717TWP3W3P3003W3PXX56N40X3005W5PXX99E40X3005W5SXX99A30X3005W5SXX99E40X3013W6SCM99A10X3036W4PCM41A10X3036W4SCM99A10XFCE17-E2W2SS-2N0212522-7PII-468-13003W3PXX43A10X3003W3SXX56N40X3005W5PXX88N40X3007W2PAR71E20X3008W8SXX57A30X3009W4PCT57P20X3011W1SXK99A10X3017W2SAR69C40X321WA4PXK99A60X3F3SSC22S41A30XL717TWA7W2PP2SY3RDBM-17W2S-1A8N-A190-A197-1421WA4PCR50E20X09691009009096911000225000969300917609692009147096939090156017W2PCM41B30X790-061SH-36W2NMNA790-044SE-7P3MNPB790-043PE-11P2MPA790-043PB-2P2MPB790-029SB-2P2MEPA790-028PK-9P9MPA790-028PH-54P2MGA790-028PH-36P2MNA790-028PB-2P2MPA790-028PB-2P2MPA027SH-5W5MTEP790-026PH-54P2ZNUG790-026PH-54P2MP790-026PH-36P2ZNUG790-026PH-36P2MG790-026PD-3P3MP