

This document was generated on 07/26/2021 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: 1731090145 Status: Active Overview: FCT D-Sub Connectors Description: FCT Standard-Density D-Sub Connector, Female, Straight, PCB Through Hole, Gold Description: FCT Standard-Density D-Sub Connector, Female, Straight, PCB Through Hole, Gold Documents: RoHS Certificate of Compliance (PDF) Brochure (PDF) RoHS Certificate of Compliance (PDF)	
Overview: Description: FCT D-Sub Connectors FCT Standard-Density D-Sub Connector, Female, Straight, PCB Through Hole, Gold Plating, 500 Mating Cycles, 6.60mm Snap-in Bolt, 50 Circuits Documents: Datasheet (PDF) RoHS Certificate of Compliance (PDF)	
Description: FCT Standard-Density D-Sub Connector, Female, Straight, PCB Through Hole, Gold Plating, 500 Mating Cycles, 6.60mm Snap-in Bolt, 50 Circuits Documents: Documents: Datasheet (PDF) RoHS Certificate of Compliance (PDF)	
Datasheet (PDF) RoHS Certificate of Compliance (PDF)	i
Series	mage - Reference only
Series 173109 EU ELV ID Daties ID20 ID20 ID20	
IP Rating IP20 Not Relevant	
Overview FCT D-Sub Connectors EU RoHS Product Category D-Sub Connector EU RoHS	China RoHS
Product Name FCT Products Compliant wit	
Type Standard Density Exemption 6(c	
UPC 889056486279 REACH SVHC	
Contained Per	
Physical D(2020)4578-E	UC (25
Circuits (Loaded) 50 June 2020)	
Circuits (maximum) 50 lead	
Color - Resin White <u>Halogen-Free</u>	
Durability (mating cycles max) 500 <u>Status</u>	
Gender Female Not Reviewed	
Material - Contact Copper Alloy For more inform	nation, please visit Contact US
Material - Resin PBT	
Material - Shell Steel China ROHS	50 Image
Net Weight 21.800/g ELV	Not Relevant
Number of Rows 3 RoHS Phthalat	es Not Contained
Orientation Straight	
PC Tail Length 10.30mm	
PCB Locator Yes Search Parts	s in this Series
PCB Retention Yes <u>173109</u> Serie	
PCB Thickness - Recommended 1.60mm	
Packaging Type Carton	
Panel Mount Rear Mates With	d Danaita D Cult Cina 5 50
	d-Density D-Sub, Size 5, 50
Pitch - Mating Interface 2.84mm Position, Plug	J
Pitch - Termination Interface 2.84mm	
Plating - Contact Gold over Nickel	
Plating - Shell Tin	
Polarized to Mating Part Yes	
Polarized to PCB Yes	
Ports 1	
Shielded Yes	
Temperature Range - Operating -55° to +125°C	
Termination Style Through Hole	
Waterproof / Dustproof No	
Waterproof / Dustproof Type IP20	
Electrical	
Current - Maximum per Contact 7.5A	
Material Info	
Engineering Number F50S1G1-0982	

This document was generated on 07/26/2021 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for D-Sub Standard Connectors category:

Click to view products by Molex manufacturer:

Other Similar products are found below :

 56F711-015
 LV242999-142T12
 015-0341-000
 015-0372-005
 015-0372-008
 015-8755-001
 020419-0104
 012-0467-000
 012-9507-034
 012

 9507-114
 020745-0008
 609-25P
 CT2-14S-2PCA34
 CT2-18-11PCAU
 CT6-10SL-3SC
 CT6-10SL-4SC
 CT6-14S-2SC
 CT6E14SA7SC

 M83513/01-FC
 M83723/76W24619
 L/C
 M85049/48-3-2F
 6STD09PCM99B70X
 6STD09SCM99B30X
 6STD09SCT99S40X

 6STD15PCT99S40X
 6STD15SCM99B30X
 6STD15SCT99S40X
 6STF09PCM05B70X
 7-135760-9
 MC11E-10-6SN
 747552-3
 MD1-21PS

 MDM-15SCBRM7-F222
 MDM96517-699
 MDM96521-744
 MDVB1-21SL1
 MIK0-1-7SH003
 MIKQ6-7SH076
 MIKQ7-7PH077
 MIKQ7

 7PH11
 MIKQ7-7PH32
 MJSV-28SL61
 MKJ4A1F14-55S
 8-135760-3
 8STD09PCM99B30X
 PG-KV/PV-16-GROM-SEALING
 GDA15P

 GDAY15PB
 980-0000-170
 980-0000-171
 980-0000-171
 980-0000-171