

This document was generated on 07/28/2021 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Product NamePC DecisionProduct NameFCT ProductsTypeStandard DensityUPC889056486651PhysicalNot ReviewedCircuits (Loaded)25Circuits (Loaded)25Color - ResinWhiteDurability (mating cycles max)200CenterFemaleMaterial - ContactCopper AlloyMaterial - ShellSteelNet Weight16.000/gNumber of Rows2OrientationRight-AnglePC Tail Length11.10mmPCB LocatorYesPCB Thickness - Recommended1.60mmPackaging TypeCarton	
Overview: FCT D-Sub Connectors Description: FCT Standard-Density D-Sub Connector, Female, Right-Angle, PCB Through Hole, Gold Plating, 200 Mating Cycles, Riveted Metal Bracket and Clinch Nut, 25 Circuits Documents: Datasheet (PDF) Batasheet (PDF) RoHS Certificate of Compliance (PDF) Brochure (PDF) Brochure (PDF) General Product Family Product Category D-Sub Products Series 173109 IP Rating IP20 Overview FCT Products Product Category D-Sub Connector Product Category UPC Banasheet (PDF) Banasheet (PDF) Chiral (Loaded) 25 Circuits (maximum) 25 Color - Resin White Durability (Intating cycles max) 200 Gender Gender Material - Contact	
Description: FCT Standard-Density D-Sub Connector, Female, Right-Angle, PCB Through Hole, Gold Plating, 200 Mating Cycles, Riveted Metal Bracket and Clinch Nut, 25 Circuits Documents: Datasheet (PDF) Datasheet (PDF) RoHS Certificate of Compliance (PDF) Brochure (PDF) Series Product Family D-Sub Products Series 173109 IP Rating IP20 Overview ECT D-Sub Connectors Product Name FCT Poducts Type Standard Density Not Relevend ReACH SVHC Not Relevend Not Relevend Physical China Circuits (Loaded) 25 Color - Resin White Durability (mating cycles max) 200 Gender Female Material - Shell Steel Net Weight 16.000/g Number of Rows 2 Oriention Right-Angle PC Catator Yes PCB Retention Yes PCB Thickness - Recommended 1.60mm Packaging Type Carton	
Gold Plating, 200 Mating Cycles, Riveted Metal Bracket and Clinch Nut, 25 Circuits Documents: RoHS Certificate of Compliance (PDF) Brochure (PDF) RoHS Certificate of Compliance (PDF) Brochure (PDF) D-Sub Products Series 173109 IP Rating IP20 Overview FCT D-Sub Connectors Product Category D-Sub Connector Product Category D-Sub Connector Product Category Standard Density UPC 889056486651 Physical Clirouits (Loaded) Circuits (Loaded) 25 Color - Resin White Durability (mating cycles max) 200 Gender Female Material - Contact Copper Alloy Material - Shell Steel Net Weight 16.000/g Number of Rows 2 Orientation Right-Angle PC Tail Length 11.10mm PCB Trailen Tistomar PCB Trailen 1.60mm Pect Tail proper Carton	1 🐵
Documents: Datasheet (PDF) Brochure (PDF) RoHS Certificate of Compliance (PDF) General Product Family D-Sub Products Series 173109 IP Rating 172109 Overview FCT D-Sub Connectors Product Category D-Sub Connector Clore - Resin Vhite Durability (mating cycles max) 200 Color - Resin White Durability (mating cycles max) 200 Material - Shell Steel Nuterial - Shell Steel Number of Rows 2 Orientation Right-Angle PC Tail Length 11.10mm PCB Traile Category Yes PCB Trailer 1.60mm PCB Trailer 1.60mm	
Documents: RoHS Certificate of Compliance (PDF) General Series image - Reference Product Family D-Sub Products Series 173109 IP Rating IP20 Overview ECT D-Sub Connectors Product Category D-Sub Connector Product Arame FCT Products Type Standard Density UPC 889056486651 Physical Circuits (Loaded) Circuits (Loaded) 25 Corr - Resin White Durability (mating cycles max) 200 Oireuits (maximum) 25 Color - Resin White Durability (mating cycles max) 200 Material - Contact Copper Alloy Material - Shell Steel Number of Rows 2 Orientation Right-Angle PC Tail Length 11.10mm PC B Retention Yes PC B Thickness - Recommended 1.60mm Packaging Type Carton	<u> </u>
Datasheet (PDF) Brochure (PDF) RoHS Certificate of Compliance (PDF) General Product Family D-Sub Products Series 173109 IP Rating IP20 Overview FCT D-Sub Connectors Product Category D-Sub Connector Product Name FCT Products Type Standard Density UPC 899056486651 Physical Circuits (Loaded) Circuits (Loaded) 25 Color - Resin White Durability (mating cycles max) 200 Gender Female Material - Contact Copper Alloy Material - Resin PBT Material - Resin	
Brochure (PDE) Sories General D-Sub Products Product Family D-Sub Products Series 1/73109 IP Rating IP20 Overview FCT D-Sub Connectors Product Name FCT Products Type Standard Density UPC 889056486651 Physical Circuits (Loaded) Circuits (Loaded) 25 Color - Resin White Durability (mating cycles max) 200 Gender Female Material - Contact Copper Alloy Material - Shell Steel Number of Rows 2 Orientation Right-Angle PC Tail Length 11.10mm PCB Retention Yes PCB Retention Yes PCB Thickness - Recommended 1.60mm Packaging Type Carton	
General Series image - Reference Product Family D-Sub Products Series 173109 IP Rating IP20 Overview FCT D-Sub Connectors Product Category D-Sub Connector Product Name FCT Products Type Standard Density UPC 889056486651 Physical Not Reviewed Circuits (Loaded) 25 Color - Resin White Durability (mating cycles max) 200 Gender Female Material - Shell Steel Net Weight 16.000/g Number of Rows 2 Orientation Right-Angle PC B Retention Yes PCB Retention Yes PCB Thickness - Recommended 1.60mm Packaging Type Carton	
Product FamilyD-Sub ProductsSeries173109IP RatingIP20OverviewFCT D-Sub ConnectorsProduct CategoryD-Sub ConnectorProduct CategoryD-Sub ConnectorProduct NameFCT ProductsTypeStandard DensityUPC889056486651PhysicalCircuits (Loaded)Circuits (Loaded)25Color - ResinWhiteDurability (mating cycles max)200GenderFermaleMaterial - ContactCopper AlloyMaterial - ShellSteelNet Weight16.000/gNumber of Rows2OrientationRight-AnglePC B RetentionYesPCB Thickness - Recommended1.60mmPackaging TypeCarton	
Series173109EU ELVIP RatingIP20Not RelevantOverviewFCT D-Sub ConnectorsEU RoHSProduct CategoryD-Sub ConnectorNot ReviewedProduct NameFCT ProductsNot ReviewedTypeStandard DensityREACH SVHCUPC889056486651Not ReviewedPhysicalCircuits (Loaded)25Circuits (Loaded)25Not ReviewedCircuits (maximum)25For more information, please vDurability (mating cycles max)200China ROHSDurability (mating cycles max)200China ROHSMaterial - ContactCopper AlloyRoHS PhthalatesMaterial - ShellSteelSteelNet Weight16.000/gSearch Parts in this SeriesNumber of Rows22OrientationRight-AnglePCB LocatorYesPCB RetentionYesPCB RetentionYesPCB Thickness - Recommended1.60mmPackaging TypeCarton	ce only
IP RatingIP20Not RelevantOverviewFCT D-Sub ConnectorsEU RoHSChinaProduct CategoryD-Sub ConnectorNot ReviewedChinaProduct NameFCT ProductsREACH SVHCNot ReviewedTypeStandard DensityREACH SVHCNot ReviewedUPC889056486651Halogen-FreeStatusPhysical25Not ReviewedHalogen-FreeCircuits (Loaded)25Not ReviewedColor - ResinWhitePoper AlloyDurability (mating cycles max)200China ROHSNot ReviewedGenderFemaleELVNot ReviewedMaterial - ContactCopper AlloyRoHS PhthalatesNot ReviewedMaterial - ShellSteelSteelSearch Parts in this SeriesNumber of Rows2CorientationRight-AnglePC B LocatorYesYesCT Standard-Density D-SuPCB RetentionYesCartonPosition, PlugPackaging TypeCartonCartonPosition, Plug	
IP RatingIP20Not RelevantOverviewFCT D-Sub ConnectorsEU RoHSChinaProduct CategoryD-Sub ConnectorNot ReviewedChinaProduct NameFCT ProductsREACH SVHCNot ReviewedTypeStandard DensityREACH SVHCNot ReviewedUPC889056486651Not ReviewedHalogen-FreePhysical25Not ReviewedHalogen-FreeCircuits (Loaded)25Not ReviewedFor more information, please vColor - ResinWhiteDurability (mating cycles max)200China ROHSNot ReviewedGenderFemaleELVNot ReviewedELVNot ReviewedMaterial - ContactCopper AlloyRoHS PhthalatesNot ReviewedMaterial - ShellSteelSteelSteries173109 SeriesNumber of Rows2CorientationRight-AnglePCT Standard-Density D-Su PGB Thickness - Recommended1.60mmPosition, PlugPackaging TypeCartonYesCartonPosition, Plug	
OverviewFCT D-Sub ConnectorsProduct CategoryD-Sub ConnectorProduct NameFCT ProductsTypeStandard DensityUPC889056486651PhysicalCircuits (Loaded)Circuits (Loaded)25Color - ResinWhiteDurability (mating cycles max)200GenderFemaleMaterial - ContactCopper AlloyMaterial - ShellSteelNet Weight16.000/gNumber of Rows2OrientationRight-AnglePC B LocatorYesPC B RetentionYesPC B RetentionYesPC B Thickness - Recommended1.60mmPackaging TypeCarton	
Product CategoryD-Sub ConnectorEU RoHSChinaProduct NameFCT ProductsNot ReviewedTypeStandard DensityREACH SVHCUPC889056486651Not ReviewedPhysicalCircuits (Loaded)25Circuits (maximum)25StatusColor - ResinWhiteFor more information, please NDurability (mating cycles max)200China ROHSDurability (mating cycles max)200China ROHSMaterial - ContactCopper AlloyRoHS PhthalatesMaterial - ShellSteelSteelNumber of Rows2SteelVeight16.000/g11.10mmPCB LocatorYesPCB RetentionYesPCB RetentionYesPCB Thickness - Recommended1.60mmPackaging TypeCarton	
Product NameFCT ProductsNot ReviewedTypeStandard DensityREACH SVHCUPC889056486651Not ReviewedPhysicalNot ReviewedCircuits (Loaded)25Not ReviewedColor - ResinWhiteFor more information, please ofDurability (mating cycles max)200China ROHSNot ReviewedBurability (mating cycles max)200China ROHSNot ReviewedBurability (mating cycles max)200China ROHSNot ReviewedMaterial - ContactCopper AlloyRoHS PhthalatesNot ReviewedMaterial - ShellSteelSearch Parts in this SeriesNumber of Rows2Search Parts in this SeriesOrientationRight-Angle173109 SeriesPCB LocatorYesYesPCB RetentionYesPCB Thickness - Recommended1.60mmPackaging TypeCarton	RoHS
TypeStandard DensityREACH SVHCType889056486651Not ReviewedPhysicalCircuits (Loaded)25StatusCircuits (Loaded)25For more information, please vColor - ResinWhiteFor more information, please vDurability (mating cycles max)200China ROHSGenderFemaleELVMaterial - ContactCopper AlloyMaterial - ShellSteelNumber of Rows2OrientationRight-AnglePC Tail Length11.10mmPCB LocatorYesPCB RetentionYesPCB Thickness - Recommended1.60mmPackaging TypeCarton	
TypeNot ReviewedUPC889056486651Physical25Circuits (Loaded)25Circuits (maximum)25Color - ResinWhiteDurability (mating cycles max)200GenderFemaleMaterial - ContactCopper AlloyMaterial - ShellSteelNet Weight16.000/gNumber of Rows2OrientationRight-AnglePC Tail Length11.10mmPCB LocatorYesPCB RetentionYesPCB Thickness - Recommended1.60mmPackaging TypeCarton	
Halogen-Free StatusPhysicalHalogen-Free StatusCircuits (Loaded)25Not ReviewedCircuits (maximum)25For more information, please of Color - ResinDurability (mating cycles max)200China ROHSNot ReviewedGenderFemaleELVNot ReviewedMaterial - ContactCopper AlloyRoHS PhthalatesNot ReviewedMaterial - ResinPBTRoHS PhthalatesNot ReviewedMaterial - ShellSteelSearch Parts in this SeriesNumber of Rows2OrientationRight-AnglePC Tail Length11.10mmYesMates WithPCB LocatorYesYesMates WithPCB Thickness - Recommended1.60mmPosition, PlugPackaging TypeCartonCarton	
PhysicalStatusCircuits (Loaded)25Not ReviewedCircuits (maximum)25For more information, please ofColor - ResinWhiteFor more information, please ofDurability (mating cycles max)200China ROHSNot ReviewedGenderFemaleELVNot ReviewedMaterial - ContactCopper AlloyRoHS PhthalatesNot ReviewedMaterial - ResinPBTRoHS PhthalatesNot ReviewedNet Weight16.000/gSearch Parts in this SeriesNumber of Rows2T3109 SeriesOrientationRight-AnglePC Tail Length11.10mmPCB LocatorYesPCB Thickness - Recommended1.60mmPackaging TypeCarton	
Circuits (Loaded)25Not ReviewedCircuits (maximum)25For more information, please ofColor - ResinWhiteChina ROHSNot ReviewedDurability (mating cycles max)200China ROHSNot ReviewedGenderFemaleELVNot ReviewedMaterial - ContactCopper AlloyRoHS PhthalatesNot ReviewedMaterial - ResinPBTSteelRoHS PhthalatesNot ReviewedNet Weight16.000/gSearch Parts in this Series173109 SeriesNumber of Rows2OrientationRight-Angle173109 SeriesPC Tail Length11.10mmFCT Standard-Density D-Su PCB RetentionYesMates With FCT Standard-Density D-Su Position, PlugPackaging TypeCartonCartonSearchStandard-Density D-Su Position, Plug	
Circuits (maximum)25For more information, please of Color - ResinDurability (mating cycles max)200China ROHSNot RevGenderFemaleELVNot RevMaterial - ContactCopper AlloyRoHS PhthalatesNot RevMaterial - ResinPBTSteelRoHS PhthalatesNot RevNet Weight16.000/gSearch Parts in this Series173109 SeriesNumber of Rows2OrientationRight-AnglePC Tail Length11.10mmYesMates WithPCB RetentionYesPosition, PlugPCB Thickness - Recommended1.60mmPosition, Plug	
Color - ResinWhiteColor and an analysis, product ofDurability (mating cycles max)200China ROHSNot RevGenderFemaleELVNot RevMaterial - ContactCopper AlloyRoHS PhthalatesNot RevMaterial - ResinPBTRoHS PhthalatesNot RevMaterial - ShellSteelSteelSearch Parts in this SeriesNumber of Rows2OrientationRight-AnglePC Tail Length11.10mmYesMates WithPCB RetentionYesFCT Standard-Density D-SuPCB Thickness - Recommended1.60mmPosition, PlugPackaging TypeCartonCarton	
Durability (mating cycles max)200China ROHSNot RevGenderFemaleELVNot RevMaterial - ContactCopper AlloyRoHS PhthalatesNot RevMaterial - ResinPBTMaterial - ShellSteelNet Weight16.000/gNumber of Rows2OrientationRight-AnglePC Tail Length11.10mmPCB RetentionYesPCB Thickness - Recommended1.60mmPackaging TypeCarton	sit Contact US
GenderFemaleELVNot RelMaterial - ContactCopper AlloyRoHS PhthalatesNot RelMaterial - ResinPBTSteelRoHS PhthalatesNot RelNet Weight16.000/gSearch Parts in this Series173109 SeriesNumber of Rows211.10mmMates WithFCT Standard-Density D-SuPCB RetentionYesYesFCT Standard-Density D-SuPCB Thickness - Recommended1.60mmPosition, Plug	louro d
NoticePointiceRoHS PhthalatesNot RevMaterial - ContactCopper AlloyRoHS PhthalatesNot RevMaterial - ResinPBTMaterial - ShellSteelNet Weight16.000/gNumber of Rows2OrientationRight-AnglePC Tail Length11.10mmPCB LocatorYesPCB RetentionYesPCB Thickness - Recommended1.60mmPackaging TypeCarton	
Material - ResinPBTMaterial - ShellSteelNet Weight16.000/gNumber of Rows2OrientationRight-AnglePC Tail Length11.10mmPCB LocatorYesPCB RetentionYesPCB Thickness - Recommended1.60mmPackaging TypeCarton	
Material - ShellSteelNet Weight16.000/gNumber of Rows2OrientationRight-AnglePC Tail Length11.10mmPCB LocatorYesPCB RetentionYesPCB Thickness - Recommended1.60mmPackaging TypeCarton	lewed
Net Weight16.000/gSearch Parts in this SeriesNumber of Rows2173109 SeriesOrientationRight-Angle173109 SeriesPC Tail Length11.10mmMates WithPCB LocatorYesFCT Standard-Density D-SuPCB RetentionYesPosition, PlugPCB Thickness - Recommended1.60mmPosition, PlugPackaging TypeCartonFCT Standard-Density D-Su	
Number of Rows2173109 SeriesOrientationRight-Angle173109 SeriesPC Tail Length11.10mmMates WithPCB LocatorYesFCT Standard-Density D-SuPCB RetentionYesPosition, PlugPCB Thickness - Recommended1.60mmPosition, PlugPackaging TypeCartonPosition, Plug	
Number of Rows2173109 SeriesOrientationRight-Angle173109 SeriesPC Tail Length11.10mmMates WithPCB LocatorYesFCT Standard-Density D-SuPCB RetentionYesPosition, PlugPCB Thickness - Recommended1.60mmPosition, PlugPackaging TypeCartonPosition, Plug	
OrientationRight-AnglePC Tail Length11.10mmPCB LocatorYesPCB RetentionYesPCB Thickness - Recommended1.60mmPackaging TypeCarton	
PC Tail Length11.10mmMates WithPCB LocatorYesFCT Standard-Density D-SuPCB RetentionYesPCB Thickness - Recommended1.60mmPCB Thickness - Recommended1.60mmPosition, PlugPackaging TypeCartonPosition, Plug	
PCB LocatorYesMates WithPCB RetentionYesFCT Standard-Density D-SuPCB Thickness - Recommended1.60mmPosition, PlugPackaging TypeCartonFCT Standard-Density D-Su	
PCB Retention Yes FC1 Standard-Density D-Su PCB Thickness - Recommended 1.60mm Position, Plug Packaging Type Carton	
PCB Thickness - Recommended 1.60mm Position, Plug Packaging Type Carton	o, Size 3, 25
Packaging Type Carton	
Papal Mount Page	
Panel Mount Rear	
Panel Mount Method Thread-In	
Pitch - Mating Interface 2.84mm	
Pitch - Termination Interface 2.54mm	
Plating - Contact Gold over Nickel	
Plating - Shell Tin	
Polarized to Mating Part Yes	
Polarized to PCB Yes	
Ports 1	
Shielded Yes	
Temperature Range - Operating -55° to +125°C	
Termination Style Through Hole	
Waterproof / Dustproof No	
Waterproof / Dustproof Type IP20	
Electrical	
Current - Maximum per Contact 7.5A	
Material Info	
Engineering Number F25S5G2-1002	

This document was generated on 07/28/2021 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for D-Sub Standard Connectors category:

Click to view products by Molex manufacturer:

Other Similar products are found below :

 56F711-015
 LV242999-142T12
 015-0341-000
 015-0372-005
 015-0372-008
 015-8755-001
 020419-0104
 012-0467-000
 012-9507-034
 012

 9507-114
 020745-0008
 609-25P
 CT2-14S-2PCA34
 CT2-18-11PCAU
 CT6-10SL-3SC
 CT6-10SL-4SC
 CT6-14S-2SC
 CT6E14SA7SC

 M83513/01-FC
 M83723/76W24619
 L/C
 M85049/48-3-2F
 6STD09PCM99B70X
 6STD09SCM99B30X
 6STD09SCT99S40X

 6STD15PCT99S40X
 6STD15SCM99B30X
 6STD15SCT99S40X
 6STF09PCM05B70X
 7-135760-9
 MC11E-10-6SN
 747552-3
 MD1-21PS

 MDM-15SCBRM7-F222
 MDM96517-699
 MDM96521-744
 MDVB1-21SL1
 MIK0-1-7SH003
 MIKQ6-7SH076
 MIKQ7-7PH077
 MIKQ7

 7PH11
 MIKQ7-7PH32
 MJSV-28SL61
 MKJ4A1F14-55S
 8-135760-3
 8STD09PCM99B30X
 PG-KV/PV-16-GROM-SEALING
 GDA15P

 GDAY15PB
 980-0000-170
 980-0000-171
 980-0000-171
 980-0000-171